

1

2


3

4

5

6

7



Solid Block
02 2 CONTACTS
03 3 CONTACTS
...
24 24 CONTACTS



TY xx 01 x 0 xxxx G $\triangle_6$

G RoHS compliant
(lead<4%)
In copper Alloy

0000:"@ "Logo (Standard)
000A:"ANYTEK"Logo
Any special item by
customer request,
please contact sales
department.

0 Black (RAL9005)
2 Red (RAL3001/D)
3 Orange(RAL2011/P)
4 Yellow(RAL1018/A)
5 Green(RAL6018/T)
6 Blue (RAL5015/A)
8 Grey(RAL7035/D)
9 White(RAL1102)
C Green(RAL6018/U)

$\phi 3.60$ (Screw hole diameter)



SECTION C-C



Dimension

Dim L	N×5.0
Dim B	(N-1)×5.0

N= Number of poles

Poles	Tolerance
2P-6P	±0.15
7P-12P	±0.20
13P-18P	±0.25
19P-24P	±0.30

SIGN	DATE	DESCRIPTION	APPROVER
$\triangle_6$	2008.12.02	Add the tolerance table	Jacke
$\triangle_6$	2008.12.02	Add the inspection dimension	Jacke
$\triangle_6$	2008.12.02	The temperature changed from -30°C, +105°C to -40°C, +115°C	Jacke
$\triangle_6$	2008.12.16	The dimension changed from 1.1mm to 1.06mm+0.05/-0	Jacke
$\triangle_6$	2009.04.19	Add TUV standard	Jacke
$\triangle_6$	2013.11.19	Update the drawing	Chen Bo

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

Material

- Item (a) Terminal body (metal housing): Brass (Cu Zn)
- Item (b) Terminal screw: Steel Zinc plating "-" slot type
- Item (c) Wire guard: PhBz, tin plated
- Item (d) Terminal (housing): Thermoplastic (UL94V-0)

Electrical cULus TUV

- Voltage rating: 300VAC /300VAC
- Current rating: 10A /10A
- Wire range: 0.2-2.5mm
- Solid wire(AWG): 14-26/14-26
- Stranded wire(AWG): 14-26/14-26
- Torque: 3.5Lb-In /0.4Nm
- Screw: M2.6
- Wire strip length: 6-7mm
- Withstanding Voltage: 1.6KV/2.5KV
- Operating temperature: -40°C to +115°C
- Safety Approval: cULus $\triangle_{10V}$
- Critical dimension: $\triangle_6$

ANYTEK

CUSTOMER COPY

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE	TY-5.0mm Series (two beam contact)						
PART NO.	TYxx01x0xxxxG			DWG NO.	8TY0001		
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.			Tolerance
		Chen Bo 11/19`13	Chen Bo 11/19`13		UNIT: mm	X.	±0.50
					SCALE: NONE	X.X	±0.30
				SHEET: 01/01	REV.: E	X.XX	±0.10
						X°	±1°

1

2

3

4

5

6

7