





Rev.	SIGN	DATE	DESCRIPTION	APPROVER
D	△	10/17'08	Add APPROVAL: : CQC	Kind
E	△	3/5'09	The terminal material changed from Brass to PHBZ.	Kind
F	△	4/17'09	Explanation changed	Eris
G	△	06/04`11	Critical dimension is changed.	Tason
H	△	06/04`11	The Wire Range is changed from 20-14AWG to 22-14AWG	Tason
	△	06/04`11	The tolerance table is changed.	Tason
I	△	06/16`11	The dimension is changed from 5.55 to 5.5	Tason
	△	06/16`11	The dimension is changed from (5.6) to (5.5)	Tason
	△	06/16`11	The dimension is changed from 1.6 to 1.5	Tason
J	△	11/10'12	Change the screw plating specification	Jacky
K	△	12/19'13	Change the withatand voltage , current,Screw Torque.	Jacky
L	△	05/08'17	Add the TUV electrical.	Guoxue

THIS IS CAD DRAWING, DO NOT REVISE MANUALL Y!!!



N = Number of poles
Dim A=Nx9.5+1.5
Dim B=(N-1)x9.5

Poles	Tol.	Dim A&B
2-4p		±0.20
5-8p		±0.25
9-16p		±0.35
17-23p		±0.40
24-30p		±0.50

MATERIALS ELECTRICAL	cULus	CQC	TUV
③ RATED VOLTAGE & CURRENT:	300 V, 30A	/ 300V 24A	③ 300V 24A
WITHSTAND VOLTAGE:	AC2500V/min		③ AC2500V/min
INSULATION RESISTANCE:	1000 MΩ		③ MORE AT DC 500 V
OPERATING TEMPERATURE RANG:	-40 °C ~ +115 °C		
SCREW TORQUE VALUE:	10.54 Lb-In.	/ 0.8Nm	③ 1.2N.m
③ WIRE RANGE:	22 - 10 AWG	/ 22-14 AWG	⑤ 0.34-2.5mm ²
1) MOLDED PARTS:	Thermoplastic, UL 94 V-0 BLACK		
③ ② 2) TERMINAL:	BRASS, 0.8t.		
③ ③ 3) TERMINAL SCREWS:	STEEL, M3.5		
④ Critical dimension:			
③ ① APPROVAL:	cULus	CQC	TUV
PART NO.:			

YK 441 xx 0 x x 00G

NO. OF POLES	RoHS compliant (lead<4%) In copper Alloy
02: 2 POLES	MARK
03: 3 POLES	0: "@" MARK
04: 4 POLES	1: "ANY" MARK
...	
30: 30 POLES	
TERMINAL & SCREW PLATED	
③ 0: TERMINAL & SCREW: G/F	
③ 1: TERMINAL: G/F, SCREW: Zinc	
③ 2: TERMINAL: Sn, SCREW: G/F	
③ 3: TERMINAL: Sn, SCREW: Zinc	

Amphenol ANYTEK				CUSTOMER COPY ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD			
TITLE	YK-441 Series						
PART NO.	YK441xx0xx00G			DWG NO.	8YK0001-441		
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.			Tolerance
		Guoxue 2017.05.08	Guoxue 2017.05.08				UNIT: mm
					SCALE: NONE		X.X ±0.30
				SHEET: 01/01	REV.: L		X.XX ±0.10
							X° ±1°