


THESE DRAWINGS ARE THE PROPERTY OF QUALTEK ELECTRONICS AND NOT TO BE REPRODUCED FOR OR COMMUNICATED TO A THIRD PARTY WITHOUT THE EXPRESS WRITTEN PERMISSION OF AN OFFICER OF QUALTEK ELECTRONICS.

REVISION			
REV.	DESCRIPTION	DATE	APPROVED
B	Updated Specifications	02-09-12	LY



P/N: 3021029-16
USB 4P(A)/M-BLUNT CUT
Length:16 FT
Color:Black

NOTES:

- CABLE: UL2725 20/26AWG
26AWGx1P+20AWGx2C+ AEB(AL) 65%
OUTER JACKET: BLACK, OD: $5.3 \pm 0.2\text{mm}$
- CONNECTOR: USB A TYPE MALE
INSULATOR: WHITE PBT
PIN G/F
GOLD PLATED SHELL
- BLUNT CUT
- PVC MOLDED: COLOR V398 45P BLACK
- ELECTRICAL TEST:
<1>.100% OPEN SHORT & MISS WIRE TEST
<2>.INSULATION RESISTANCE: DC400V 10M ohm MIN.
<3>.CONDUCTOR RESISTANCE: 3 ohm MAX.
- PACKING: 1PC/POLYBAG W/ LABEL

CONTROLLED

Dim range (mm)		Qualtek Electronics Corp. WCI DIVISION		
		Part Number:	3021029-16	RoHS Compliant
0-1	0.15	Description: USB 4P(A)/M - BLUNT CUT		
1-6	0.20			
6-18	0.30	Drawn / Date B.Grubb 01-26-07	UNIT: mm Checked / Date 01-26-07	REV. B Approved / Date JJH / 01-26-07
18-50	0.50			
50-120	0.70			
120-250	0.90			
250-500	1.20			