

MC21605G6W-SPTLY3.3-V2	2 x 16	5mm Character Height	LCD Module
Specification			
Version: 1		Date: 12/03/2021	
Revision			
1	10/03/2021	First Issue	

Display Features			
Character Count	2 x 16		
Appearance	Black on Yellow/Green		
Logic Voltage	3.3V		
Interface	Parallel		
Font Set	English / Japanese		
Display Mode	Transflective		
Character Height	5.23mm		
LC Type	STN		
Module Size	80.00 x 36.00 x 13.50 mm		
Operating Temperature	-20°C ~ +70°C		
Construction	COB		
LED Backlight	Yellow/Green	Box Quantity	Weight / Display

* - For full design functionality, please use this specification in conjunction with the ST7066U + ST7065C specification. (Provided Separately)

Display Accessories	
Part Number	Description
MCCMDB-16SIL	LCD Interconnect board, can be driven from either a PC or a single Board computer with a USB output.
MCCBL1A16SLIP-16DILS-150	16 Way, Single in-line to Dual In-line connector Cable.
MCCBL1A16SLIP-16SILS-150	16 Way, Single in-line to Single In-line connector Cable.

Optional Variants		
Fonts	Appearances	Voltage
English/Euro English/Cyrillic	White on Blue Black on White Black on RGB	3V 5V

FEATURES

AVAILABLE OPTIONS	CHARACTERISTICS
a f p m i ^ v = d o j ^ q	16 Characters by 2 Lines
m l i ^ o f w b o = l m q f l k p	Positive Transflective
_ ^ ` h i f d e q = q v m b = l m q f l k p	Edge Type LED Backlight (Long life span version)
_ ^ ` h i f d e q = ` l i l o = l m q f l k p	Yellow-Green color
i ` a = m ^ k b i = l m q f l k p	Yellow-Green STN
s f b t f k d = ^ k d i b = l m q f l k p	6:00 (Bottom)
q b j m b o ^ q r o b = o ^ k d b = l m q f l k p	-20°C ~ 70°C, Single Supply Voltage
p r d d b p q b a = a o f s f k d = s l i q ^ d b	V _{lcm} = 3.3V V _{led} = 3.3V
p r d d b p q b a = i b a = a o f s f k d = j l a b	PIN15: LED+, PIN16: LED-
` l k q o l i i b o	ST7066U+ST7065C
c l k q = j ^ m ` l a b	E Version
a o f s f k d = a r q v	1/16
a o f s f k d = _ f ^ p	1/5

MECHANICAL SPECIFICATIONS

OVERALL SIZE	80.0W x 36.0H	mm	THICKNESS	max 13.5	mm
VIEWING AREA	64.5W x 16.4H	mm	HOLE-HOLE	75.0W x 31.0H	mm
CHARACTER SIZE	3.00W x 5.23H	mm	CHARACTER PITCH	0.51W x 0.52H	mm
DOT SIZE	0.56W x 0.61H	mm	DOT PITCH	0.05W x 0.05H	mm

ABSOLUTE MAXIMUM RATINGS

ITEM	SYMBOL	CONDITION	MIN	TYP	MAX	UNIT
m l t b o = p r m m i v = E ^ i d f ^ F	s ÇÇ	OR = `	-0.3	—	7.0	V
m l t b o = p r m m i v = E ^ a F	s M	OR = `	V _{dd} -13.5	—	V _{dd} +0.3	V
f k m r q = s l i q ^ d b	s ää	OR = `	-0.3	—	V _{dd} +0.3	V
l m b o ^ q f k d = q b j m b o ^ q r o b	s ç éê	—	-20	—	70	°C
p q l o ^ d b = q b j m b o ^ q r o b	s ëíÖ	—	-30	—	80	°C





ELECTRONIC CHARACTERISTICS

	ITEM	SYMBOL	CONDITION	MIN	TYP	MAX	UNIT
	f k m r q = s l i q ^ d b	s ÇÇ	—	—	3.3	—	V
	p r m m i v = ` r o o b k q	f ÇÇ	V _{dd} =3.3V	—	1.5	—	mA
	a o f s f k d = s l i q ^ d b c l o = ` a = m ^ k b i	s äÄZEsÇÇsMF	-20°C	—	—	—	V
			0°C	—	—	—	
			25°C	—	—	—	
			50°C	—	—	—	
			70°C	—	—	—	

LCD CHARACTERISTICS

FOR STN/FSTN TYPE LCD Panel (TA=25 °C, Vlcd=5.0V ± 0.5V)

ITEM	SYMBOL	CONDITION	MIN	TYP	MAX	UNIT
sfbt fkd= k di b	$\Phi_2 \text{ } \Phi_1$	K=4	40	—	—	deg
	θ		60			
` l k qo ^ p q = o ^ q fl	K	—	6	—	—	—
o b p m l k p b = q f j b E o f p b F	To	—	—	150	250	ms
o b p m l k p b = q f j b E ^ i i F	Tc	—	—	150	250	ms




LED CHARACTERISTICS

ITEM	SYMBOL	CONDITION	MIN	TYP	MAX	UNIT
i ba=cl ot ^ oa=sl i q ^ d b	s Ñ	25 °C If = 5mA	—	3.0	—	V
i ba=cl ot ^ oa= ` r o o b k q	f Ñ	25 °C	—	5	—	mA
i ba=obsbopb= ` r o o b k q	f ê	25 °C Vr= 5V	—	—	10	µA
i ba=nb ^ h=t ^ s b=i b k d q e	λ é	25 °C If = 5mA	569	—	575	nm
i ba=_ ofdeqk b p p = f q e l r q ð ` a F	i î	25 °C If = 5mA	—	125	—	cd/m ²
i ba=_ ofdeqk b p p = f k f c l o j f q v	i î ã ä ü î ã ~ ñ	25 °C If = 5mA	70	—	—	Ratio
i ba=i f c b = q f j b	—	25 °C If = 5mA	20K	—	—	Hours


PIN ASSIGNMENT

PIN	SYMBOL	DESCRIPTION	REMARKS
1	Vss	GND	
2	Vdd	Power supply for LCM	3.3V
3	NC	No connection	
4	RS	Register Select Signal	
5	R/W	Data Read / Write	
6	E	Enable Signal	
7	DB0	Data bus line	
8	DB1	Data bus line	
9	DB2	Data bus line	
10	DB3	Data bus line	
11	DB4	Data bus line	
12	DB5	Data bus line	
13	DB6	Data bus line	
14	DB7	Data bus line	
15	LED+	Power supply for BKL	3.3V
16	LED-	Power supply for BKL	

BLOCK DIAGRAM



POWER SUPPLY DIAGRAM



r ééÈè QÄä QÄä	iiii	iiie	iiiei	iiiee	ieiii	ieiee	ieeii	ieeee	eiiii	eiiee	eieii	eieee	eeiii	eeiee	eeeee	eeee
iiii	d o^j ENF															
iiie	EOF															
iiiei	EPF															
iiiee	EOF															
ieiii	EPF															
ieiee	ESF															
ieeii	ETF															
ieeee	EUF															
eiii	ENF															
eiie	EOF															
eiei	EPF															
eiee	EOF															
eeii	EPF															
eeie	ESF															
eeei	ETF															
eeee	EUF															

