

Type 0ACA

Power Battery Packs Protection Series

HF  0ACA Series

RoHS Compliant

Features

- Surface mount design to save space, 2410 SMD
- Ceramic square body with Silver plated end cap
- Compatible with 260°C, IR Pb-free solder process
- Wide operating temperature range, -55°C to 125°C
- Tape & Reel for auto-insert SMD process
- Designed to UL248-1
- Fully compliance with EU Directive 2011/65/EU and amending directive 2015/863
- Fully compatible with lead-free solder and high temperature profile associated with lead-free assembly
- pass internal reliability performance and applicable for low duty application (bicycle etc.)

HALOGEN FREE = 
LEAD FREE = 

Applications

- E-Bike
- E-Motor
- e Robot sweeper
- Power Tools



Physical Specifications

Materials	Body : Ceramic
	Cap : Silver plated copper
Marking	On Fuse :
	"Current Rating"
	On Label :
	"bel", "0ACA", "Current Rating", "Voltage Rating", "Interrupting Rating", and "  " (China RoHS compliant).

Electrical Characteristics

% of Ampere Rating (A)	Operating Time	
	Min	Max
100%	4hours	-
200%	-	60sec

Ratings

Safety Agency	Ampere Rating / Voltage Rating	Ampere Range / Volt @ I.R. ability*
	20-30A / 72V DC 40A / 63V DC	20-30A / 72V @ 500A DC 40A / 63V @ 500A DC
*I.R.=DC Interrupting Rating		

Electrical Specifications

Part Number	Ampere Rating	Voltage and Interrupting Ratings	Typical Cold. Resistance (mohms)	Typical Voltage Drop (mV)	Typical Pre-Arcing I ² t (A ² Sec)*
0ACA-9200-XX	20A	See Table of Ratings on Page 1 for Voltage and associated Interrupting Ratings	2.3	60	210
0ACA-9250-XX	25A		1.7	55	400
0ACA-9300-XX	30A		1.2	50	900
0ACA-9400-XX	40A		0.9	50	1600


Consult manufacturer for other ratings
*Typical Pre-arcing I²t are measured at 10In Current.

Temperature Re-Rating Curve

Normal Operating Temperature: $25^{\circ}\text{C} \pm 2^{\circ}\text{C}$


Operating Temperature: -55°C to 125°C with proper correction factor applied.

Chart of correction factor



Storage Temperature: -55°C to 125°C

Average Time Current Curve



Soldering Characteristics

Wave Immersion

- Reservoir Temperature: 260°C
- Time in Reservoir : 10 Seconds Maximum

Infrared Reflow

- Temperature: 260°C
- Time: 30 Seconds Maximum

Hand Soldering (not recommended)

- Maximum tip temperature: 350°C
- Maximum soldering time: 5 seconds max

Type 0ACA


Fuse FGNO Explanation

0ACA - [XXXX] -XX

0ACA=0ACA; [XXXX]=Ampere Rating; XX=See Ordering Information as below

Decimal	Amps	Bel FGNO[XXXX]
20	20	9200
25	25	9250
30	30	9300
40	40	9400

Mechanical Dimensions



Ordering Information

	0ACA	-	XXXX	-	XX
FUSE TYPE					
0ACA = 0ACA					
AMPERE RATING					
Refer to fuse FGNO explanation table					
QUANTITY & PACKAGING CODE					
TE = 1000pcs fuses in tape (width 12mm) and reel (dia. 7inch)					

Packaging

Packaging Option	Quantity	Packaging Code
Tape (width 12mm) and reel (dia. 7inch)	1000	TE