


P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	RELEASED FOR PRODUCTION	06AUG2019	RK	PS

- NOTES:
1. MATERIALS & FINISH
HOUSING : PA66, UL94 V0, COLOR - GREEN
PUSH BUTTON : PA66, COLOR - ORANGE.
CONTACT : COPPER ALLOY, TIN PLATED
SPRING : STAINLESS STEEL
2. MECHANICAL
WIRE STRIPPING LENGTH : 12-13 mm
3. ELECTRICAL
WIRE RANGE : 12-26 AWG
RATED VOLTAGE : 300V
RATED CURRENT : 16A
INSULATION RESISTANCE : >2000 M Ohm (500V DC)
4. OPERATING TEMPERATURE RANGE : -40°C TO +105°C
-  TOLERANCE NOT CUMULATIVE

80.0	16	1-2350397-6
75.0	15	1-2350397-5
70.0	14	1-2350397-4
65.0	13	1-2350397-3
60.0	12	1-2350397-2
55.0	11	1-2350397-1
50.0	10	1-2350397-0
45.0	9	2350397-9
40.0	8	2350397-8
35.0	7	2350397-7
30.0	6	2350397-6
25.0	5	2350397-5
20.0	4	2350397-4
15.0	3	2350397-3
10.0	2	2350397-2
DIM A	NO. OF POS	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN 08APR2019 RAGHAVENDRA.K	 TE Connectivity		
		CHK 01JUL2019 KARTHIK.JK			
		APVD 02JUL2019 PRASHANTH.S			
		PRODUCT SPEC			
DIMENSIONS: mm		TOLERANCES UNLESS OTHERWISE SPECIFIED:		NAME SPRING FEMALE PLG, GREEN 5.00mm PITCH	
		0 PLC ± 1 PLC ± 2 PLC ± 3 PLC ± 4 PLC ± ANGLES ±		APPLICATION SPEC	
MATERIAL SEE NOTES		FINISH SEE NOTES		WEIGHT	
-		-		-	
CUSTOMER DRAWING			SIZE A3	CAGE CODE 00779	DRAWING NO C-2350397
			SCALE 3:1	SHEET 1 OF 1	REV A

