






LOC	DIST	REVISIONS			
		P	LTR	DESCRIPTION	DATE
HB	-	E1		ADDED TUBE PACKAGE P/N 1461405-8, ECO-20-008189	17JUN2020



CONNECTION FIGURE




FIGURE FOR PRINTED CIRCUIT BOARD PROCESSING
(BOTTOM VIEW)

THIS DRAWING IS A CONTROLLED DOCUMENT.			DWN	H.Sasaki	-	 TE Connectivity						
			CHK	Y.Oikawa	-							
DIMENSIONS: mm		TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD	A.Nagai	-	NAME					
		0 PLC ± -		PRODUCT SPEC		OJ-SH-HM SPEC,000 CUSTOMER DRAWING						
		1 PLC ± -		-								
		2 PLC ± -		APPLICATION SPEC								
		3 PLC ± -		-								
4 PLC ± -		ANGLES ± -										
MATERIAL		FINISH		WEIGHT		-	SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO		
-		-					A3	00779	C= 1461405	-		
CUSTOMER DRAWING							SCALE	5:1	SHEET	1 of 2	REV	E1

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

© COPYRIGHT - By - TE CONNECTIVITY

ALL RIGHTS RESERVED.

LOC

DIST

REVISIONS

HB

-

P

LTR

DESCRIPTION

DATE

DWN

APVD

-

SEE SHEET 1

-

-

-

E1

1461405-8	OJ-SH-112HM,000T0	107-84030	12V	OJ-SH-112HM	h
1461405-4	OJ-SH-148HM, 000	107-79010	48V	OJ-SH-148HM	g
1461405-6	OJ-SH-124HM, 000	107-79010	24V	OJ-SH-124HM	f
1461405-5	OJ-SH-112HM, 000	107-79010	12V	OJ-SH-112HM	e
1461405-2	OJ-SH-109HM, 000	107-79010	9V	OJ-SH-109HM	d
1461405-1	OJ-SH-106HM, 000	107-79010	6V	OJ-SH-106HM	c
1461405-3	OJ-SH-105HM, 000	107-79010	5V	OJ-SH-105HM	b
1461405-7	OJ-SH-103HM, 000	107-79010	3V	OJ-SH-103HM	a
PART NO	DESCRIPTION	PACKAGE SPEC.	PART B	PART A	TYPE

RELAY TYPE

		UV RESIN	SEAL (VENT HOLE)	16
		EPOXY RESIN	SEAL (BASE & BOBBIN)	15
		3UEW	MAGNETIC WIRE	14
94V-0		P.B.T	CASE	13
94V-0		P.B.T	BASE	12
94V-0		P.B.T	BOBBIN	11
	SOLDER DIP	C.P WIRE	COIL TERMINAL	10
94V-0		P.P.S	CARD	9
		Ag ALLOY	MOVABLE CONTACT	8
		Ag	NO.CONTACT	7
		STEEL	HINGE SPRING	6
	SOLDER DIP	PBP	NO.TERMINAL	5
	SOLDER DIP	Cu ALLOY	MOVABLE SPRING	4
	NIP	STEEL	CORE	3
	NIP	STEEL	ARMATURE	2
	NIP	STEEL	YOKE	1
INCOMBUSTIBILITY	TREATMENT	MATERIAL	DESCRIPTION	ITEM

NOTES:

1.LOT NO. SYSTEM AS FOLLOWING:

5.ADD LOT NO. SYSTEM AS FOLLOWING:

1

1

A

I, DIGITS FOR DAY OF THE WEEK

1...MONDAY IN THIS WEEK;

2...TUESDAY IN THIS WEEK;

.....

7...SUNDAY IN THIS WEEK

II, DIGITS FOR SHIFT OF THE DAY

1...DAY SHIFT IN THIS DAY;

2...NIGHT SHIFT IN THIS DAY;

III, ONE CHARACTER DISTINGUISH THE LINE IDENTITY,

SUCH AS: A,B.....Z

2.TERMINAL DIMENSION IS BEFORE SOLDER DIP;

3.FOR THE TIN-PLATING OF THE PINS:

+0.1mm FOR WIDTH,THICKENSS AND DIAMETER.

+0.5mm FOR LENGTH.

4.MARKING FROM INK TO LASER AND WELDED CONTACT

Diagram dimension

Tolerance

0.99mm max.

±0.1mm

1 - 2.99mm

±0.2mm

3mm min.

±0.3mm

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN

H.Sasaki

CHK

Y.Oikawa

APVD

A.Nagai

PRODUCT SPEC

APPLICATION SPEC

WEIGHT

CUSTOMER DRAWING

DIMENSIONS:

mm

0 PLC ± -

1 PLC ± -

2 PLC ± -

3 PLC ± -

4 PLC ± -

ANGLES ± -

TOLERANCES UNLESS OTHERWISE SPECIFIED:

± -

± -

± -

± -

± -

± -

MATERIAL

FINISH

-

-

TE

TE Connectivity

NAME

OJ-SH-HM SPEC,000 CUSTOMER DRAWING

SIZE

CAGE CODE

DRAWING NO

RESTRICTED TO

A3

00779

C=

1461405

-

CUSTOMER DRAWING

SCALE

SHEET

REV

5:1

2 of 2

E1

1470-19 (3/11)