

## Modular Signal Towers / KombiSIGN 72

**TwinLIGHT Classic 24VAC/DC RD**


|           |              |
|-----------|--------------|
| Part No.: | 647.110.75   |
| Series:   | KombiSIGN 72 |


**MECHANICAL DATA**

|                             |       |
|-----------------------------|-------|
| Height                      | 66 mm |
| Diameter                    | 70 mm |
| Materials                   | PC    |
| Dome colour                 | Red   |
| Protection category         | IP65  |
| Working temperature minimum | -30°C |
| Working temperature maximum | +60°C |
| Weight with packaging       | 91 g  |
| Product weight              | 77 g  |

**ELECTRICAL DATA**

|                             |                    |
|-----------------------------|--------------------|
| Operating voltage           | 24V                |
| Operating voltage type      | AC/DC              |
| Operating voltage frequency | 50Hz               |
| Operating voltage tolerance | +/- 10%            |
| Rated operational voltage   | 24 VDC             |
| Rated operational current   | 80 mA              |
| Rated inrush current        | 500 mA             |
| Protection class            | Protection class 2 |
| Pollution degree            | 3                  |

**OPTICAL DATA**

|                      |                                 |
|----------------------|---------------------------------|
| Light source         | LED                             |
| Light colour         | Red                             |
| Optical signal image | Blink<br>Permanent<br>TwinLight |
| Blink frequency (Hz) | 1 Hz                            |
| Service life optical | 50,000 h maximum                |

**APPROVAL DATA**

|                             |         |
|-----------------------------|---------|
| Conforms with CE            | Yes     |
| WEEE                        | Yes     |
| Conforms with RED directive | No      |
| Conform with ATEX-directive | No      |
| Conforms with CCC           | No      |
| Conforms with UL            | cULus   |
| UL Type Rating              | Type 12 |
| Conforms with FCC           | No      |
| Conforms with IC            | No      |




For additional installation and mounting information, refer to the appropriate user guide at [www.werma.com](http://www.werma.com). This printed copy is for information only and is subject to alteration.

## Modular Signal Towers / KombiSIGN 72 TwinLIGHT Classic 24VAC/DC RD

|                           |     |
|---------------------------|-----|
| EAC certificate available | Yes |
| Conforms with AS-I        | No  |
| ICAO Certification        | No  |
| Conforms with GL          | No  |
| Conforms with RoHS CN     | No  |
| Conforms with VdS         | No  |

### DRAWING



For additional installation and mounting information, refer to the appropriate user guide at [www.werma.com](http://www.werma.com). This printed copy is for information only and is subject to alteration.