

SENCITY® Road PUCK Antenna

K7023231

Properties

- Frequency range from 440 MHz to 470 MHz
- Meets EN 50155 standard
- ECE-R118 approved
- Single-hole mounting with only 70mm in height



Electrical data			
	Band 1	Band 2	Band 3
Frequency	440 MHz ... 450 MHz	450 MHz ... 465 MHz	465 MHz ... 470 MHz
Impedance	50 Ω	50 Ω	50 Ω
VSWR	1.7	1.5	1.7
Ambient Temperature	25 °C	25 °C	25 °C

Electrical remarks	
Remarks	Indicated VSWR values are valid for a metallic ground plane of 1M x 1M or larger.

Ports	
	Port 1
Port name	Tetra
Connector	N, jack (female)
Polarization	vertical
DC grounded	Yes

Connections	
	Port 1
Port name	Tetra
Band 1	✓
Band 2	✓
Band 3	✓

SENCITY® Road PUCK Antenna

K7023231

Mechanical data	
Weight	0.4 kg
Dimensions	70 mm x 110 mm (Height x Diameter)
Remarks	Packaging size (outside): 117 x 117 x 114 mm
	Radiator and base: Aluminum. All metal parts of this antenna are DC grounded. Robust and car-wash proof vehicular antenna.

Material data	
Radome material	High impact plastic
Radome colour	Black
Back plate/base plate material	Aluminum
Back plate/base plate colour	Grey

Environmental data	
Operation temperature	-40 °C ... 85 °C
Storage temperature	-40 °C ... 85 °C
Transport temperature	-40 °C ... 85 °C
Environment (application)	Outdoor
Ingress protection (IP Rating)	Mated / IP56
Flammability rating	ECE-R118

Environmental remarks
ECE-R118 for rooftop installation only.

Additional Information
The drilling diameter is 12 mm except the N connector versions: 17 mm. A special zinc washer ensures a good contact at the edges of the hole.

Ordering information		
Item description	Item number	Product name
K7023231	84459192	SENCITY® Road PUCK Antenna

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P1027 / Date of publication: 13.02.2026 / uncontrolled copy