


Schottky Barrier Rectifier multicomp^{PRO}

RoHS
Compliant



Features

- The plastic package carries Underwriters Laboratory Flammability Classification 94V-0
- Metal silicon junction, majority carrier conduction
- Low power loss, high efficiency
- High forward surge current capability
- High temperature soldering guaranteed:
250 C/10 seconds, 0.375" (9.5mm) lead length, 5 lbs. (2.3kg) tension

Mechanical Data

Case	: JEDEC SOD-123FL molded plastic body
Terminals	: Plated axial leads, solderable per MIL-STD-750, Method 2026
Polarity	: Colour band denotes cathode end
Mounting Position	: Any
Weight	: 0.0007 ounce, 0.02 grams

Maximum Ratings and Electrical Characteristics

Rating at 25°C ambient temperature unless otherwise specified. Single phase, half wave, 60Hz, resistive or inductive load.
For capacitive load, derate current by 20%






Characteristics	Symbol	MP008615	UNIT
Maximum Recurrent Peak Reverse Voltage	V _{RRM}	200	V
Maximum RMS Voltage	V _{RMS}	140	V
Maximum DC Blocking Voltage	V _{DC}	200	V
Maximum Average Forward Rectified Current	I _(AV)	2.0	A
Peak Forward Surge Current 8.3ms Single Half Sine-Wave Super Imposed On Rated Load (JEDEC Method)	I _{FSM}	50	A
Maximum Forward Voltage at 2.0A DC	V _F	0.85	V
Maximum DC Reverse Current @TA=25°C at Rated DC Blocking Voltage @TA=100°C	I _R	0.2 2	mA
Typical junction capacitance (NOTE 1)	C _J	80	
Operating junction Temperature Range	T _J	-55 to + 175	°C
Storage Temperature Range	T _{STG}	-50 to + 150	
Note: 1. Measured at 1MHz and applied reverse voltage of 4.0V D.C. 2. The typical data above is for reference only.			

Newark.com/multicomp-pro
Farnell.com/multicomp-pro
sg.element14.com/b/multicomp-pro

multicomp^{PRO}

Schottky Barrier Rectifier **multicomp**PRO


Rating and Characteristic Curves



Schottky Barrier Rectifier multicomp^{PRO}

Package Dimensions

SOD-123FL



Dimensions : Millimetres

Part Number Table

Description	Part Number
Schottky Barrier Rectifier, 1A, 200V, SOD-123FL	MP008615

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro
Farnell.com/multicomp-pro
sg.element14.com/b/multicomp-pro

multicomp^{PRO}