



Click [here](#) for the 3D model.

General Information

| | |
|--------------------------|--|
| Series | PEH227 |
| Dielectric | Aluminum Electrolytic |
| Style | Radial Crown |
| Description | Radial Crown Ultra High CV Aluminum Electrolytic |
| RoHS | Yes |
| Lead | Radial Crown |
| Qualifications | AEC-Q200 |
| Halogen Free | Yes |
| Typical Component Weight | 8 g |
| Shelf Life | 520 Weeks |

Dimensions

| | |
|----|-----------------|
| D | 16.2mm +/-0.5mm |
| L | 27.7mm +/-1mm |
| LL | 3.3mm +/-0.5mm |
| F | 1mm +/-0.03mm |

Packaging Specifications

| | |
|-----------|------|
| Packaging | Tray |
|-----------|------|

Specifications

| | |
|-------------------|---|
| Capacitance | 780 uF |
| Tolerance | -10/+30% |
| Voltage DC | 63 VDC, 54 VDC (150C) |
| Temperature Range | -40/+150°C |
| Rated Temperature | 125°C |
| Life | 6300 Hrs (Rated Voltage At 125C), 1500 Hrs (Rated Voltage At 150C) |
| ESR | 107 mOhms (100Hz 20C), 45 mOhms (100kHz 20C), 21.3 mOhms (5-100kHz 150C) |
| Ripple Current | 12.9 Amps (5kHz 125C, With Heat Sink), 8.2 Amps (5kHz 140C, With Heat Sink), 3.7 Amps (5kHz 150C, With Heat Sink), 4.6 Amps (5kHz 125C), 5.9 Amps (5kHz 125C Max) |
| Leakage Current | 151.4 uA (5min 20°C) |

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.