

## Product Summary (@ T<sub>A</sub> = +25°C)

| V <sub>RRM</sub> (V) | I <sub>o</sub> (A) | V <sub>F(MAX)</sub> (V) | I <sub>R(MAX)</sub> (μA) |
|----------------------|--------------------|-------------------------|--------------------------|
| 100                  | 8                  | 0.88                    | 2                        |

## Description and Applications


This Super Barrier Rectifier (SBR) diode has been designed to meet the stringent requirements of Automotive Application. It is ideally suited to such as:

- Polarity Protection Diode
- Re-Circulating Diode
- Switching Diode
- Blocking Diode
- DC-DC Converter
- AC-DC Converter

This device is suitable to protect sensitive automotive circuits against surges defined in ISO7637-2.

- Polarity (ISO7637-2 for 24V System)

Pulse 1: US = -600V  
Pulse 2a: US = +112V  
Pulse 3a: US = -300V  
Pulse 3b: US = +300V




## Features and Benefits

- Low Forward Voltage Drop
- Excellent High Temperature Stability
- Patented Super Barrier Rectifier SBR<sup>®</sup> Technology
- Soft, Fast Switching Capability
- **Lead-Free Finish; RoHS Compliant (Notes 1 & 2)**
- **Halogen and Antimony Free. "Green" Device (Note 3)**
- **The SBR8M100P5Q is suitable for automotive applications requiring specific change control; this part is AEC-Q101 qualified, PPAP capable, and manufactured in IATF 16949 certified facilities.**

<https://www.diodes.com/quality/product-definitions/>

## Mechanical Data

- Case: PowerDI<sup>®</sup>5
- Case Material: Molded Plastic, "Green" Molding Compound. UL Flammability Classification Rating 94V-0
- Moisture Sensitivity: Level 1 per J-STD-020
- Terminals: Finish – Matte Tin Annealed over Copper Leadframe. Solderable per MIL-STD-202, Method 208 (E3)
- Terminal Connections: See Diagram Below
- Weight: 0.093 grams (Approximate)




**Note: Pins Left & Right must be electrically connected at the printed circuit board.**

## Ordering Information (Note 4)

| Part Number              | Compliance | Case     | Packaging        |
|--------------------------|------------|----------|------------------|
| SBR8M100P5Q-13           | Automotive | PowerDI5 | 5000/Tape & Reel |
| SBR8M100P5Q-13D (Note 5) | Automotive | PowerDI5 | 5000/Tape & Reel |

- Notes:
1. EU Directive 2002/95/EC (RoHS), 2011/65/EU (RoHS 2) & 2015/863/EU (RoHS 3) compliant. All applicable RoHS exemptions applied.
  2. See <https://www.diodes.com/quality/lead-free/> for more information about Diodes Incorporated's definitions of Halogen- and Antimony-free, "Green" and Lead-free.
  3. Halogen- and Antimony-free "Green" products are defined as those which contain <900ppm bromine, <900ppm chlorine (<1500ppm total Br + Cl) and <1000ppm antimony compounds.
  4. For packaging details, go to our website at <https://www.diodes.com/design/support/packaging/diodes-packaging/>.
  5. Suffix -13D is designated for 12mm tape width.

## Marking Information



S8M100 = Product Type Marking Code  
DII = Manufacturers' Code Marking  
YYWW = Date Code Marking  
YY = Last Two Digits of Year (ex: 21 for 2021)  
WW = Week Code (01 to 53)  
K = Factory Designator

**Maximum Ratings** (@T<sub>A</sub> = +25°C, unless otherwise specified.)

| Characteristic                                                                         | Symbol           | Value | Unit |
|----------------------------------------------------------------------------------------|------------------|-------|------|
| Peak Repetitive Reverse Voltage<br>Working Peak Reverse Voltage<br>DC Blocking Voltage | V <sub>RRM</sub> | 100   | V    |
| Average Rectified Output Current                                                       | I <sub>O</sub>   | 8     | A    |
| Non-Repetitive Peak Forward Surge Current 8.3mS                                        | I <sub>FSM</sub> | 130   | A    |
| Non-Repetitive Avalanche Energy at I <sub>AS</sub> = 5.0A, L = 50mH                    | E <sub>AS</sub>  | 400   | mJ   |
| Non-Repetitive Avalanche Energy at I <sub>AS</sub> = 20.0A, L = 1mH                    | E <sub>AS</sub>  | 150   | mJ   |
| Electrostatic Discharge                                                                | HBM              | 4000  | V    |
| Electrostatic Discharge                                                                | MM               | 400   | V    |
| Electrostatic Discharge                                                                | CDM              | 1     | kV   |

**Thermal Characteristics** (Note 9)

| Characteristic                                          | Symbol                            | Value       | Unit |
|---------------------------------------------------------|-----------------------------------|-------------|------|
| Typical Thermal Resistance Junction to Ambient (Note 6) | R <sub>θJA</sub>                  | 25          | °C/W |
| Typical Thermal Resistance Junction to Ambient (Note 7) | R <sub>θJA</sub>                  | 90          | °C/W |
| Operating and Storage Temperature Range                 | T <sub>J</sub> , T <sub>STG</sub> | -55 to +175 | °C   |

**Electrical Characteristics** (@T<sub>A</sub> = +25°C, unless otherwise specified.)

| Characteristic                  | Symbol          | Min | Typ  | Max  | Unit | Test Condition                                                            |
|---------------------------------|-----------------|-----|------|------|------|---------------------------------------------------------------------------|
| Forward Voltage Drop            | V <sub>F</sub>  | —   | 0.72 | —    | V    | I <sub>F</sub> = 4A, T <sub>J</sub> = +25°C                               |
|                                 |                 | —   | 0.78 | 0.88 |      | I <sub>F</sub> = 8A, T <sub>J</sub> = +25°C                               |
|                                 |                 | —   | 0.59 | —    |      | I <sub>F</sub> = 4A, T <sub>J</sub> = +125°C                              |
|                                 |                 | —   | 0.65 | 0.74 |      | I <sub>F</sub> = 8A, T <sub>J</sub> = +125°C                              |
| Leakage Current (Note 8)        | I <sub>R</sub>  | —   | 0.08 | 2.0  | μA   | V <sub>R</sub> = 100V, T <sub>J</sub> = +25°C                             |
|                                 |                 | —   | 15   | 100  |      | V <sub>R</sub> = 100V, T <sub>J</sub> = +125°C                            |
| Junction Capacitance            | C <sub>J</sub>  | —   | 245  | —    | pF   | V <sub>R</sub> = 4V, T <sub>J</sub> = +25°C                               |
| Switching Speed t <sub>RR</sub> | t <sub>RR</sub> | —   | 16   | —    | ns   | I <sub>F</sub> = 0.5A, I <sub>R</sub> = 1A, I <sub>RR</sub> = 0.25A (RG1) |

- Notes:
6. 2inch sq. Al board.
  7. MRP FR-4 PC board, 2oz.
  8. Short duration pulse test used to minimize self-heating effect.
  9. The heat generated must be less than thermal conductivity from junction-to-ambient:  $dP_D/dT_J < 1/R_{\theta JA}$ .




Figure 1. Typical Forward Characteristics




Figure 2. Typical Reverse Characteristics




Figure 3. Forward Power Dissipation  $T_J=125^\circ\text{C}$




Figure 4. Forward Power Dissipation  $D=0.5$




Figure 5. Forward Current Derating Curve




Figure 6. Typical Single Pulse Max. Avalanche Energy and Current




Figure 7. Typical Junction Capacitance





Figure 8. Transient Thermal Resistance MRP (Note 7)

## Package Outline Dimensions

Please see <http://www.diodes.com/package-outlines.html> for the latest version.

PowerDI5




| PowerDI5             |      |      |       |
|----------------------|------|------|-------|
| Dim                  | Min  | Max  | Typ   |
| A                    | 1.05 | 1.15 | 1.10  |
| A1                   | 0.00 | 0.05 | --    |
| A2                   | 0.33 | 0.43 | 0.381 |
| b1                   | 0.80 | 0.99 | 0.89  |
| b2                   | 1.70 | 1.88 | 1.78  |
| D                    | 3.90 | 4.05 | 3.966 |
| D2                   | --   | --   | 3.054 |
| E                    | 6.40 | 6.60 | 6.51  |
| e                    | --   | --   | 1.84  |
| E1                   | 5.30 | 5.45 | 5.37  |
| E2                   | --   | --   | 3.549 |
| L                    | 0.75 | 0.95 | 0.85  |
| L1                   | 0.50 | 0.65 | 0.57  |
| W                    | 1.10 | 1.41 | 1.255 |
| All Dimensions in mm |      |      |       |

## Suggested Pad Layout

Please see <http://www.diodes.com/package-outlines.html> for the latest version.

PowerDI5



| Dimensions | Value (in mm) |
|------------|---------------|
| C          | 1.840         |
| G          | 0.852         |
| X          | 1.400         |
| X1         | 4.860         |
| X2         | 1.310         |
| Y          | 1.390         |
| Y1         | 3.360         |

**IMPORTANT NOTICE**

1. DIODES INCORPORATED AND ITS SUBSIDIARIES (“DIODES”) MAKE NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARDS TO ANY INFORMATION CONTAINED IN THIS DOCUMENT, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION).
2. The Information contained herein is for informational purpose only and is provided only to illustrate the operation of Diodes products described herein and application examples. Diodes does not assume any liability arising out of the application or use of this document or any product described herein. This document is intended for skilled and technically trained engineering customers and users who design with Diodes products. Diodes products may be used to facilitate safety-related applications; however, in all instances customers and users are responsible for (a) selecting the appropriate Diodes products for their applications, (b) evaluating the suitability of the Diodes products for their intended applications, (c) ensuring their applications, which incorporate Diodes products, comply the applicable legal and regulatory requirements as well as safety and functional-safety related standards, and (d) ensuring they design with appropriate safeguards (including testing, validation, quality control techniques, redundancy, malfunction prevention, and appropriate treatment for aging degradation) to minimize the risks associated with their applications.
3. Diodes assumes no liability for any application-related information, support, assistance or feedback that may be provided by Diodes from time to time. Any customer or user of this document or products described herein will assume all risks and liabilities associated with such use, and will hold Diodes and all companies whose products are represented herein or on Diodes’ websites, harmless against all damages and liabilities.
4. Products described herein may be covered by one or more United States, international or foreign patents and pending patent applications. Product names and markings noted herein may also be covered by one or more United States, international or foreign trademarks and trademark applications. Diodes does not convey any license under any of its intellectual property rights or the rights of any third parties (including third parties whose products and services may be described in this document or on Diodes’ website) under this document.
5. Diodes products are provided subject to Diodes’ Standard Terms and Conditions of Sale (<https://www.diodes.com/about/company/terms-and-conditions/terms-and-conditions-of-sales/>) or other applicable terms. This document does not alter or expand the applicable warranties provided by Diodes. Diodes does not warrant or accept any liability whatsoever in respect of any products purchased through unauthorized sales channel.
6. Diodes products and technology may not be used for or incorporated into any products or systems whose manufacture, use or sale is prohibited under any applicable laws and regulations. Should customers or users use Diodes products in contravention of any applicable laws or regulations, or for any unintended or unauthorized application, customers and users will (a) be solely responsible for any damages, losses or penalties arising in connection therewith or as a result thereof, and (b) indemnify and hold Diodes and its representatives and agents harmless against any and all claims, damages, expenses, and attorney fees arising out of, directly or indirectly, any claim relating to any noncompliance with the applicable laws and regulations, as well as any unintended or unauthorized application.
7. While efforts have been made to ensure the information contained in this document is accurate, complete and current, it may contain technical inaccuracies, omissions and typographical errors. Diodes does not warrant that information contained in this document is error-free and Diodes is under no obligation to update or otherwise correct this information. Notwithstanding the foregoing, Diodes reserves the right to make modifications, enhancements, improvements, corrections or other changes without further notice to this document and any product described herein. This document is written in English but may be translated into multiple languages for reference. Only the English version of this document is the final and determinative format released by Diodes.
8. Any unauthorized copying, modification, distribution, transmission, display or other use of this document (or any portion hereof) is prohibited. Diodes assumes no responsibility for any losses incurred by the customers or users or any third parties arising from any such unauthorized use.

Copyright © 2021 Diodes Incorporated

[www.diodes.com](http://www.diodes.com)