



- Robust aluminium housing including wire guard
- Extreme durability thanks to low wear belt drive
- Salt water resistant
- Extremely quiet
- Installation without the need to disassemble the mechanism
- Robust bracket made of V2A stainless steel (accessory)

TECHNICAL SPECIFICATIONS:

Dimensions (Ø x Height):	153 mm x 198 mm
Housing:	Black laquered aluminium with integral wire guard
Lens:	PC, transparent
Fixing:	Base mounting
Connection:	Screw terminal with wire protection max. 2.5 mm ²
Cable entry:	Cable gland M20 x 1.5 mm (included in assembly) Cable diameter 6-13 mm
Installation position:	As required
Halogen bulb:	G 6.35 20 W 12/24 V
Mirror rotating rate:	C. 180 r.p.m.
Service life of drive:	> 5.000 hrs

ORDER SPECIFICATIONS:

Voltage	24 V AC/DC	115 V AC	/ 115 V DC	/ 230 V AC	/ 230 V DC
Current consumption	1.0 A	0.35 A	/ 0.5 A	/ 0.15 A	/ 0.1 A
red	839 160 75	839 160 78			
yellow	839 360 75	839 360 78			

ACCESSORIES:

Mounting bracket	975 839 02
------------------	-------------------

SPARE PARTS:

Halogen bulb 20 W/12 V for 115 V AC/DC, 230 V AC	955 885 24
--	-------------------

Halogen bulb 20 W/24 V for 24 V AC/DC	955 885 25
---------------------------------------	-------------------

TECHNICAL DIAGRAMS:

see page 317





Also suitable for use in rough conditions

Sizes of Rotating Beacons



See note on page 347



WERMA
SIGNALTECHNIK

