

RKDGE D2X6,5 PT6**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Intelligent cabling solutions can save you valuable time and money.**

The FieldPower® modular system contains the right solution for every cabling task.

Foldable seals for the use of pre-assembled cables

Seals available with M16 and M20 connection thread

Integration of operating and signalling devices into the seal possible

General ordering data

Version	FieldPower®, Field Power® sealing insert, round, IP54, 4.5 - 6.5 mm ²
Order No.	2443800000
Type	RKDGE D2X6,5 PT6
GTIN (EAN)	4050118457704
Qty.	10 pc(s).

RKDGE D2X6,5 PT6**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Technical data****Dimensions and weights**

Depth	16 mm	Depth (inches)	0.63 inch
Height	21 mm	Height (inches)	0.827 inch
Width	21 mm	Width (inches)	0.827 inch
Net weight	3.32 g		

Temperatures

Operating temperature	-40 °C...85 °C
-----------------------	----------------

General data

Clamping range, max.	6.5 mm ²	Clamping range, min.	4.5 mm ²
Colour	beige	Design	Slotted sealing insert
Line type	round	Material	TPE-V
Mounting position, installation notice	in RKDG D17 PT6 (4324010000)	Protection degree	IP54
UL 94 flammability rating	HB		

Classifications

ETIM 6.0	EC002624	ETIM 7.0	EC002624
ETIM 8.0	EC002624	ECLASS 9.1	27-18-27-90
ECLASS 10.0	27-18-28-15	ECLASS 11.0	27-18-28-15

Important note

Product information	The foldable seal RKDG D17 PT6 (4324010000) is the carrier seal for the slotted sealing insert. Cables for IP54 with multiple sealing insert 2 x 6.5 mm (2443800000): • IE cable Ø 6.5 mm Type: IE-C5DD4UG..... • 24 V cable Ø 6.5 mm E.g. Lapp Ölflex Classic 110 3G1,5
---------------------	--

Approvals

ROHS	Conform
------	---------

Downloads

Catalogues	Catalogues in PDF-format
------------	--