


Zener Diodes

5W, Axial Lead

multicompPRO



Features

- Low Zener impedance.
- High reliability chips.
- Lead-free finish
- The plastic package carries Underwriters Laboratory Flammability Classification 94V-0
- This product is available in AEC-Q101 Compliant also

**RoHS
Compliant**

Applications

- Regulates voltage over a broad operating current and temperature range
- Wide selection from 3.3 to 200V
- Flexible axial-lead mounting terminals
- Nonsensitive to ESD per MIL-STD-750 Method 1020
- Withstands high surge stresses
- Minimal changes of voltage versus current as specified by voltage regulation (ΔV_z)
- High specified maximum current (I_{zm}) when adequately heat sunk
- Moisture classification is Level 1 per IPC/JEDEC J-STD-020B with no dry pack required

Absolute Maximum Ratings ($T_a = 25^\circ\text{C}$ Unless otherwise specified)

Parameter	Symbol	Value	Unit
Power Dissipation	P_D	5	W
Thermal Resistance Junction To Ambient Air	$R_{\theta JA}$	100	$^\circ\text{C/W}$
Thermal Resistance Junction To Leads	$R_{\theta JL}$	25	$^\circ\text{C/W}$
Forward voltage @ $I_F=200\text{mA}$	V_F	1.2	V
Storage Temperature Range	T_{STG}	-55 to +150	$^\circ\text{C}$
Operating Junction Temperature Range	T_J	-55 to +150	$^\circ\text{C}$

Electrical Characteristics at ($T_a = 25^\circ\text{C}$ Unless otherwise specified)

Part Number	Zener voltage			Test current	Dynamic impedance	Knee current	Knee impedance	Reverse current	Reverse voltage	Max.DC current
	VZ /V			IZT	ZZT	IZK	ZZK	IR(Max.)	VR	IZM
	Vz(MIN)	Vz(NOR)	Vz(MAX)	mA	Ω	mA	Ω	μA	V	mA
MP008755	5.890	6.200	6.510	200	1	1	200	1	4	765
MP008756	6.460	6.800	7.140	175	1	1	200	150	4.9	700
MP008757	7.790	8.200	8.610	150	1.5	1	200	150	5.9	580
MP008758	9.500	10.000	10.500	125	2	1	125	150	7.2	475
MP008759	11.400	12.000	12.600	100	2.5	1	125	2	8.6	395
MP008760	12.350	13.000	13.650	100	2.5	1	100	1	9.4	365
MP008761	13.330	14.000	14.700	100	25	1	75	1	10.1	340
MP008762	14.280	15.000	15.750	75	25	1	75	1	10.8	315
MP008763	15.230	16.000	16.800	75	2.5	1	75	1	11.5	295
MP008764	25.710	27.000	28.350	50	5	1	120	0.5	19.4	176
MP008765	31.420	33.000	34.650	40	10	81	150	0.5	23.8	144
MP008766	34.280	36.000	37.800	30	11	1	160	0.5	25.9	132

Newark.com/multicomp-pro
Farnell.com/multicomp-pro
sg.element14.com/b/multicomp-pro

multicompPRO

Zener Diodes

5W, Axial Lead

multicompPRO

Typical Characteristic Curves

Fig 1: Power Temperature Derating Curve




Fig 3: Typical Capacitance vs. Reverse Voltage for 5 Watt Zeners





Fig 2: Typical Capacitance vs. Reverse Voltage for 5 Watt Zeners




Zener Diodes

5W, Axial Lead

multicompPRO

Dimensions



DIM	Millimeters		Inches	
	Min	Max	Min	Max
A	25.4	--	1.000	--
B	5.80	7.60	0.230	0.300
C	0.70	0.90	0.028	0.034
D	2.60	3.60	0.104	0.140

Part Number Table

Description	Part Number
Zener Diode, 5W, 6.2V, DO-15P, Axial	MP008755
Zener Diode, 5W, 6.8V, DO-15P, Axial	MP008756
Zener Diode, 5W, 8.2V, DO-15P, Axial	MP008757
Zener Diode, 5W, 10V, DO-15P, Axial	MP008758
Zener Diode, 5W, 12V, DO-15P, Axial	MP008759
Zener Diode, 5W, 13V, DO-15P, Axial	MP008760
Zener Diode, 5W, 14V, DO-15P, Axial	MP008761
Zener Diode, 5W, 15V, DO-15P, Axial	MP008762
Zener Diode, 5W, 16V, DO-15P, Axial	MP008763
Zener Diode, 5W, 27V, DO-15P, Axial	MP008764
Zener Diode, 5W, 33V, DO-15P, Axial	MP008765
Zener Diode, 5W, 36V, DO-15P, Axial	MP008766

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro
Farnell.com/multicomp-pro
sg.element14.com/b/multicomp-pro

multicompPRO