
Item no.: 740-102
Product description: PCB TERMINAL STRIP; 1 SOLDER PIN / POLE; 2 POLE; PIN
SPACING 5 MM / 0.197 IN; SIDE-ENTRY; CAGE
CLAMP®CONNECTION



Packing unit 460 4*115 pieces

Pin spacing from	5 mm
Pin spacing from	0,197 in
pole count	2
Cross section from [mm²]	0,08 mm²
Cross section to [mm²]	2,5 mm²
Cross section from [AWG]	28 AWG
Cross section to [AWG]	12 AWG
Connection method	CAGE CLAMP®CONNECTION
Measured voltage EN	250 V
Measured shock voltage	4 kV
Pollution degree	3
Current intensity EN	16 A
Voltage CSA	300 V
Current CSA	16 A
Voltage UL	300 V
Current UL	10 A
Weight	2,735 g
Color	grey
Wiring type	Side-entry
No. of connection Points	2
No. of potentials	2
Height	18,2 mm



Width	10 mm
Width	0,394 in
Depth	11,1 mm
Depth	0,437 in
Strip length from	6 mm
Strip length to	7 mm
Strip length	0,24 in



Item number	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [mm²]
740-102	BBJ	B/12/697/03	250	16	0,5-2,5
740-102	BV	11915/A0	250	16	0,5-2,5
740-102	CCA	DK2097	250	16	0,5-2,5
740-102	CSA	154112-1711139	300	16	28-12
740-102	DEMKO	99-04159	250	16	0,5-2,5
740-102	DNV	E7569	250	16	0,5-2,5
740-102	GL	17296-00HH	250	16	0,5-2,5
740-102	RMR	11130002	250	16	0,5-2,5
740-102	UL	E45172	300	10	28-12

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected