

2822HC

High current surface mount Brick fuse



Product features

- 7.7 x 6.0 x 4.3 mm surface mount package
- High current Brick fuse
- Current rating: 40 A to 125 A
- Voltage rating: Up to 80 Vdc
- High interrupting rating
- cURus recognized
- Single fuse solution for high current applications
- Moisture sensitivity level: (MSL): 1

Applications

- Servers and back planes
- Power distribution units (PDUs)
- Power supplies
- Energy storage system
- Industrial automation tools
- Robotic machinery
- Telecom DC/DC power
- Routers & switches

Agency information

cURus Recognition file number: E91958,
Guide JFHR2 & JFHR8




Environmental compliance



Ordering part number

2822HC xx -RTR



Packaging code suffix

TR (1000 parts on a 13" diameter tape and reel)



Powering Business Worldwide

Electrical characteristics

Amp Rating	1.0 In minimum	2.5 In maximum
40 A ~ 125 A	4 hours	60 seconds


Product specifications

Part number	Current rating (A)	Voltage rating (Vdc)	Interrupting rating @ rated voltage ¹ (A)	Typical cold resistance ² (mΩ)	Typical voltage drop (mV)	Part marking
2822HC40-R	40	72*	1000 A @ 72 Vdc 1000 A @ 80 Vdc	1.10	75	BUSS 2822HC 40A
2822HC50-R	50	72*	1000 A @ 72 Vdc 1000 A @ 80 Vdc	0.87	75	BUSS 2822HC 50A
2822HC60-R	60	72*	1000 A @ 72 Vdc 1000 A @ 80 Vdc	0.78	100	BUSS 2822HC 60A
2822HC70-R	70	72*	1000 A @ 72 Vdc 500 A @ 80 Vdc	0.60	100	BUSS 2822HC 70A
2822HC80-R	80	72*	1000 A @ 72 Vdc 500 A @ 80 Vdc	0.58	100	BUSS 2822HC 80A
2822HC90-R	90	72*	1000 A @ 72 Vdc 500 A @ 80 Vdc	0.54	100	BUSS 2822HC 90A
2822HC100-R	100	72*	1000 A @ 72 Vdc 500 A @ 80 Vdc	0.45	100	BUSS 2822HC 100A
2822HC125-R	125	60	1000 A @ 60 Vdc	0.40	110	BUSS 2822HC 125A

1. DC Interrupting rating (measured at designated voltage, time constant of less than 1 milliseconds, battery source)
2. Typical cold resistance is measured at <10% of rated current in ambient temperature of +25 °C
*= UL rated at 72 Vdc and 80 Vdc


Dimensions- mm

Drawing not to scale




Amp rating	L	W	T	W1	T1
40 A - 90 A	7.6 ± 0.30	6.0 ± 0.30	4.2 ± 0.20	5.0 REF	1.6 REF
100 A - 125 A	7.7 ± 0.30	6.0 ± 0.30	4.3 ± 0.30	5.0 REF	1.6 REF

Recommended pad layout



Standard test board




Testing board: 1.6 mm FR4 PCB
Copper thickness: 3 oz for 40 A – 70 A,
6 oz for above 70 A. Tin plated

General specifications

Operating temperature: -40 °C to +125 °C with proper derating factor applied
Soldering heat resistance: MIL-STD-202 method 210, Solder temperature +260 ±5 °C, solder immersion time 10±5 s
Solderability test: J-STD-002, method B1, Steam aging 1 hour, Solder temperature + 255 ±5 °C, solder immersion time 5 s
Thermal shock: MIL-STD-202 method 107, -40 °C/+125 °C. 1000 cycles, maximum transfer time 20 seconds, Dwell time 15 minutes. Air-Air
Humidity bias: MIL-STD-202 method 103, 1000 hours +85 °C/85% RH. at 10% of operating power.
Vibration: MIL-STD-202F method 201, 2 hours each of 3 orientations. Test from 10-55 Hz for 1 minute
Mechanical shock: MIL-STD-202 method 213, Figure 1 of Method 213. Condition C 100 g 6 ms
High temperature operating life: MIL-STD-202 method 108, Condition D steady state TA=+70 °C at 60% rated current.


Packaging information - mm

1000 parts per 13" diameter reel (EIA-481 compliant)
Drawing not to scale




Dimension	millimeter
W	16.0
F	7.5
E	1.75
P0	4.0
P	12.0
P2	2.0
ØD0	1.50
ØD1	N/A
A0	6.3
B0	8.0
K0	4.7

Reel dimension- mm




Dimension	millimeter
A	330
B	2.2
C	13.5
D	22
W1	16.5
W2	22.4 maximum


Temperature derating curve




Time vs. current curve




I²t vs. time curve



I²t vs. current



Wave solder profile



Reference

Profile feature		Standard SnPb solder	Lead (Pb) free solder
Preheat	• Temperature min. (T_{smin})	100 °C	100 °C
	• Temperature typ. (T_{styp})	120 °C	120 °C
	• Temperature max. (T_{smax})	130 °C	130 °C
	• Time (T_{smin} to T_{smax}) (t_s)	70 seconds	70 seconds
Δ preheat to max Temperature		150 °C max.	150 °C max.
Peak temperature (T_p)*		235 °C – 260 °C	250 °C – 260 °C
Time at peak temperature (t_p)		6 seconds max 3 seconds max each wave	6 seconds max 3 seconds max each wave
Ramp-down rate		~ 2 K/s min ~3.5 K/s typ ~5 K/s max	~ 2 K/s min ~3.5 K/s typ ~5 K/s max
Time 25 °C to 25 °C		4 minutes	4 minutes

Manual solder

+350 °C (4-5 seconds by soldering iron), generally manual/hand soldering is not recommended.

Solder reflow profile




Table 1 - Standard SnPb solder (TC)

Package thickness	Volume mm ³ <350	Volume mm ³ ≥350
<2.5 mm	235 °C	220 °C
≥2.5 mm	220 °C	220 °C

Table 2 - Lead (Pb) free solder (TC)

Package thickness	Volume mm ³ <350	Volume mm ³ 350 - 2000	Volume mm ³ >2000
<1.6 mm	260 °C	260 °C	260 °C
1.6 – 2.5 mm	260 °C	250 °C	245 °C
>2.5 mm	250 °C	245 °C	245 °C

Reference J-STD-020

Profile feature	Standard SnPb solder	Lead (Pb) free solder
Preheat and soak	<ul style="list-style-type: none"> Temperature min. (T_{Amin}) Temperature max. (T_{Amax}) Time (T_{Amin} to T_{Amax}) (t_s) 	<ul style="list-style-type: none"> 100 °C 150 °C 60-120 seconds
Ramp up rate T _L to T _P	3 °C/ second max.	3 °C/ second max.
Liquidous temperature (T _L) Time (t _L) maintained above T _L	<ul style="list-style-type: none"> 183 °C 60-150 seconds 	<ul style="list-style-type: none"> 217 °C 60-150 seconds
Peak package body temperature (T _P)*	Table 1	Table 2
Time (t _p)* within 5 °C of the specified classification temperature (T _C)	20 seconds*	30 seconds*
Ramp-down rate (T _P to T _L)	6 °C/ second max.	6 °C/ second max.
Time 25 °C to peak temperature	6 minutes max.	8 minutes max.

* Tolerance for peak profile temperature (T_p) is defined as a supplier minimum and a user maximum.

Life Support Policy: Eaton does not authorize the use of any of its products for use in life support devices or systems without the express written approval of an officer of the Company. Life support systems are devices which support or sustain life, and whose failure to perform, when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.

Eaton reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Eaton also reserves the right to change or update, without notice, any technical information contained in this bulletin.

Eaton
Electronics Division
1000 Eaton Boulevard
Cleveland, OH 44122
United States
Eaton.com/electronics

© 2022 Eaton
All Rights Reserved
Printed in USA
Publication No. ELX1147 BU-ELX22002
February 2022

Eaton is a registered trademark.
All other trademarks are property of their respective owners.

Follow us on social media to get the latest product and support information.

