



LOW BAND COILS/WHIPS

| Model    | Type                 | Frequency (MHz) | Gain (dBi) | Max Height (In) | Power Rating (Watts) | Whip Color | Cable Assembly/Mount |
|----------|----------------------|-----------------|------------|-----------------|----------------------|------------|----------------------|
| NMO27BCO | Loaded 1/4 $\lambda$ | 27-30           |            | 4               | 150                  | Coil Only  | Order Separately     |
| NMO27B   | Loaded 1/4 $\lambda$ | 27-30           | 2          | 52.5            | 150                  | Black      | Order Separately     |
| NMO27C   | Loaded 1/4 $\lambda$ | 27-30           | 2          | 52.5            | 150                  | Stainless  | Order Separately     |
| NMO30BCO | Loaded 1/4 $\lambda$ | 30-34           |            | 4               | 150                  | Coil Only  | Order Separately     |
| NMO30B   | Loaded 1/4 $\lambda$ | 30-34           | 2          | 57.5            | 150                  | Black      | Order Separately     |
| NMO30C   | Loaded 1/4 $\lambda$ | 30-34           | 2          | 57.5            | 150                  | Stainless  | Order Separately     |
| NMO34BCO | Loaded 1/4 $\lambda$ | 34-40           |            | 4               | 150                  | Coil Only  | Order Separately     |
| NMO34B   | Loaded 1/4 $\lambda$ | 34-40           | 2          | 57.5            | 150                  | Black      | Order Separately     |
| NMO34C   | Loaded 1/4 $\lambda$ | 34-40           | 2          | 57.5            | 150                  | Stainless  | Order Separately     |
| NMO40BCO | Loaded 1/4 $\lambda$ | 40-50           |            | 3.5             | 150                  | Coil Only  | Order Separately     |
| NMO40B   | Loaded 1/4 $\lambda$ | 40-50           | 2          | 57.5            | 150                  | Black      | Order Separately     |
| NMO40C   | Loaded 1/4 $\lambda$ | 40-50           | 2          | 57.5            | 150                  | Stainless  | Order Separately     |
| NMOWB40C | Loaded 1/4 $\lambda$ | 40-50           | 2          | 55              | 150                  | Stainless  | Order Separately     |
| NMO50BCO | Loaded 1/4 $\lambda$ | 47-54           |            | 3.5             | 150                  | Coil Only  | Order Separately     |
| NMO50B   | Loaded 1/4 $\lambda$ | 47-54           | 2          | 52.5            | 150                  | Black      | Order Separately     |
| NMO50C   | Loaded 1/4 $\lambda$ | 47-54           | 2          | 52.5            | 150                  | Stainless  | Order Separately     |
| NMOQ52C  | 1/4 $\lambda$        | 52-88           | 2          | 55              | 150                  | Stainless  | Order Separately     |
| NMOQ88C  | 1/4 $\lambda$        | 88-136          | 2          | 35              | 150                  | Stainless  | Order Separately     |
| Q52      | 1/4 $\lambda$        | 52-88           | 2          | 55              | 200                  | Stainless  | Order Separately     |
| Q88      | 1/4 $\lambda$        | 88-136          | 2          | 35              | 200                  | Stainless  | Order Separately     |



NMO Low Band



NMOQ Low Band



NMOWB Low Band



Q Series Low Band

The most commonly used cable assembly/mount is the NMOKHFUD (27 MHz to 6 GHz) with 17' of UD (RG-58/U Dual Shield).

NOTE: Larsen springs (SPRING or SPRINGB) can be added to most mobile antennas.

