

7

6

5

4

3

2

1

ECN NO.

REV

DESCRIPTION


DATE

REVISER

APPROVED

E

E




D

D

TABLE 1

PART NO.:	LENGTH(L)
CS33251	200±30
CS33252	500±30
CS33253	1000±30
CS33254	2000±30

PIN ASSIGNMENT:



C

C

B

ELECTRICAL CHARACTER:
1.100% OPEN & SHORT TESTING.

B

A

A

GENERAL TOLERANCES
(UNLESS SPECIFIED)

CUST PART NO.:

PRO-SIGNAL

.XXX: ±0.15

ANGULAR:
±3°

DESIGN:

SCALE: NONE

UNIT: mm

.XX: ±0.25

CHECKED:

TITLE: USB 2.0 AM TO MINI USB 5P BM CABLE

.X: ±0.50

APPROVED:

PART NO.: SEE TABLE1

REV:A

SIZE
A4

DATE: 2019.07.05

SHEET NO.: 1 OF 1

ITEM	DESCRIPTION	UNIT	QT'Y
4	PVC: BLACK.	g	8
3	CONN: USB MINI 5P BM, CONTACT: GOLD PLATED, SHELL: GOLD PLATED, BLACK INSULATOR	PCS	1
2	CONN: USB AM, CONTACT: GOLD PLATED, SHELL: GOLD PLATED, WHITE INSULATOR.	PCS	1
1	CABLE: USB 2.0 28AWG(7/0.12 TC)x1P+28AWG(7/0.12 TC)x2C+AL/MYLAR +D7*0.12BC), PVC JACKET OD: 3.8, BLACK.	mm	see table

7

6

5

4

3

2

1