

RoHS
Compliant

Input Characteristics

Input Voltage

Rated Input Voltage : 100V AC to 240V AC

Variable Input Voltage : 90V AC to 264V AC

Input Current

1.5A max when input rated voltage and output rated load

Input Frequency

Rate Frequency : 50/60Hz

Variation Frequency : 47Hz to 63Hz

In-rush Current

60 Amps Max. Cold start at 240V AC input ,with rated load and 25°C ambient

AC Leakage Current

3.5mA Max. .@ 240V AC input

Output Characteristics

Rated Output Power : 60W

Voltage : +12V

Max. Load : 5A

Load Regulation : 11.4V to 12.6V

Unload Output Voltage : 11.4V to 12.6V

Efficiency

115V AC input, the average efficiency $\geq 88\%$ output rated load is 25%, 50%, 75%, 100% 4 situations of average efficiency

230V AC input, the average efficiency $\geq 88\%$ output rated load is 25%, 50%, 75%, 100% 4 situations of average efficiency

Unload standby Power : 0.21W Max.

Ripple & Noise

Measurement is done by 20MHz bandwidth oscilloscope and the output paralleled a 0.1 μ F ceramic capacitor and a 47 μ F electrolysis capacitor. (Test under the condition of rated input and rated output)

Voltage : +12V

Current : 5000mA

Ripple And Noise (Max) : 120m Vp-p

Turn On Delay Time

5 second Max .@ 100V AC input and output Max. Load

Rise Time

100ms Max. @ 100V AC input and output Max. Load

Hold Up Time

5ms Min. @ 100V AC input and output Max. Load.

Overshoot

10% Max. When power supply on or turn off.

Environmental Requirements

Operating Temperature : 0°C to +45°C (Full Load, Normal operation)

Storage temperature : -10°C to +75°C (With enclosure)

Relative Humidity : 5% (0°C) to 90% (40°C) 72h (Full Load, Normal operation)

Vibration : Operating: IEC 721-3-3 3M3 5~9Hz, A=1.5mm (9~200Hz, Acceleration 5m/s)



