


EXEMPLARY LOADED



CONTACT DIMENSIONS



PART NO.	PLATING TABLE Δ			
	UNDER-COATING $\mu\text{m Ni MIN.}$	CONTACT AREA $\mu\text{m Au MIN.}$	ACTION-PIN AREA μm	CONSERVATION TREATMENT
352332-1	1,27	0,76	0,5-2,5 Sn/Pb	NO
352332-9	1,27	0,76	0,5-2,5 Sn/Pb	YES
-	-	-	-	-
-	-	-	-	-
-	-	-	-	-

NOTES:

- ① FOR FINISH TYPES SEE PLATING TABLE.
- ② MATERIAL CONTACT: PHOSPHORBRONZE.
MATERIAL HOUSING: GREY GLASSFILLED POLYESTER
UL-RATING 94VO.
- ③ CONNECTOR PRINTED WITH PART NUMBER AND DATE CODE.
- ④ PLATED-THROUGH HOLES AT 2x2mm SQUARE GRID,
TOTAL 154 HOLES.
- ⑤ AREA FOR KEYING PART (BASIC PART NUMBER 100525).
- ⑥ FOR ACTUAL PIN LOADING SEE "CONTACT LAYOUT".
- ⑦ LOCATION PEG.
- ⑧ CONNECTOR LUBRICATED WITH BELLCORE
APPROVED LUBRICANT TECHNICAL REFERENCE
TR-NWT-001217 ISSUE 1 SEPT 1992



RECOMMENDED PCB-HOLE LAY-OUT
COMPONENT SIDE SHOWN

P.C.B. HOLE DIM. ACTION PIN

DRILLED HOLE: $0,7 \pm 0,025 \text{ mm}$

FIN. HOLE : 0,55 TO 0,65mm

Cu-thks : 0,025 TO 0,050mm


DO NOT SCALE

DIMENSIONS IN mm

METRIC

THIRD ANGLE

PROJECTION



CONTACT LAYOUT

		z	a	b	c	d	e	f
1		C	B	B	B	B	B	C
2		C	B	B	C	B	B	C
3		C	B	B	B	C	B	C
4		C	B	B	C	B	B	C
5		C	B	B	B	B	B	C
6		C	B	B	B	B	B	C
7		C	B	B	B	C	B	C
8		C	B	B	B	B	B	C
9		C	B	B	B	C	B	C
10		C	B	B	B	B	B	C
11		C	B	B	B	A	B	C
		MULTI PURPOSE CENTRE						
15		C	B	B	B	C	B	C
16		C	B	B	B	B	B	C
17		C	B	A	B	C	B	C
18		C	B	B	B	B	B	C
19		C	B	B	B	C	B	C
20		C	B	B	C	B	B	C
21		C	B	B	B	C	B	C
22		C	B	B	C	B	B	C
23		C	B	B	B	C	B	C
24		C	B	B	B	B	B	C
25		C	B	B	B	B	B	C

[illegible]