



Color: white

Electrical data

Ratings per IEC/EN	
Nominal voltage (III/3)	800 V
Rated impulse voltage (III/3)	8 kV
Rated current	30 A

Material data

Note (material data)		Information on material specifications can be found here
Color	white	
Insulation material	Polyamide (PA66)	
Flammability class per UL94	V0	
Fire load	0.029 MJ	
Weight	2.2 g	

Environmental requirements

Continuous operating temperature	105 °C
----------------------------------	--------

Commercial data

Product Group	22 (TOPJOB S)
eCl@ss 10.0	27-14-11-92
eCl@ss 9.0	27-14-11-92
ETIM 8.0	EC002848
ETIM 7.0	EC002848
PU (SPU)	100 (25) pcs
Packaging type	Box
Country of origin	DE
GTIN	4055143094689
Customs tariff number	85366990990

Approvals / Certificates

Declarations of conformity and manufacturer's declarations



Approval	Standard	Certificate Name
Railway WAGO GmbH & Co. KG	-	Railway Ready

Downloads

Environmental Product Compliance

Compliance Search
Environmental Product Compliance 2006-401/000-050



Documentation

Additional Information
Technical Section

pdf
2142.18 KB



Bid Text			
2006-401/000-050	19.02.2019	xml 2.58 KB	
2006-401/000-050	28.04.2017	doc 23.50 KB	



CAD/CAE-Data


CAD data
2D/3D Models 2006-401/000-050



CAE data	
EPLAN Data Portal 2006-401/000-050	
ZUKEN Portal 2006-401/000-050	



Installation Notes



Carrier terminal block (2006-1661) with
disconnect plug (2006-401/050-000) in
operating position