


THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF L-COM, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF L-COM, INC. IS PROHIBITED.

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	1/28/14	D.GRIFFIN



ONE 28AWG STRANDED TINNED COPPER TWISTED PAIR
 TWO 24AWG STRANDED TINNED COPPER CONDUCTORS
 OVERALL ALUMINIZED POLYESTER SHIELD WITH DRAIN WIRE
 PLUS TINNED COPPER BRAIDED SHIELD.
 PVC OUTER JACKET: BLACK

"P2"
 USB SERIES "B"
 STRAIGHT PLUG
 CONTACTS: 30 μINCHES
 GOLD PLATING


"P1"
 USB SERIES "A"
 LEFT ANGLE PLUG
 CONTACTS: 30 μINCHES
 GOLD PLATING

2X, MOLDED HOOD
 AND STRAIN RELIEF,
 PVC, BLACK

DIELECTRIC

(.463 MIN.)
 [11.75]

PIN 1



PART NUMBER	LENGTH	
	METERS	FEET
CABLK90LA-B-03M	0.3	.98
CABLK90LA-B-05M	0.5	1.64
CABLK90LA-B-1M	1.0	3.28
CABLK90LA-B-2M	2.0	6.56
CABLK90LA-B-3M	3.0	9.84
CABLK90LA-B-5M	5.0	16.40

- NOTES:**
1. CABLE ASSEMBLY SHALL HAVE 360° SHIELD TERMINATION.
 2. CABLE ASSEMBLY SHALL MEET USB 2.0 REQUIREMENTS.
 3. CABLE ASSEMBLY SHALL BE TESTED FOR CONTINUITY.
 4. CABLE ASSEMBLY SHALL BE INDIVIDUALLY PACKAGED IN ACCORDANCE WITH L-COM SPECIFICATION PS-0031.

REGULATORY COMPLIANCE:
 CE2011/65/EU(RoHS DIRECTIVE)

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES [mm] OVERALL CABLE LENGTH TOLERANCE: ≤12 [305] = +1 [25] / -0 >12 [305] ≤60 [1524] = +2 [51] / -0 >60 [1524] ≤120 [3048] = +4 [102] / -0 >120 [3048] ≤300 [7620] = +6 [152] / -0 >300 [7620] = +5% / -0%	APPROVALS	DATE		45 BEECHWOOD DRIVE NORTH ANDOVER, MA 01845
	DRAWN BY D.FRISIELLO	1/27/14		CATEGORY
ALL OTHER DIMENSIONAL TOLERANCES: .X = ± .2 [5.08] .XX = ± .02 [1.51] .XXX = ±.005 [1.3]	CHECKED BY R.SCOTT	1/27/14	PRODUCT DESCRIPTION	
PROJECTION	APPROVED BY S. SMITH	1/27/14	CA USB 90LA A/STR B BLK	
	CONFIGURATION DETAILS OF UNDIMENSIONED FEATURES MAY VARY	COLOR VARIATIONS MAY OCCUR	SIZE A	FSCM NO. 43321
			DWG. NO. CABLK90LA-B	REV. A
			SCALE: NONE	CAD FILE: CABLK90LA-B.SLDDRW
				SHEET 1 OF 1