





8 7 6 5 4 3 2 1

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF L-COM, INC.. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF L-COM, INC. IS PROHIBITED.

REVIEWS			
REV	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	1/15/16	D.GRIFFIN
B	ECN 8306: UPDATE TO USB TYPE C VERSION 1.2, ADD CONNECTION LINE TO THE WIRE MAP	4/20/16	S.LI



USB 2.0 PLUG
SERIES "C"
30μ INCHES
GOLD PLATING



USB 2.0 PLUG
SERIES "B"
30μ INCHES
GOLD PLATING

UL STYLE 2725,
(1) 28AWG STRANDED TINNED COPPER TWISTED PAIR
(2) 28AWG STRANDED TINNED COPPER CONDUCTORS
OVERALL ALUMINUM/POLYESTER SHIELD PLUS TINNED
COPPER BRAID SHIELD AND DRAIN WIRE
JACKET: PVC, BLACK (NOM DIA. .126" [3.2])

B

WIRE MAP					
"P1"	SIGNAL NAME	CONDUCTOR	"P2"	SIGNAL NAME	COLOR
A1,B1,A12,B12	GND	INDV.	4	GND	BLACK
A4,B4,A9,B9	VBUS	INDV.	1	VBUS	RED
A5	CC	N/C			
B5	VCONN	N/C			
A6	Dp1	UNSHIELDED PAIR	3	D+	GREEN
A7	Dn1		2	D-	WHITE
SHELL	SHIELD	BRAID	SHELL	SHIELD	N/A

PART NUMBER	LENGTH METERS [FEET]
CAU2CB-03M	0.3 [.98]
CAU2CB-05M	0.5 [1.64]
CAU2CB-1M	1.0 [3.28]
CAU2CB-2M	2.0 [6.56]
CAU2CB-3M	3.0 [9.84]
CAU2CB-5M	5.0 [16.40]

NOTES:

- CABLE ASSEMBLY SHALL HAVE 360° SHIELD TERMINATION.
- CABLE ASSEMBLY SHALL BE TESTED FOR CONTINUITY.
- L-COM LOGO AND USB ICON MAY BE ON ANY SIDE OF THE OVERMOLD FOR USB SERIES "C" END.
- CABLE ASSEMBLY SHALL BE INDIVIDUALLY PACKAGED IN ACCORDANCE WITH L-COM SPECIFICATION PS-0031.

REGULATORY COMPLIANCE:

CE2011/65/EU(RoHS DIRECTIVE)

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES [mm] OVERALL CABLE LENGTH TOLERANCE: ≤12 [305] = +1 [25] / -0 >12 [305] ≤60 [1524] = +2 [51] / -0 >60 [1524] ≤120 [3048] = +4 [102] / -0 >120 [3048] ≤300 [7620] = +6 [152] / -0 >300 [7620] = +3% / -0% ALL OTHER DIMENSIONAL TOLERANCES: .X = ±.2 [5.08] .XX = ±.02 [.51] .XXX = ±.005 [.13] PROJECTION 	APPROVALS	DATE	 50 HIGH STREET NORTH ANDOVER, MA 01845	
	DRAWN BY D. CASTRO	4/23/15		
	CHECKED BY S. LI	1/15/16	CATEGORY USB	
	APPROVED BY S. LI	1/15/16	PRODUCT DESCRIPTION CBL USB 2.0 TYPE C/B	
CONFIGURATION DETAILS OF UNDIMENSIONED FEATURES MAY VARY		SIZE A	FSCM NO. 43321	DWG. NO. CAU2CB
COLOR VARIATIONS MAY OCCUR		SCALE: NONE	CAD FILE: CAU2CB.SLDDRW	REV. B
		SHEET 1 OF 1		