



THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF L-COM, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF L-COM, INC. IS PROHIBITED.


RoHS Compliant ✓

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	9/9/11	D.GRIFFIN
B	ECN 5868: ADDED LENGTH 03 M, 075 M	12/1/11	D.FRISIELLO
C	ECN 6451: UPDATED LOGOS, NOTES, AND CHANGED EXPOSED CONN. DIM.	10/10/12	D. DESJARDIN



ONE 28AWG STRANDED (19X40) TINNED COPPER TWISTED PAIR
TWO 24AWG STRANDED (42X40) TINNED COPPER CONDUCTORS
DRAIN WIRE, 28AWG STRANDED (19X40) TINNED COPPER
OVERALL ALUMINIZED POLYESTER SHIELD PLUS TINNED COPPER BRAID SHIELD
POLYURETHANE OUTER JACKET, BLACK

MODEL NUMBER	LENGTH METERS [FEET]
CAUAAHFX-03M	.3 [.98]
CAUAAHFX-05M	.5 [1.64]
CAUAAHFX-075M	.75 [2.46]
CAUAAHFX-1M	1.0 [3.28]
CAUAAHFX-2M	2.0 [6.56]
CAUAAHFX-3M	3.0 [9.84]
CAUAAHFX-5M	5.0 [16.41]



NOTES:

1. CABLE IS RATED FOR 10,000 BEND CYCLES, MINIMUM
2. CABLE ASSEMBLY SHALL HAVE 360° SHIELD TERMINATION.
3. CABLE ASSEMBLY SHALL MEET USB 2.0 REQUIREMENTS.
4. CABLE ASSEMBLY SHALL BE TESTED FOR CONTINUITY.
5. CABLE ASSEMBLY SHALL BE INDIVIDUALLY PACKAGED IN ACCORDANCE WITH L-COM SPECIFICATION PS-0031.

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES [mm] OVERALL CABLE LENGTH TOLERANCE: ≤12 [305] = +1 [25] / -0 >12 [305] ≤60 [1524] = +2 [51] / -0 >60 [1524] ≤120 [3048] = +4 [102] / -0 >120 [3048] ≤300 [7620] = +6 [152] / -0 >300 [7620] = +5% / -0% ALL OTHER DIMENSIONAL TOLERANCES: .X = ±.2 .XX = ±.02 .XXX = ±.005 PROJECTION 	APPROVALS	DATE	 45 BEECHWOOD DRIVE NORTH ANDOVER, MA 01845	
	DRAWN BY D. PARHAM	05/19/2011		
	CHECKED BY D.GRIFFIN	9/9/11	CATEGORY USB	
	APPROVED BY S.SMITH	9/9/11	PRODUCT DESCRIPTION CA,USB A/A HI-FLEX	
COLOR VARIATIONS MAY OCCUR	SIZE A	FSCM NO. 43321	DWG. NO. CAUAAHFX	REV. C
	SCALE: NONE	CAD FILE: CAUAAHFX.SLDDRW	SHEET 1 OF 1	