



THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF L-COM, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF L-COM, INC. IS PROHIBITED.

RoHS Compliant ✓

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	9/9/11	D.GRIFFIN
B	ECN 5868: ADDED LENGTHS 03 M, 075 M	12/1/11	D.FRISIELLO
C	ECN 6451: UPDATED LOGOS, NOTES, AND CHANGED EXPOSED CONN. DIM.	10/10/12	D. DESJARDIN




PIN 1
DIELECTRIC
"P1"
SERIES "A"
USB PLUG
CONTACTS: 30 μINCHES
GOLD PLATING



PIN 1
"P2"
SERIES "B"
USB PLUG
CONTACTS: 30 μINCHES
GOLD PLATING

ONE 28AWG STRANDED (19X40) TINNED COPPER TWISTED PAIR
TWO 24AWG STRANDED (42X40) TINNED COPPER CONDUCTORS
DRAIN WIRE, 28AWG STRANDED (19X40) TINNED COPPER
OVERALL ALUMINIZED POLYESTER SHIELD PLUS TINNED COPPER BRAID SHIELD
POLYURETHANE OUTER JACKET, BLACK

MODEL NUMBER	LENGTH METERS [FEET]
CAUABHFX-03M	.3 [.98]
CAUABHFX-05M	.5 [1.64]
CAUABHFX-075M	.75 [2.46]
CAUABHFX-1M	1.0 [3.28]
CAUABHFX-2M	2.0 [6.56]
CAUABHFX-3M	3.0 [9.84]
CAUABHFX-5M	5.0 [16.41]



NOTES:

- CABLE IS RATED FOR 10,000 BEND CYCLES, MINIMUM
- CABLE ASSEMBLY SHALL HAVE 360° SHIELD TERMINATION.
- CABLE ASSEMBLY SHALL MEET USB 2.0 REQUIREMENTS.
- CABLE ASSEMBLY SHALL BE TESTED FOR CONTINUITY.
- CABLE ASSEMBLY SHALL BE INDIVIDUALLY PACKAGED IN ACCORDANCE WITH L-COM SPECIFICATION PS-0031.

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES [mm] OVERALL CABLE LENGTH TOLERANCE: ≤12 [305] = +1 [25] / -0 >12 [305] ≤60 [1524] = +2 [51] / -0 >60 [1524] ≤120 [3048] = +4 [102] / -0 >120 [3048] ≤300 [7620] = +6 [152] / -0 >300 [7620] = +3% / -0% ALL OTHER DIMENSIONAL TOLERANCES: .X = ±.2 .XX = ±.02 .XXX = ±.005 PROJECTION 	APPROVALS DRAWN BY D. PARHAM CHECKED BY D.GRIFFIN APPROVED BY S.SMITH	DATE 05/19/2011 9/9/11 9/9/11	 45 BEECHWOOD DRIVE NORTH ANDOVER, MA 01845	
	CONFIGURATION DETAILS OF UNDIMENSIONED FEATURES MAY VARY		CATEGORY USB	
	COLOR VARIATIONS MAY OCCUR		PRODUCT DESCRIPTION CA,USB A/B HI-FLEX	
	SIZE A	FSCM NO. 43321	DWG. NO. CAUABHFX	REV. C
SCALE: NONE		CAD FILE: CAUABHFX.SLDDRW		SHEET 1 OF 1