



THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF L-COM, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF L-COM, INC. IS PROHIBITED.

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
B	ECN#1965: CHANGING BRAIDED SHIELD TO SPIRAL STYLE	01/31/05	M.LAHEY
C	ECN#2286 ADDED ARROW TO TYPE A PLUG	01/04/06	MCCORMICK
D	ECN# 2305 REVISED EXPANDED LENGTH FROM 10.5 FEET	02/01/06	MCCORMICK
E	ECN# 2419 ADDED .463" MIN DIMENSION	05/18/06	MCCORMICK



WIRING DIAGRAM



NOTES:

1. THESE CABLE ASSEMBLIES ARE CONSTRUCTED TO MEET THE REQUIREMENTS OF THE UNIVERSAL SERIES BUS SPECIFICATION USB 2.0.
2. CONNECTOR CONTACTS HAVE 30 MICROINCHES GOLD PLATING OVER NICKEL PLATING.
3. THE CABLE SHIELD DRAIN WIRE IS CONNECTED TO THE METAL SHELL OF EACH PLUG.

UNLESS OTHERWISE SPECIFIED,
DIMENSIONS ARE IN INCHES
TOLERANCES ARE:
X ±.1
XX ±.05
XXX ±.005
CABLE LENGTH TOLERANCE
<300" ±5% >300" ±2%

APPROVALS	DATE
DRAWN BY C.MCCORMICK	10/01/2004
CHECKED BY D.PARHAM	10/01/2004
APPROVED BY R.CARRICK	10/01/2004

CONFIGURATION DETAILS OF
UNDIMENSIONED FEATURES
MAY VARY

L-com CONNECTIVITY PRODUCTS		45 BEECHWOOD DRIVE NORTH ANDOVER, MA 01845	
PRODUCT DESCRIPTION			
TYPE "A" LATCHING PLUG TO TYPE "B" PLUG			
DRAWING TITLE			
OUTLINE DRAWING			
SIZE A	FSCM NO. 43321	DWG. NO. COILUAB-OD1	REV. E
SCALE: NONE		CAD FILE: COILUAB-OD1.SLDDRW	SHEET 1 OF 1