

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF L-COM, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF L-COM, INC. IS PROHIBITED.

PART NUMBER	LENGTH	
	INCHES	MM
ECF504-12AAS	12.0	[304.8]
ECF504-24AAS	24.0	[609.6]
ECF504-36AAS	36.0	[914.4]
ECF504-72AAS	72.0	[1828.8]
ECF504-120AAS	120.0	[3048.0]

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
J	ECN 8409: ADD TEMPERATURE RATING -10~70°C	7/15/16	S.LI
K	ECN 8666: REVISED ADAPTER TO USB 2.0 STANDARDS	3/9/17	D.FRISIELLO
L	ECN8674: REVISE STRAIN RELIEF FROM 2 PCS TO 1PC TYP. IN THE PNL MNT END.	03/15/2017	B.ZHANG



D

C



B

A


PIN 1
DIELECTRIC
"P1"
USB SERIES "A" PLUG
CONTACTS: 30 μINCHES
GOLD PLATING



MOLDED PVC HOOD,
COLOR: LIGHT GRAY
(PANTONE 400C)




"J1"
USB SERIES "A" RECEPTACLE
BULKHEAD ADAPTOR
CONTACTS: 30 μINCHES
GOLD PLATING



RECOMMENDED
PANEL CUT OUT

"P1" WIRING DIAGRAM




NOTES:

1. OPERATING TEMPERATURE: -10°C TO +70°C
2. CABLE ASSEMBLY SHALL HAVE 360° SHIELD TERMINATION.
3. CABLE ASSEMBLY SHALL MEET USB 2.0 REQUIREMENTS.
4. CABLE ASSEMBLY SHALL BE TESTED FOR CONTINUITY.
5. CABLE ASSEMBLY SHALL BE INDIVIDUALLY PACKAGED IN ACCORDANCE WITH L-COM SPECIFICATION PS-0031.

REGULATORY COMPLIANCE:

CE2011/65/EU(RoHS DIRECTIVE)

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES [mm] OVERALL CABLE LENGTH TOLERANCE: ≤12 [305] = +1 [25] / -0 >12 [305] ≤60 [1524] = +2 [51] / -0 >60 [1524] ≤120 [3048] = +4 [102] / -0 >120 [3048] ≤300 [7620] = +6 [152] / -0 >300 [7620] = +5% / -0% ALL OTHER DIMENSIONAL TOLERANCES: .X = ±.2 [5.08] .XX = ±.02 [1.51] .XXX = ±.005 [1.13] PROJECTION 	APPROVALS	DATE	 Global Connectivity 50 HIGH STREET NORTH ANDOVER, MA 01845 CATEGORY USB PRODUCT DESCRIPTION USB A-F PNL MNT/A-M SHLD SIZE A FSCM NO. 43321 DWG. NO. ECF504-AAS REV. L	
	DRAWN BY C.MCCORMICK	04/02/2003		
	CHECKED BY D.PARHAM	04/02/2003		
	APPROVED BY R.CARRICK	04/02/2003		
	CONFIGURATION DETAILS OF UNDIMENSIONED FEATURES MAY VARY			
	COLOR VARIATIONS MAY OCCUR		SCALE: NONE CAD FILE: ECF504-AAS.SLDDRW	
			SHEET 1 OF 1	