






THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF L-COM, INC. ANY REPRODUCTIONS IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF L-COM, INC. IS PROHIBITED.

REVISIONS			
REV	DESCRIPTION	DATE	CHANGED BY
L	ECN 8473:UPD DWG TO MATCH NEW DESIGN. ADD MATERIAL NOTE 7 INFO	09/02/2016	DCUI
M	ECN 8516:UPD NOTES 4&5,CANCELED NOTES 3	10/20/2016	DCUI
N	ECN 9243:ADDED NEW PART NUMBER WPUSBAX-03M ON THE TABLE	06/12/2018	DCUI
P	ECN 12047:REVISED NOTES, ADDED NOTE 4 (TORQUE), REVISED FORMAT	09/02/2022	GUITTAURO



PART NUMBER	LENGTH	
	METER	FEET
WPUSBAX-03M	0.3	0.98
WPUSBAX-05M	0.5	1.64
WPUSBAX-1M	1.0	3.28
WPUSBAX-2M	2.0	6.56
WPUSBAX-3M	3.0	9.84
WPUSBAX-5M	5.0	16.41

- NOTES:**
1. THESE CABLE ASSEMBLIES ARE CONSTRUCTED TO MEET THE REQUIREMENTS OF THE UNIVERSAL SERIAL BUS SPECIFICATION USB 2.0
  2. CONNECTOR CONTACTS HAVE 30 μINCHES GOLD PLATING OVER NICKEL PLATING
  3. CABLE ASSEMBLY SHALL BE TESTED FOR CONTINUITY
  4. SUGGESTED MAX. TORQUE VALUE FOR HEX NUT IS 1.0N-m (8.8 lbf-in)
  5. INGRESS PROTECTION RATING IS IP67 (J1 ONLY ,MATED)
  6. CABLE ASSEMBLY SHALL BE INDIVIDUALLY PACKAGED IN ACCORDANCE WITH L-COM SPECIFICATION PS-0031

**REGULATORY COMPLIANCE:**  
EU ROHS DIRECTIVE (MOST RECENT RELEASED VERSION)

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES (mm). OVERALL CABLE LENGTH TOLERANCE: ±12 [305] = +1 [25] / -0 >12 [305] ≤60 [1524] = ±2 [51] / -0 >60 [1524] ≤120 [3048] = ±4 [102] / -0 >120 [3048] ≤300 [7620] = ±6 [152] / -0 >300 [7620] = ±5% / -0	APPROVALS	DATE	 50 High Street, West Mill, North Andover, MA 01845 USA. Phone: 1.800.341.5266 1.978.682.6936
	DRAWN BY C.MCCORMICK CHECKED BY D.FAIRHAM APPROVED BY R.CARRICK	07/29/2003	
ALL OTHER DIMENSIONAL TOLERANCES: .X = ±.02 [5]      FRACTIONS ± 1/32 .XX = ±.005 [13]      ANGLES ± 1°	CONFIGURATION DETAILS OF UNDIMENSIONED FEATURES MAY VARY		CATEGORY USB
THIRD-ANGLE PROJECTION	COLOR VARIATIONS MAY OCCUR		PRODUCT DESCRIPTION USB WATERPROOF SERIES "A" BULKHEAD TO SERIES "A" PLUG
	SIZE B	CAGE CODE 43321	ITEM NO. WPUSBAX
SCALE: NONE		CAD FILE: WPUSBAX.SLDRAW	REV P
			SHEET 1 OF 1