







MOUNTING HARDWARE TYP 2 PLACES

NOTES:

1. CONFORMS TO PERFORMANCE REQUIREMENTS OF MIL-DTL-12883.
2. MATERIALS:
HOUSING: POLYETHERIMIDE, COLOR: BLUE GREEN.
GROMMET - SILICONE RUBBER PER A-A-59588, 50±10 DUROMETER, COLOR: RED
3. SOCKET CONTACTS CONFORM TO PERFORMANCE REQUIREMENTS OF MIL-C-39029/92.
4. COMPLETE MOUNTING HARDWARE SUPPLIED.
5. OPERATING TEMPERATURE -70°C TO 125°C.
6. CONTACT INSTALLATION TOOLS:
* 12 CONTACT - CRIMP TOOL: M22520/1-01
POSITIONER: M22520/1-02
INSERTION/REMOVAL: M81969/14-04
* 16 CONTACT - CRIMP TOOL: M22520/1-01
POSITIONER: M22520/1-02
INSERTION/REMOVAL: M81969/14-03

RELAY SOCKET P/N		SUPPLIED CONTACTS				MARKING
MILITARY	APCD	SIZE	MIL P/N	APCD P/N	QTY	
M12883/55-01	RSE112034	CONTACTS NOT SUPPLIED				M12883/55-01 J 58982 XXXX RSE112035
	RSE112035	12/12	M39029/92-535	CNS128900	3	
		16/16	M39029/92-533	CNS126900	2	
M12883/55-02	RSE112036	12/16	M39029/92-536	CNS129900	3	M12883/55-02 J 58982 XXXX RSE112036
		16/16	M39029/92-533	CNS126900	2	
	RSE112039	CONTACTS NOT SUPPLIED				

DIMENSIONS ANSI Y14.5M UNITS: INCHES Pro/E FILE	TOLERANCES .XX ±0.01 .XXX ±0.005 ANGLES ±2.0°	PROJECTION 	Amphenol Pcd SPECIFICATION DRAWING ENGR M. DiGIACOMO 3/2/2010		TITLE RELAY SOCKET (3) SIZE 12, (2) SIZE 16 M12883/55		
ORIGINAL 	THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION WHICH IS THE CONFIDENTIAL PROPERTY OF AMPHENOL PCD INC. BEVERLY, MA, USA		CHKD  3/4/10	SIZE B	DWG NO. RSE112034		REV A
			APPD  3/4/10	CODE: 58982		SHEET 1 OF 1	