

LTMG708

PRODUCT OVERVIEW

The 7-cable LTMG708 antenna includes two Global 5G LTE antennas, four WiFi antennas and one GNSS antenna. This provides MIMO (multiple-input-multiple-output) coverage for both Cellular and WiFi. In addition, GNSS operates on GPS, Galileo, Glonass, QZSS or Beidou.

The Global LTE 5G-ready antenna element covers: 617-960 & 1710-6000 MHz. Cellular coverage includes these bands: CBRS (Citizen Band Radio Service) at 3.55-3.7 GHz and Band 71 at 617-698 MHz.

This 7 element antenna is part of our 626 line with a wider frequency covering sub-6 & 5G Ready.

Specify LTM708 for a model configured with GPS only.

Visit our eStore to customize an Antenna Online.


Electrical Specifications		
Frequency & Gain	LTE Cables 1 & 2	617 - 960 MHz, 3 dBi 1710 - 6000 MHz, 4 dBi
	WiFi Cables 3, 4, 5 & 6	2.4 - 2.5 & 4.9 - 6.0 GHz, 5 dBi
	GNSS Cable 7	1561, 1575, & 1602 MHz, LNA 26 dB, 5 dBi
VSWR	< 2:1 VSWR over Range	
Impedance	50 Ohm Nominal	
Power Rating	10 Watts	
GNSS	Amplifier Gain	16 dB
	Amplifier Bias Voltage	3 to 5 VDC
	Noise Figure	2.0 dB max, 1.5 dB typical
	Current	20 mA max, 10 mA typical

Mechanical Specifications	
Radome Material & Color	ASA UV-Inhibitive Plastic, Available in Black or White
Radome Dimension	5.5" (13.9 cm) in diameter 2.38" (6.0 cm) in height
Standard Connectors (MALE)	SMA Plugs for LTE & GNSS, Rev Pol SMA Plugs for WiFi
Cables 1 - 6	Separate LL-195, 15 ft (4.5m)
GNSS Cable 7	RG-174, 15 ft (4.5 m)
Operating Temperature	-40° to +80° C
Mounting	7/8" (22.2 mm) Dia. Feed Through 3/4" (19 mm) Long Thread for Up to 1/2" (12.7 mm) Thick Surface
Shock & Vibration	IEEE1478, EN61373, MIL-810G, TIA 329.2-C
Water Ingress	IPX7 When Properly Mounted



MULTI-BAND ANTENNA

LTMG708-3C3C3J3J3J2C-WHT-120



HIGHLIGHTS:

- Multiband:
2x LTE, 4x WiFi, 1x GNSS
- Covers Sub-6 5G Ready
617 - 6000 MHz
Including CBRS & Band 71
- High Performance; High Gain
- Made-in-the-USA & UK

RELATED MODELS:

- LLPG708
(Same Freq, Lower Profile)
- MXFG708
(Same Freq, MaxFin Style)
- LTM708
(GPS Model)

COMMON APPLICATIONS:

- Vehicle Fleet Management
- WiFi Data Transfer
- Multiband Modems
- Public Transportation



US Headquarters +1.847.671.6690
US/CA Toll Free +1.800.648.2800
European Facility +44.1543.459555

www.MobileMark.com