


Data Sheet

Type Number 6430
Designation IEC CR 2430
System Li-Manganese dioxide / Organic Electrolyte

UL Recognition:..... MH 13654 (N)
Nominal Voltage 3 V
Typical Capacity C 280 mAh
 Load 5.6 kOhm, at 20°C down to 2 V



Weight (approx.) 4 g
Volume 1,3 ccm
Coding..... Date of Manufacturing Month/Year

Temperature Ranges
 Storage min -55°C max. 70°C
 Discharge min -20°C max. 65°C

Dimensions
 Diameter (A) min 24,2 max. 24,5
 Height (B) min 2,7 max. 3,0
 Shoulder Diameter[E].....
 Shoulder Height [C].....

Segment Electronic

Main Applications Watch
 Photo
 Electronic

Typical Capacities (at 20°C)

Discharge Type	Load	End Voltage:	2.0 V
Continuous	5600 Ω	Time:	560 h
24h/d, 7d/w		Capacity [mAh]:	280
Current [μA]:		Energy [mWh]:	785

All Data contained herein is for single cells

For battery applications, performance data may vary from single cell data, depending on specific battery configuration

VARTA Microbattery GmbH, Daimlerstr. 1, D-73479 Ellwangen/Jagst
 Tel.: (+49) 7961/921-0, Telefax: (+49) 7961/921-553

Subject to change without prior notice!
 Date of issue: 2004-12-16