

Solid-state relay, Hockey Puck, 1-phase, 125 A, 42 - 660 V, DC, high fuse protection

Part no. **HLR125/1H(DC)600V/S**
360056

General specifications		
Product name		Eaton Moeller series HLR solid state relay
Part no.		HLR125/1H(DC)600V/S
EAN		4015081998234
Product Length/Depth		28.8 millimetre
Product height		58.2 millimetre
Product width		44.8 millimetre
Product weight		0.1 kilogram
Compliances		RoHS Compliant CE Marked
Certifications		EAC UL 508 CE CCC UL-File No.: E338590 CSA-File No.: 603498
Product Tradename		HLR
Product Type		Solid-state relay
Product Sub Type		None
General information		
Degree of protection		IP20
Frequency rating		45 Hz - 65 Hz
Mounting position		Mount device in specified orientation and do not obstruct the heatsink
Number of phases		1
Number of pilot lights		1
Overvoltage category		III
Pollution degree		2
Rated impulse withstand voltage (Uimp)		6 kV (1.2/50 µs)
Series		HLR
Shock resistance		15/11 g/ms (according to EN 50155, EN 61373)
Type		Solid-state relay
Vibration resistance		2 g/axis (2-100 Hz, IEC 60068-2-6, EN 50155, EN 61373)
Voltage type		DC
Features & Functions		
Functions		Switching at zero-crossing
Electrical connection type for auxiliary- and control-current circuit		Screw connection
Electrical connection type of main circuit		Screw connection
Climatic environmental conditions		
Altitude		9
Ambient storage temperature - min		-40 °C
Ambient storage temperature - max		100 °C
Climatic proofing		95% relative humidity non-condensing at 40°C
Operating temperature - min		-40 °C
Operating temperature - max		80 °C
Electro magnetic compatibility		
Air discharge		8 kV (according to IEC/EN 61000-4-2)
Burst Impulse		Main: 2 kV, 5 kHz PC 1 (according to IEC/EN 61000-4-4) Control: 1 kV, 5 kHz PC 1 (according to IEC/EN 61000-4-4)
Contact discharge		4 kV (according to IEC/EN 61000-4-2)
Electromagnetic fields		10 V/m, 80 - 1000 MHz and 1.4 - 2.0 GHz, PC 1

			3 V/m, 2.0 - 2.7 GHz, PC 1
Immunity to line-conducted interference			10 V/m, 0.15 - 80 MHz, PC 1 (according to IEC/EN 61000-4-6)
Radio interference class			Class A
Terminal capacities			
Terminal capacity (flexible with ferrule)			Main: 1 x 1-4 mm ² , 2 x 1-4 mm ² Control: 1 x 0.5-2.5 mm ² , 2 x 0.5-2.5 mm ²
Terminal capacity (solid)			Main: 1 x 2.5-6 mm ² , 2 x 2.5-6 mm ² Control: 1 x 0.5-2.5 mm ² , 2 x 0.5-2.5 mm ²
Terminal capacity (solid/stranded AWG)			Main: 1 x 14-10, 2 x 14-10 Control: 1 x 18-12, 2 x 18-12
Terminal capacity (stranded)			Main: 1 x 2.5-6 mm ² , 2 x 2.5-6 mm ² Control: 1 x 0.5-2.5 mm ² , 2 x 0.5-2.5 mm ²
Tightening torque			Main: 2.4 Nm (21.2 lb-in) Control: 0.5 Nm (4.4 lb-in)
Screwdriver size			Main: Pozidriv 2 Control: Pozidriv 1
Electrical rating			
Operating voltage - max.			660 V
Operating voltage - min.			42 V
Rated operational current (Ie) at AC-1			0 A
Rated operational current (Ie) at AC-3			0 A
Rated operational current (Ie) at AC-51			125 A
Rated operational current (Ie) at AC-53A			30 A
Rated operational current (Ie) at AC-53B			0 A
Rated operational voltage (Ue) at AC - min			42 V
Rated operational voltage (Ue) at AC - max			660 V
Short-circuit rating			
Rated conditional short-circuit current, type 1, 600 Y/347 V			kA
Rated conditional short-circuit current (Iq), type 2, 230 V			kA
Rated conditional short-circuit current (Iq), type 2, 380 V, 400 V, 415 V			kA
Control circuit			
Delay time			1/2 period
Drop-out time			< 1/2 period
Drop-out voltage			1.2 V DC
Input current			< 12 mA
Pick-up voltage			3.5 V DC
Rated control supply voltage (Us) at AC, 50 Hz - min			0 V
Rated control supply voltage (Us) at AC, 50 Hz - max			0 V
Rated control supply voltage (Us) at AC, 60 Hz - min			0 V
Rated control supply voltage (Us) at AC, 60 Hz - max			0 V
Rated control supply voltage (Us) at DC - min			4 V
Rated control supply voltage (Us) at DC - max			32 V
Design verification			
Equipment heat dissipation, current-dependent Pvid			132 W
Heat dissipation per pole, current-dependent Pvid			132 W
Rated operational current for specified heat dissipation (In)			125 A
Static heat dissipation, non-current-dependent Pvs			0 W
10.2.2 Corrosion resistance			Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures			Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat			Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects			Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation			Please enquire
10.2.5 Lifting			Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact			Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions			Meets the product standard's requirements.
10.3 Degree of protection of assemblies			Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances			Meets the product standard's requirements.

10.5 Protection against electric shock			Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components			Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections			Is the panel builder's responsibility.
10.8 Connections for external conductors			Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength			Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage			Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material			Is the panel builder's responsibility.
10.10 Temperature rise			The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function			The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 8.0

Relays (EG000019) / Solid state relay (EC002055)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Contactor (LV) / Solid state relay (ecl@ss10.0.1-27-37-10-14 [ACN970011])			
Rated control supply voltage Us at AC 50HZ	V		0 - 0
Rated control supply voltage Us at AC 60HZ	V		0 - 0
Rated control supply voltage Us at DC	V		4 - 32
Voltage type for actuating			DC
Operating voltage	V		42 - 660
Rated operation current Ie at AC-1	A		0
Rated operation current Ie at AC-3	A		0
Rated operation current Ie at AC-51	A		125
Rated operation current Ie at AC-53a	A		30
Rated operation current Ie at AC-53b	A		0
Number of phases			1
Modular version			No
Switching at zero-crossing			Yes