


GP Batteries

Data Sheet


Model No.: GP400LAHT

Type	High Temperature Rechargeable Nickel Metal Hydride Cylindrical Cell		
Nominal Dimension (with Sleeve)	$\Phi = 18.3\text{mm}$ $H = 70\text{mm}$		
Applications	Recommended discharge current 400mA to 4000mA		
Nominal Voltage	1.2V		
Nominal Capacity	Minimum : 4000 mAh Typical : 4200mAh when discharge at 800mA to 1.0V at 20°C		
Charging Condition	400mA for 16 hrs at 20°C		
Service Life	>350 cycles (IEC 61951-2)		
Continuous Overcharge	Comply with IEC61951-2 Permanent Charge Endurance Test		
Weight	70.0 g		
Internal Resistance	Average 22m Ω upon fully charged (Range 19-25m Ω) at 1000Hz		
Max. Charging Voltage	1.5V at 400mA charging		
Ambient Temperature Range	Charging	:	0 to 70°C
	Discharging	:	-20 to 70°C
	Storage	:	-20 to 35°C
	Storage (1 week)	:	-20 to 60 °C



Low Rate Discharge



High Rate Discharge



Available Capacity (%)



* The information (subject to change without prior notice) contained in this document is for reference only and should not be used as a basis for product guarantee or warranty. For applications other than those described here, please consult your nearest GP Sales and Marketing Office or Distributors.