



Features

- Microminiature relay
- Dimensions: 20.4mm × 7mm × 14.9mm
- Slim type, 7mm width
- High mounting density
- High sensitivity 200mW
- Switching capacity : 7A

Specification


Contact Data		
Contact Form		1 Form A
Contact Material		Ag Alloy
Contact Rating		GP:7A 250V AC,10A 250V AC, TV-5 250V AC
Contact Resistance		Max.100mΩ (6V DC 1A)
Load	Max. Switching Voltage	277V AC/30V DC
	Max. Switching Current	10A
	Max. Switching Power	2500VA,300W
	Min. Switching Load	5V DC,100mA
Life	Electrical	30,000 (7A,3s ON/3s OFF, 85°C) 10,000 (10A, 3s ON/3s OFF,85°C) 25,000 (TV-5, 40°C)
	Mechanical	10,000,000 operations
Coil Data		
Nominal Coil Power		200mW
General Data		
Insulation Resistance		Min. 1000MΩ 500V DC
Dielectric Strength	Between open contacts	1,000V AC, 1min
	Between coil and contacts	4,000V AC, 1min
Operate Time		Max. 10ms
Release Time		Max. 10ms
Operating Temperature		-40°C to +85°C
Humidity		5 to 85%RH, +40°C
Shock Resistanc	Endurance	1,000m/s ²
	Misoperation	100m/s ²
Vibration Resistance	Endurance	10 to 55Hz, 1.5mm double amplitude
	Misoperation	10 to 55Hz, 1.5mm double amplitude
Weight		Approximately 4g

Note:Data shown are of initial value


Coil Data

Model	Nominal Voltage V DC	Coil Resistance $\Omega \pm 10\%$	Operate Voltage $\leq V$ DC	Release Voltage $\geq V$ DC	Coil Power mW
MPAC6T-S-DC5V	5	125	3.75	0.5	200
MPAC6T-S-DC24V	24	2880	18	2.4	



Diagram



Mounting Hole Layout
(Bottom View)



Wiring Diagram
(Bottom View)



Part Number Table

Description	Part Number
Power Relay, PCB Type, NO, 0.2W, 7 Amp, 5V DC	MPAC6T-S-DC5V
Power Relay, PCB Type, NO, 0.2W, 7 Amp, 24V DC	MPAC6T-S-DC24V

Dimensions : Millimetres

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.