


RoHS  
Compliant

## Features

- Unique 36 pole strip
- Easily cut to required number of poles
- Can be supplied pre-cut to specified number of poles
- Dual horizontal or vertical mounting
- Moulded in grey UL94-V0 flame retardant PC
- Professional rising clamp terminals
- 0.2-2.5mm<sup>2</sup> (24-12AWG) solid & stranded cable
- Optional polarising clips
- Anti solder wicking
- Guided pin alignment
- Captive screws


## Specification

|                           |                                             |
|---------------------------|---------------------------------------------|
| Rating                    | : 16A/250V<br>UL=14A/300V, VDE&IMQ=16A/250V |
| Dielectric strength       | : $\geq 2.5\text{kV}$                       |
| Impulse withstand voltage | : 4kV                                       |
| Working temperature       | : 130°C                                     |
| Moulding                  | : UL94-V0 flame retardant PA66              |
| Pin/terminal              | : Tinned, nickel plated brass               |
| Rising Clamp              | : Zinc plated steel                         |
| Screw/torque              | : M2.5 steel zinc plated, 0.4Nm             |
| Recommended PCB hole size | : $\varnothing 1.3\text{mm}$                |







MCPTB9308/18 / MCPTB9308/6



MCPTB9358/10AO



MCPTB93VE/4



Dimensions : Millimetres

## Part Number Table

| Description                                               | Poles | Length | Part Number    |
|-----------------------------------------------------------|-------|--------|----------------|
| Terminal Block Header, Vertical, 5mm Pitch Pluggable      | 36    | 180mm  | MCPTB7300/36M  |
| Terminal Block Header, vertical, 5.08mm Pitch Pluggable   | 18    | 92.6mm | MCPTB9308/18   |
|                                                           | 6     | 31.7mm | MCPTB9308/6    |
| Terminal Block Header, Horizontal, 5.08mm Pitch Pluggable | 10    | 50.8mm | MCPTB9358/10AO |
| Terminal Block Header, Vertical, 3.81mm Pitch Pluggable   | 4     | 16.6mm | MCPTB93VE/4    |

**Important Notice :** This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.