

1A, 20 - 40V Schottky Barrier Surface Mount Rectifier

FEATURES

- Plastic package has carries underwriters
- Ideal for automated placement
- Surge overload rating to 25A peak
- Reliable low cost construction utilizing molded
- RoHS Compliant
- Halogen-free according to IEC 61249-2-21

APPLICATIONS

- Inverters
- Converters
- Adapters

MECHANICAL DATA

- Case: MELF
- Meet JESD 201 class 1A whisker test
- Polarity: Indicated by cathode band
- Weight: 120.00mg (approximately)

KEY PARAMETERS		
PARAMETER	VALUE	UNIT
I_F	1	A
V_{RRM}	20 - 40	V
I_{FSM}	25	A
$T_{J\ MAX}$	125	°C
Package	MELF	


**HALOGEN
FREE**


MELF

ABSOLUTE MAXIMUM RATINGS ($T_A = 25^\circ\text{C}$ unless otherwise noted)					
PARAMETER	SYMBOL	LL5817	LL5818	LL5819	UNIT
Repetitive peak reverse voltage	V_{RRM}	20	30	40	V
Reverse voltage, total rms value	$V_{R(RMS)}$	14	21	28	V
DC blocking voltage	V_{DC}	20	30	40	V
Forward current	I_F	1			A
Surge peak forward current 8.3ms single half sine-wave superimposed on rated load	I_{FSM}	25			A
Junction temperature	T_J	-65 to +125			°C
Storage temperature	T_{STG}	-65 to +125			°C

THERMAL PERFORMANCE

PARAMETER	SYMBOL	TYP	UNIT
Junction-to-Ambient thermal resistance	$R_{\theta JA}$	80	°C/W

ELECTRICAL SPECIFICATIONS ($T_A = 25^\circ\text{C}$ unless otherwise noted)

PARAMETER		CONDITIONS	SYMBOL	TYP	MAX	UNIT
Forward voltage ⁽¹⁾	LL5817	I _F = 1.0A	V _F	-	0.450	V
		I _F = 3.0A		-	0.750	
	LL5818	I _F = 1.0A		-	0.550	
		I _F = 3.0A		-	0.875	
	LL5819	I _F = 1.0A		-	0.600	
		I _F = 3.0A		-	0.900	
Reverse current @ rated V _R ⁽²⁾		T _J = 25°C	I _R	-	0.5	mA
		T _J = 100°C		-	5	mA
Junction capacitance		1MHz, V _R = 4.0V	C _J	110	-	pF

Notes:

1. Pulse test with $PW = 0.3\text{ms}$
2. Pulse test with $PW = 30\text{ms}$

ORDERING INFORMATION

ORDERING CODE ⁽¹⁾	PACKAGE	PACKING
LL581x L0G	MELF	5,000/13" reel

Notes:

1. "x" defines voltage from 20V(LL5817) – 40V(LL5819)

CHARACTERISTICS CURVES

($T_A = 25^\circ\text{C}$ unless otherwise noted)

Fig.1 Forward Current Derating Curve




Fig.2 Maximum Non-Repetitive Peak Forward Surge Current




Fig.3 Typical Forward Characteristics




Fig.4 Typical Reverse Characteristics




Fig.5 Typical Junction Capacitance






Fig.6 Typical Transient Thermal Impedance




PACKAGE OUTLINE DIMENSIONS

MELF



DIM	Unit (mm)		Unit (inch)	
	Min	Max	Min	Max
A	4.80	5.50	0.189	0.217
B	2.25	2.67	0.089	0.105
C	0.30	0.60	0.012	0.024

SUGGESTED PAD LAYOUT



DIM	Unit (mm)	Unit (inch)
	TYP	TYP
C	4.80	0.189
G	3.30	0.130
X	1.50	0.059
X1	6.30	0.248
Y	2.70	0.106

Notice

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Purchasers are solely responsible for the choice, selection, and use of TSC products and TSC assumes no liability for application assistance or the design of Purchasers' products.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.