

EXM10

10 x 38 mm EV fuse



Product features

- 10 x 38 mm fuse
- Current rating: 5 A to 50 A
- Up to 800 Vdc rating
- High breaking capacity for high energy applications
- Designed to JASO D622, ISO8820-8, GB/T31465
- Produced in a factory with ISO9001 & IATF16949 certification
- Minimum breaking capacity 300% In at rated DC voltage
- Bolt-down terminal and PCB terminal options

Applications

- Automotive and commercial grade on-board chargers
- Uninterruptible power supplies (UPS)
- 3-phase EVSE and charging infrastructure
- Motor protection
- Rectifiers and inverters
- Energy storage systems
- On-board electric vehicle powertrain and distribution

Agency information

UL (RU) recognition file number: E532712



Environmental compliance



Ordering part number

EXM10-30-SCT

Family code

Ampere rating (30 = 30 A)

Option code

Option code

1P = 1 pin PCB terminal

2P = 2 pin PCB terminal

SCT= Bolt down single cap

Electrical characteristics

Amps (A)	Minimum (seconds)	Maximum (seconds)
1.0 In	14,400	-
2.0 In	0.5	100
3.0 In	0.1	15
5.0 In	0.05	1

Product specifications

Part number	Rated voltage	Rated current (A)	Breaking capacity	Typical cold resistance ¹ (mΩ)	Typical voltage drop (mV)
EXM10-5	800 Vdc	5	800 Vdc/50 kA	31	250
EXM10-10	800 Vdc	10	800 Vdc/50 kA	12.5	180
EXM10-15	800 Vdc	15	800 Vdc/50 kA	7.2	150
EXM10-20	800 Vdc	20	800 Vdc/50 kA	5.2	154
EXM10-25	800 Vdc	25	800 Vdc/50 kA	4.0	145
EXM10-30	800 Vdc	30	800 Vdc/50 kA	3.1	150
EXM10-40	800 Vdc	40	800 Vdc/50 kA	2.2	148
EXM10-50	750 Vdc	50	750 Vdc/50 kA	1.6	155

1. Cold resistance is measured at <10% In and +25 °C ambient temperature


Dimensions- mm

Tolerances unless otherwise specified


One place x.x = ± 0.3 mm

Two places x.xx = ± 0.13 mm


SCT: Bolt-down single cap



1P: 1 pin PCB terminal



2P: 2 pin PCB terminal




Note: recommended tightening torque is 4.5+/-1.0 Nm for M5 Screw

Part marking

BUSS	Trademark
EXM10	Family name
30A	Rated current
800Vdc	Rated voltage
	Certificate

PCB layout 1P: 1 pin PCB terminal



PCB layout 2P: 2 pin PCB terminal



General specifications

Operating temperature: -40 °C to +125 °C with proper derating factor applied

Strength of terminals: JASO D622 6.3.9, mounting torque 4.5 +/-1 Nm, 3 times

Temperature humidity cycling: JASO D622 6.3.4.1,

a) maintain the samples at standard conditions for 4 hours

b) increase T to 55 +/-2 °C at 95% to 99% RH within 0.5 hours

c) maintain T at 55 +/-2 °C at 95% to 99% RH for 10 hours

d) decrease T to -40 +/-2 °C within 2.5 hours; the humidity is uncontrolled

e) maintain T at -40 +/-2 °C for 2 hours; the humidity is uncontrolled

f) increase T to 120 +/-2 °C within 1.5 hours from -40 +/-2 °C; the humidity is uncontrolled

g) maintain T at 120 +/-2 °C for 2 hours; the humidity is uncontrolled

h) allow to return to RT within 1.5 hours; the humidity is uncontrolled 10 cycles.

Thermal shock: ISO8820-8 GB/T31465.6, 48 cycles; -40 °C to 100 °C, each cycle 60 minutes

Vibration: JASO D622 6.3.3, 10-55 Hz, 3 directions, 2 hours each direction


Transient current cycling: JASO D622 6.3.2 (reference), The transient current start from 2.0 In for 0.25 seconds, then drop to 0.5 In and keep this current to 15 seconds to finish one cycle, total 50000 cycles

Lubricant & fuel oil resistance: GB/T31465.1-5.4, Wipe the marking with lubricant or oil 30 seconds


Packaging information

Terminals	Inner package	Ship package
SCT	40 pieces/tray	400 pieces/box
1P	20 pieces/bag	540 pieces/box
2P	20 pieces/box	640 pieces/box


Temperature derating curve




Current vs. time curve




I²t vs. time curve



I²t vs. current curve



Wave solder profile--PCB version only



Reference EN 61760-1:2006

Profile feature	Standard SnPb solder	Lead (Pb) free solder
Preheat		
• Temperature min. (T_{smin})	100 °C	100 °C
• Temperature typ. (T_{styp})	120 °C	120 °C
• Temperature max. (T_{smax})	130 °C	130 °C
• Time (T_{smin} to T_{smax}) (t_s)	70 seconds	70 seconds
Δ preheat to max Temperature	150 °C max.	150 °C max.
Peak temperature (T_p)*	235 °C – 260 °C	250 °C – 260 °C
Time at peak temperature (t_p)	10 seconds max 5 seconds max each wave	10 seconds max 5 seconds max each wave
Ramp-down rate	~ 2 K/s min ~3.5 K/s typ ~5 K/s max	~ 2 K/s min ~3.5 K/s typ ~5 K/s max
Time 25 °C to 25 °C	4 minutes	4 minutes

Manual solder

+350 °C (4-5 seconds by soldering iron), generally manual/hand soldering is not recommended.

Life Support Policy: Eaton does not authorize the use of any of its products for use in life support devices or systems without the express written approval of an officer of the Company. Life support systems are devices which support or sustain life, and whose failure to perform, when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.

Eaton reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Eaton also reserves the right to change or update, without notice, any technical information contained in this bulletin.

Eaton
Electronics Division
1000 Eaton Boulevard
Cleveland, OH 44122
United States
Eaton.com/electronics

© 2023 Eaton
All Rights Reserved
Printed in USA
Publication No. ELX1305 BU-ELX22168
May 2023

Eaton is a registered trademark.

All other trademarks are property
of their respective owners.

Follow us on social media to get the
latest product and support information.

