

W-Series
WSI 25/1 10x38**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 16

D-32758 Detmold

Germany

Fon: +49 5231 1429-0

Fax: +49 5231 14292083

www.weidmueller.com

**Klippon® Connect with clamping yoke Technology**

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easier and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

General ordering data

Type	WSI 25/1 10x38
Order No.	1966020000
Version	W-Series, Fuse terminal, Rated cross-section: 25 mm ² , Screw connection
GTIN (EAN)	4032248657766
Qty.	12 pc(s).

W-Series
WSI 25/1 10x38

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 1429-0
 Fax: +49 5231 14292083
 www.weidmueller.com

Technical data
Dimensions and weights

Width	18 mm	Width (inches)	0.709 inch
Height	81 mm	Height (inches)	3.189 inch
Depth	58 mm	Depth (inches)	2.283 inch
Weight	63 g	Net weight	51.25 g

Temperatures

Continuous operating temp., min.	-50 °C	Continuous operating temp., max.	120 °C
----------------------------------	--------	----------------------------------	--------

Material data

Material	PA 66/6	Colour	Dark Beige
UL 94 flammability rating	V-0		

System specifications

Version	Screw connection, Fuse cartridge, closed	End cover plate required	Yes
Number of potentials	1	Number of levels	1
No. of clamping points per level	2	Number of potentials per tier	1
Levels cross-connected internally	No	PE connection	No
Mounting rail	TS 35	N-function	No
PE function	No	PEN function	No

Additional technical data

Open sides	closed	Type of mounting	Snap-on
------------	--------	------------------	---------

CSA rating data

Certificate No. (CSA)	238018-1868186	Current size C (CSA)	30 A
Voltage size C (CSA)	600 V	Wire cross section max. (CSA)	3 AWG
Wire cross section min. (CSA)	18 AWG		

W-Series
WSI 25/1 10x38

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 1429-0
 Fax: +49 5231 14292083
 www.weidmueller.com

Technical data
Conductors for clamping (rated connection)

Clamping range, rated connection, max. 25 mm ²	Clamping range, rated connection, min. 1.5 mm ²
Connection direction	Cross-section for connected conductor, finely stranded with wire-end ferrules and plastic collars DIN 46228/4, rated connection, min. 1.5 mm ²
on side	Stripping length 11 mm
Number of connections 2	Tightening torque, min. 2 Nm
Tightening torque, max. 2.5 Nm	Wire connection cross section AWG, max. AWG 4
Type of connection Screw connection	Wire connection cross section, finely stranded with wire-end ferrules DIN 46228/1, rated connection, max. 25 mm ²
Wire connection cross section AWG, min. AWG 18	Wire connection cross section, finely stranded, max. 25 mm ²
Wire connection cross section, finely stranded with wire-end ferrules DIN 46228/1, rated connection, min. 1.5 mm ²	Wire connection cross section, solid core, min. rated connection 1.5 mm ²
Wire connection cross section, solid core max. rated connection 25 mm ²	Wire connection cross section, stranded, rated connection, min. 1.5 mm ²
Wire connection cross section, stranded, rated connection, max. 25 mm ²	Wire connection cross-section, finely stranded, min. 1.5 mm ²
Wire connection cross-section, finely stranded with wire-end ferrules and plastic collars DIN 46228/4, rated connection, max. 25 mm ²	

Dimensions

TS 35 offset	40.5 mm
--------------	---------

Fuse terminals

Cartridge fuse	max. 3W for gG/gL max. 1.2W for aM	Permitted power loss for fuse with semiconductor protection
Power loss, 1-pole ; 2-pole ; 3-pole		

Rating data

Rated cross-section 25 mm ²	Rated voltage 690 V
Rated voltage to adjoining terminal 690 V	Rated current 32 A
Current at maximum wires 32 A	Standards IEC 60947-7-3
Volume resistance according to IEC 60947-7-x 0.32 mΩ	Rated impulse withstand voltage 6 kV
Pollution severity 3	

UL rating data

Certificate No. (cURus)	E175322
-------------------------	---------

Classifications

ETIM 3.0	EC000899	ETIM 4.0	EC000899
ETIM 5.0	EC000899	ETIM 6.0	EC000899
UNSPSC	30-21-18-01	eClass 6.2	27-14-11-16
eClass 7.1	27-14-11-16	eClass 8.1	27-14-11-16
eClass 9.0	27-14-11-16	eClass 9.1	27-14-11-16

W-Series WSI 25/1 10x38

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 1429-0
Fax: +49 5231 14292083
www.weidmueller.com

Technical data

Product information

Descriptive text ordering data	1000 VDC rated voltage tested.
Descriptive text technical data	Suitable for fuse inserts acc. to IEC 60269-6 with power losses up to 3 W maximum. 440 V DC

Approvals

Approvals



ROHS	Conform
------	---------

Downloads

Approval/Certificate/Document of Conformity	DE_PT1003_20160419_014_ISSUE01.pdf
Brochure/Catalogue	CAT 1 TERM 16/17 EN
Engineering Data	EPLAN, WSCAD, Zuken E3.S

Safety note

Safety notice	Safety Information
---------------	------------------------------------