

|                   |            |                  |            |
|-------------------|------------|------------------|------------|
| MDT0320ASHH-MULTI | 240 x 320  | MULTI Interface  | TFT Module |
| Specification     |            |                  |            |
| Version: 1        |            | Date: 11/02/2021 |            |
| Revision          |            |                  |            |
| 1                 | 09/02/2021 | First issue      |            |

| Display Features      |                        |  |                  |
|-----------------------|------------------------|-------------------------------------------------------------------------------------|------------------|
| Display Size          | 3.20"                  |                                                                                     |                  |
| Resolution            | 240 x 320              |                                                                                     |                  |
| Orientation           | Portrait               |                                                                                     |                  |
| Appearance            | RGB                    |                                                                                     |                  |
| Logic Voltage         | 2.8V                   |                                                                                     |                  |
| Interface             | Parallel / SPI         |                                                                                     |                  |
| Brightness            | 1000 cd/m <sup>2</sup> |                                                                                     |                  |
| Touchscreen           | ---                    |                                                                                     |                  |
| Module Size           | 55.04 x 77.60 x 2.55mm |                                                                                     |                  |
| Operating Temperature | -20°C ~ +70°C          |                                                                                     |                  |
| Pinout                | 40 way FFC             |                                                                                     |                  |
| Pitch                 | 0.5mm                  | Box Quantity                                                                        | Weight / Display |
|                       |                        | ---                                                                                 | ---              |

\* - For full design functionality, please use this specification in conjunction with the ILI9341 specification.(Provided Separately)

| Display Accessories |             |
|---------------------|-------------|
| Part Number         | Description |
|                     |             |
|                     |             |
|                     |             |

| Optional Variants |         |
|-------------------|---------|
| Appearances       | Voltage |
|                   |         |
|                   |         |
|                   |         |



## Summary

TFT 3.2" is a TN transmissive type color active matrix TFT liquid crystal display that uses amorphous silicon TFT as switching devices. This module is composed of a TFT\_LCD module. It is usually designed for industrial application and this module follows RoHS,

## General Specifications

- Size: 3.2 inch
- Dot Matrix: 240x RGBx 320(TFT) dots
- Module dimension: 55.04 (W) x 77.6 (H) x 2.55(D) mm
- Active area: 48.6 x 64.8 mm
- Pixel pitch: 0.2025 x 0.2025 mm
- LCD type: TFT, Normally White, Transmissive
- View Direction: 6 o'clock
- Gray Scale Inversion Direction: 12 o'clock
- Aspect Ratio: Portrait
- Driver IC: ILI9341 or Equivalent
- Interface: 80 MCU 8bit /9bit/16bit/18bit/SPI(3 Wire/4 Wire)
- Backlight Type: LED, Normally White
- With /Without TP: Without TP
- Surface: Anti-Glare

\*Color tone slightly changed by temperature and driving voltage.



## Interface

### LCM PIN Definition

| NO | Symbol  | Function                                                                                                       | I/O |
|----|---------|----------------------------------------------------------------------------------------------------------------|-----|
| 1  | NC      | No connection                                                                                                  | —   |
| 2  | NC      | No connection                                                                                                  | —   |
| 3  | NC      | No connection                                                                                                  | —   |
| 4  | NC      | No connection                                                                                                  | —   |
| 5  | VCI     | Power supply(TYP: 2.8V).                                                                                       | P   |
| 6  | IOVCC   | Power supply(TYP:1.8V/2.8V).                                                                                   | P   |
| 7  | R5      | 18-bit parallel bi-directional data bus for MCU system and RGB interface mode Fix to VSS level when not in use | I/O |
| 8  | R4      |                                                                                                                |     |
| 9  | R3      |                                                                                                                |     |
| 10 | R2      |                                                                                                                |     |
| 11 | R1      |                                                                                                                |     |
| 12 | R0      |                                                                                                                |     |
| 13 | G5      |                                                                                                                |     |
| 14 | G4      |                                                                                                                |     |
| 15 | G3      |                                                                                                                |     |
| 16 | G2      |                                                                                                                |     |
| 17 | G1      |                                                                                                                |     |
| 18 | G0      |                                                                                                                |     |
| 19 | B5      |                                                                                                                |     |
| 20 | B4      |                                                                                                                |     |
| 21 | B3      |                                                                                                                |     |
| 22 | B2      |                                                                                                                |     |
| 23 | B1      |                                                                                                                |     |
| 24 | B0      |                                                                                                                |     |
| 25 | SDA     | Serial data input/output                                                                                       | I/O |
| 26 | DOTCLK  | Data enable signal in RGB interface.                                                                           | I   |
| 27 | DE      | A data ENABLE signal in RGB I/F mode                                                                           | I   |
| 28 | HSYNC   | Horizontal synchronizing signal in RGB interface                                                               | I   |
| 29 | VSNC    | Vertical synchronizing signal in RGB interface                                                                 | I   |
| 30 | NRD     | Read enable pin I80 parallel bus system interface                                                              | I   |
| 31 | NWR_DNC | NWR Write enable pin I80 parallel bus system interface                                                         | I   |




|     |         | DNC Command/parameter or display data selection pin in serial bus system interface                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                                      |             |         |                    |                    |               |                  |      |   |   |   |                              |        |        |   |   |   |                               |        |         |   |                              |        |        |   |   |   |                              |        |        |   |                               |        |         |   |   |                                      |             |  |   |                                      |             |  |   |
|-----|---------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|-------------|---------|--------------------|--------------------|---------------|------------------|------|---|---|---|------------------------------|--------|--------|---|---|---|-------------------------------|--------|---------|---|------------------------------|--------|--------|---|---|---|------------------------------|--------|--------|---|-------------------------------|--------|---------|---|---|--------------------------------------|-------------|--|---|--------------------------------------|-------------|--|---|
| 32  | DNC_SCL | DNC Command/parameter or display data selection pin in parallel interface<br>SCL Serial data clock in serial bus system Interface                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | I                                    |             |         |                    |                    |               |                  |      |   |   |   |                              |        |        |   |   |   |                               |        |         |   |                              |        |        |   |   |   |                              |        |        |   |                               |        |         |   |   |                                      |             |  |   |                                      |             |  |   |
| 33  | NCS     | Chip select signal                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | I                                    |             |         |                    |                    |               |                  |      |   |   |   |                              |        |        |   |   |   |                               |        |         |   |                              |        |        |   |   |   |                              |        |        |   |                               |        |         |   |   |                                      |             |  |   |                                      |             |  |   |
| 34  | NRESET  | System Reset                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | I                                    |             |         |                    |                    |               |                  |      |   |   |   |                              |        |        |   |   |   |                               |        |         |   |                              |        |        |   |   |   |                              |        |        |   |                               |        |         |   |   |                                      |             |  |   |                                      |             |  |   |
| 35  | IM0     | System interface select:<br><table><tr><th rowspan="2">IM2</th><th rowspan="2">IM1</th><th rowspan="2">IM0</th><th rowspan="2">MCU-Interface Mode</th><th colspan="2">DB Pin in use</th></tr><tr><th>Register/Content</th><th>GRAM</th></tr><tr><td>0</td><td>0</td><td>0</td><td>80 MCU 8-bit bus interface I</td><td>D[7:0]</td><td>D[7:0]</td></tr><tr><td rowspan="2">0</td><td rowspan="2">0</td><td>1</td><td>80 MCU 16-bit bus interface I</td><td>D[7:0]</td><td>D[15:0]</td></tr><tr><td>0</td><td>80 MCU 9-bit bus interface I</td><td>D[7:0]</td><td>D[8:0]</td></tr><tr><td rowspan="4">0</td><td rowspan="2">1</td><td>0</td><td>80 MCU 9-bit bus interface I</td><td>D[7:0]</td><td>D[8:0]</td></tr><tr><td>1</td><td>80 MCU 18-bit bus interface I</td><td>D[7:0]</td><td>D[17:0]</td></tr><tr><td rowspan="2">1</td><td>0</td><td>3-wire 9-bit data serial interface I</td><td colspan="2">SDA: In/OUT</td></tr><tr><td>1</td><td>4-wire 8-bit data serial interface I</td><td colspan="2">SDA: In/OUT</td></tr></table> | IM2                                  | IM1         | IM0     | MCU-Interface Mode | DB Pin in use      |               | Register/Content | GRAM | 0 | 0 | 0 | 80 MCU 8-bit bus interface I | D[7:0] | D[7:0] | 0 | 0 | 1 | 80 MCU 16-bit bus interface I | D[7:0] | D[15:0] | 0 | 80 MCU 9-bit bus interface I | D[7:0] | D[8:0] | 0 | 1 | 0 | 80 MCU 9-bit bus interface I | D[7:0] | D[8:0] | 1 | 80 MCU 18-bit bus interface I | D[7:0] | D[17:0] | 1 | 0 | 3-wire 9-bit data serial interface I | SDA: In/OUT |  | 1 | 4-wire 8-bit data serial interface I | SDA: In/OUT |  | I |
| IM2 | IM1     | IM0                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |                                      |             |         |                    | MCU-Interface Mode | DB Pin in use |                  |      |   |   |   |                              |        |        |   |   |   |                               |        |         |   |                              |        |        |   |   |   |                              |        |        |   |                               |        |         |   |   |                                      |             |  |   |                                      |             |  |   |
|     |         |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | Register/Content                     | GRAM        |         |                    |                    |               |                  |      |   |   |   |                              |        |        |   |   |   |                               |        |         |   |                              |        |        |   |   |   |                              |        |        |   |                               |        |         |   |   |                                      |             |  |   |                                      |             |  |   |
| 0   | 0       | 0                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | 80 MCU 8-bit bus interface I         | D[7:0]      | D[7:0]  |                    |                    |               |                  |      |   |   |   |                              |        |        |   |   |   |                               |        |         |   |                              |        |        |   |   |   |                              |        |        |   |                               |        |         |   |   |                                      |             |  |   |                                      |             |  |   |
| 0   | 0       | 1                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | 80 MCU 16-bit bus interface I        | D[7:0]      | D[15:0] |                    |                    |               |                  |      |   |   |   |                              |        |        |   |   |   |                               |        |         |   |                              |        |        |   |   |   |                              |        |        |   |                               |        |         |   |   |                                      |             |  |   |                                      |             |  |   |
|     |         | 0                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | 80 MCU 9-bit bus interface I         | D[7:0]      | D[8:0]  |                    |                    |               |                  |      |   |   |   |                              |        |        |   |   |   |                               |        |         |   |                              |        |        |   |   |   |                              |        |        |   |                               |        |         |   |   |                                      |             |  |   |                                      |             |  |   |
| 0   | 1       | 0                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | 80 MCU 9-bit bus interface I         | D[7:0]      | D[8:0]  |                    |                    |               |                  |      |   |   |   |                              |        |        |   |   |   |                               |        |         |   |                              |        |        |   |   |   |                              |        |        |   |                               |        |         |   |   |                                      |             |  |   |                                      |             |  |   |
|     |         | 1                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | 80 MCU 18-bit bus interface I        | D[7:0]      | D[17:0] |                    |                    |               |                  |      |   |   |   |                              |        |        |   |   |   |                               |        |         |   |                              |        |        |   |   |   |                              |        |        |   |                               |        |         |   |   |                                      |             |  |   |                                      |             |  |   |
|     | 1       | 0                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | 3-wire 9-bit data serial interface I | SDA: In/OUT |         |                    |                    |               |                  |      |   |   |   |                              |        |        |   |   |   |                               |        |         |   |                              |        |        |   |   |   |                              |        |        |   |                               |        |         |   |   |                                      |             |  |   |                                      |             |  |   |
|     |         | 1                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | 4-wire 8-bit data serial interface I | SDA: In/OUT |         |                    |                    |               |                  |      |   |   |   |                              |        |        |   |   |   |                               |        |         |   |                              |        |        |   |   |   |                              |        |        |   |                               |        |         |   |   |                                      |             |  |   |                                      |             |  |   |
| 36  | IM1     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                                      |             |         |                    |                    |               |                  |      |   |   |   |                              |        |        |   |   |   |                               |        |         |   |                              |        |        |   |   |   |                              |        |        |   |                               |        |         |   |   |                                      |             |  |   |                                      |             |  |   |
| 37  | IM2     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                                      |             |         |                    |                    |               |                  |      |   |   |   |                              |        |        |   |   |   |                               |        |         |   |                              |        |        |   |   |   |                              |        |        |   |                               |        |         |   |   |                                      |             |  |   |                                      |             |  |   |
| 38  | GND     | Ground                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | P                                    |             |         |                    |                    |               |                  |      |   |   |   |                              |        |        |   |   |   |                               |        |         |   |                              |        |        |   |   |   |                              |        |        |   |                               |        |         |   |   |                                      |             |  |   |                                      |             |  |   |
| 39  | VLED+   | Anode of LED backlight.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | P                                    |             |         |                    |                    |               |                  |      |   |   |   |                              |        |        |   |   |   |                               |        |         |   |                              |        |        |   |   |   |                              |        |        |   |                               |        |         |   |   |                                      |             |  |   |                                      |             |  |   |
| 40  | VLED-   | Cathode of LED backlight.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | P                                    |             |         |                    |                    |               |                  |      |   |   |   |                              |        |        |   |   |   |                               |        |         |   |                              |        |        |   |   |   |                              |        |        |   |                               |        |         |   |   |                                      |             |  |   |                                      |             |  |   |

DESIGN • MANUFACTURE • SUPPLY




# Contour Drawing



DESIGN • MANUFACTURE • SUPPLY

## Block Diagram



## Absolute Maximum Ratings

| Item                  | Symbol | Min | Typ | Max | Unit |
|-----------------------|--------|-----|-----|-----|------|
| Operating Temperature | TOP    | -20 | —   | +70 | °C   |
| Storage Temperature   | TST    | -30 | —   | +80 | °C   |

Note: Device is subject to be damaged permanently if stresses beyond those absolute maximum ratings listed above

- Temp.  $\leq 60^{\circ}\text{C}$ , 90% RH MAX. Temp.  $> 60^{\circ}\text{C}$ , Absolute humidity shall be less than 90% RH at  $60^{\circ}\text{C}$

## Electrical Characteristics

### 1. Operating conditions:

| Item                 | Symbol | Condition  | Min       | Type | Max       | Unit |
|----------------------|--------|------------|-----------|------|-----------|------|
| Power supply voltage | VCI    |            | 2.5       | 2.8  | 3.3       | V    |
| Power supply voltage | IOVCC  |            | 1.65      | 2.8  | 3.3       | V    |
| Input high voltage   | Vih    |            | 0.7IOVCC  | -    | IOVCC     | V    |
| Input low voltage    | Vil    |            | GND       | -    | 0.3IOVCC  | V    |
| Output high voltage  | Voh    | IOL=-1.0mA | 0.8 IOVCC | -    | IOVCC     | V    |
| Output low voltage   | Vol    | IOL =1.0mA | GND       | -    | 0.2 IOVCC | V    |
| Current consumption  | Ivci   | -          | -         | 5.5  | 8.25      | mA   |


This value is test for VDD=3.3V , Ta=25 °C only

### 2. LED driving conditions

| Parameter     | Symbol | Min | Typ   | Max | Unit | Remark   |
|---------------|--------|-----|-------|-----|------|----------|
| LED current   | —      | —   | 120   | —   | mA   | —        |
| LED voltage   | VLED+  | 5.5 | 6.0   | 6.5 | V    | Note 1   |
| LED Life Time | —      | —   | 50000 | —   | Hr   | Note 2,3 |

Note 1 : There are 1 Groups LED

Note 2 : Ta = 25°C



CIRCUIT DIAGRAM

Note 3 : Brightness to be decreased to 50% of the initial value

## Optical Characteristics

| Item                                              | Symbol | Condition.                        | Min  | Typ. | Max. | Unit              | Remark            |
|---------------------------------------------------|--------|-----------------------------------|------|------|------|-------------------|-------------------|
| Response time                                     | Tr     | $\theta=0^\circ$ 、 $\phi=0^\circ$ | -    | 4    | 8    | .ms               | Note 3            |
|                                                   | Tf     |                                   | -    | 12   | 24   | .ms               |                   |
| Contrast ratio                                    | CR     | At optimized viewing angle        | 400  | 500  | -    | -                 | Note 4            |
| Color Chromaticity                                | White  | $\theta=0^\circ$ 、 $\phi=0$       | 0.26 | 0.31 | 0.36 |                   | Note 2,6,7        |
|                                                   | Wy     |                                   | 0.28 | 0.33 | 0.38 |                   |                   |
| Viewing angle<br>(Gray Scale Inversion Direction) | Hor.   | $\theta_R$                        | 35   | 45   | -    | Deg.              | Note 1            |
|                                                   |        | $\theta_L$                        | 35   | 45   | -    |                   |                   |
|                                                   | Ver.   | $\phi_T$                          | 35   | 45   | -    |                   |                   |
|                                                   |        | $\phi_B$                          | 10   | 20   | -    |                   |                   |
| Brightness                                        | -      | -                                 | 900  | 1000 | -    | cd/m <sup>2</sup> | Center of display |
| Uniformity                                        | (U)    | -                                 | 75   | -    | -    | %                 | Note 5            |

Ta=25±2℃

Note 1: Definition of viewing angle range




Fig 9.1. Definition of viewing angle

Note 2: Test equipment setup:

After stabilizing and leaving the panel alone at a driven temperature for 10 minutes, the measurement should be executed. Measurement should be executed in a stable, windless, and dark room. Optical specifications are measured by Topcon BM-7 or BM-5 luminance meter 1.0° field of view at a distance of 50cm and normal direction.





Fig 9.2. Optical measurement system setup

Note 3: Definition of Response time:

The response time is defined as the LCD optical switching time interval between "White" state and "Black" state. Rise time,  $T_r$ , is the time between photo detector output intensity changed from 90% to 10%. And fall time,  $T_f$ , is the time between photo detector output intensity changed from 10% to 90%



Note 4: Definition of contrast ratio:

The contrast ratio is defined as the following expression.

$$\text{Contrast ratio (CR)} = \frac{\text{Luminance measured when LCD on the "White" state}}{\text{Luminance measured when LCD on the "Black" state}}$$

Note 5: Definition of Luminance Uniformity

Active area is divided into 9 measuring areas (reference the picture in below). Every measuring point is placed at the center of each measuring area.

$$\text{Luminance Uniformity (U)} = L_{\min}/L_{\max} \times 100\%$$

L = Active area length

W = Active area width




Fig 9.3. Definition of uniformity

Note 6: Definition of color chromaticity (CIE 1931)


Color coordinates measured at the center point of LCD

Note 7: Measured at the center area of the panel when all the input terminals of LCD panel are electrically opened.



# Reliability

Content of Reliability Test (Wide temperature, -20℃~70℃)

| Environmental Test                   |                                                                                                                                                                   |                                                                                                                                                     |      |
|--------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------|------|
| Test Item                            | Content of Test                                                                                                                                                   | Test Condition                                                                                                                                      | Note |
| High Temperature storage             | Endurance test applying the high storage temperature for a long time.                                                                                             | 80℃<br>96hrs                                                                                                                                        | 2    |
| Low Temperature storage              | Endurance test applying the low storage temperature for a long time.                                                                                              | -30℃<br>96hrs                                                                                                                                       | 1,2  |
| High Temperature Operation           | Endurance test applying the electric stress (Voltage & Current) and the thermal stress to the element for a long time.                                            | 70℃<br>96hrs                                                                                                                                        | —    |
| Low Temperature Operation            | Endurance test applying the electric stress under low temperature for a long time.                                                                                | -20℃<br>96hrs                                                                                                                                       | 1    |
| High Temperature/ Humidity Operation | The module should be allowed to stand at 40℃, 90%RH max                                                                                                           | 40℃, 90%RH<br>96hrs                                                                                                                                 | 1,2  |
| Thermal shock resistance             | <p>The sample should be allowed stand the following 10 cycles of operation</p>  | -20℃/70℃<br>10 cycles                                                                                                                               | —    |
| Vibration test                       | Endurance test applying the vibration during transportation and using.                                                                                            | <p>Total fixed amplitude : 1.5mm<br/>Vibration Frequency :</p> <p>10~55Hz<br/>One cycle 60 seconds to 3 directions of X,Y,Z for Each 15 minutes</p> | 3    |
| Static electricity test              | Endurance test applying the electric stress to the terminal.                                                                                                      | <p>VS=±600V(contact)<br/>,±800v(air),<br/>RS=330Ω<br/>CS=150pF<br/>10 times</p>                                                                     | —    |

Note1: No dew condensation to be observed.

Note2: The function test shall be conducted after 4 hours storage at the normal Temperature and humidity after remove from the test chamber.

Note3: The packing have to including into the vibration testing.