


Pluggable Terminal Block multicomp^{PRO}

RoHS
Compliant



Description

Euro Blocks are ideal for wire termination applications. These euro blocks are offered with a 2.5mm pitch, vertical orientation, and 20-26 AWG. Various positions are available, ranging from 2-12 circuits.

Features

- .098" [2.50mm] pitch
- Position options: 2, 3, 4, 5, 6, 8, 10, or 12 circuits
- Vertical orientation
- 20-26 AWG
- Green insulator
- Operating voltage: 150V
- Current rating: 5A
- Wire guard design

Applications

- Industrial
- Testing and measurement
- Audio applications
- Communication applications
- HVAC equipment
- Traffic control

Specifications

Material:

Insulator	: PA66, rated UL 94V-0
Insulator color	: Green
Clamp	: Phosphor Bronze, Nickel plated
Wire guard	: Stainless Steel

Electrical:

Operation voltage	: 150V
Current rating	: 5A
Contact resistance	: 20mΩ max
Insulation resistance	: 500MΩ min @ 500V DC

Mechanical:


Wire range	: 26-20 AWG, 0.5mm ²
Wire strip length	: 8mm

Newark.com/multicomp-pro
Farnell.com/multicomp-pro
sg.element14.com/b/multicomp-pro

multicomp^{PRO}

Pluggable Terminal Block multicomp^{PRO}

Diagram



Dimensions : Millimetres

Part Number Table

Description	Part Number
Pluggable Terminal Block, 150V, 5A, 2.5mm, 2 Pos	MP010255
Pluggable Terminal Block, 150V, 5A, 2.5mm, 3 Pos	MP010256
Pluggable Terminal Block, 150V, 5A, 2.5mm, 4 Pos	MP010257
Pluggable Terminal Block, 150V, 5A, 2.5mm, 5 Pos	MP010258
Pluggable Terminal Block, 150V, 5A, 2.5mm, 6 Pos	MP010259
Pluggable Terminal Block, 150V, 5A, 2.5mm, 8 Pos	MP010260
Pluggable Terminal Block, 150V, 5A, 2.5mm, 10 Pos	MP010261
Pluggable Terminal Block, 150V, 5A, 2.5mm, 12 Pos	MP010262

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro
Farnell.com/multicomp-pro
sg.element14.com/b/multicomp-pro

multicomp^{PRO}