




Click [here](#) for the 3D model.

| Dimensions |             |
|------------|-------------|
| D          | 35mm MAX    |
| H          | 20mm MAX    |
| LL         | 20mm +/-2mm |
| S          | 15mm NOM    |
| L2         | 1.5mm MAX   |
| Wire Size  | 1.2mm       |

| Packaging Specifications |        |
|--------------------------|--------|
| Packaging                | Bulk   |
| Component Weight         | 48.4 g |

| General Information |                                 |
|---------------------|---------------------------------|
| Series              | SN                              |
| Style               | Through-Hole                    |
| Features            | Compact Size                    |
| RoHS                | Yes                             |
| Miscellaneous       | Temperature Rise Maximum: 40 K. |
| Core                | Fe                              |
| Specifications      |                                 |
| Inductance          | 120 uH (0.1 MHz)                |
| Current             | 5 A                             |
| Temperature Range   | -25/+105°C                      |
| DC Resistance       | 0.045 mOhms                     |

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.