



# Industrial microSD 2.0 Specification

(FxPrem I, SLC)

**Version 1.0**

Address: 28 Genting Lane, #09-03/04/05 Platinum 28, Singapore 349585

Tel : +65-6493 5035

Fax : +65-6493 5037

Website: <http://www.flexxon.com>

Email: [flexxon@flexxon.com](mailto:flexxon@flexxon.com)

ALL RIGHTS ARE STRICTLY RESERVED. ANY PORTION OF THIS PAPER SHALL NOT BE REPRODUCED, COPIED, OR TRANSLATED TO ANY OTHER FORMS WITHOUT PERMISSION FROM FLEXXON.

## Table of Contents

|           |                                                                       |           |
|-----------|-----------------------------------------------------------------------|-----------|
| <b>1.</b> | <b>General Description.....</b>                                       | <b>1</b>  |
| 1.1.      | Introduction.....                                                     | 1         |
| 1.2.      | Product Overview .....                                                | 1         |
| <b>2.</b> | <b>Product Specifications.....</b>                                    | <b>2</b>  |
| 2.1.      | Performance .....                                                     | 2         |
| 2.2.      | Power .....                                                           | 2         |
| 2.3.      | MTBF .....                                                            | 2         |
| 2.4.      | Data Retention.....                                                   | 2         |
| <b>3.</b> | <b>Environmental Specifications .....</b>                             | <b>3</b>  |
| <b>4.</b> | <b>Electrical Specifications .....</b>                                | <b>4</b>  |
| 4.1.      | DC Characteristics .....                                              | 4         |
| 4.1.1.    | Bus Operation Conditions for 3.3V Signaling.....                      | 4         |
| 4.1.2.    | Bus Signal Line Load.....                                             | 5         |
| 4.1.3.    | Power Up Time of Host .....                                           | 6         |
| 4.1.4.    | Power Up Time of Card .....                                           | 7         |
| 4.2.      | AC Characteristic.....                                                | 7         |
| 4.2.1.    | microSD Interface timing (Default).....                               | 7         |
| 4.2.2.    | microSD Interface Timing (High-Speed Mode) .....                      | 9         |
| 4.2.3.    | microSD Interface timing (SDR12, SDR25, SDR50 and SDR104 Modes) ..... | 10        |
| 4.2.4.    | microSD Interface timing (DDR50 Modes).....                           | 12        |
| <b>5.</b> | <b>Pad Assignment.....</b>                                            | <b>14</b> |
| <b>6.</b> | <b>Registers .....</b>                                                | <b>15</b> |
| <b>7.</b> | <b>Physical Dimension .....</b>                                       | <b>16</b> |
| <b>8.</b> | <b>Ordering Information.....</b>                                      | <b>18</b> |

## 1. GENERAL DESCRIPTION



### 1.1. Introduction

FLEXXON industrial FxPrem I Series microSD 2.0 card has good reliability and wide compatibility. It can alternate communication protocol between SD mode and SPI mode. It's well adapted for hand-held applications in industrial/medical markets already.

### 1.2. Product Overview

- ❖ **Flash**
  - SLC
- ❖ **Capacity**
  - 128MB up to 512MB
- ❖ **Support SD system specification version 2.0**
- ❖ **Support SD SPI mode**
- ❖ **Support CPRM (Content Protection for Recordable Media) of SD Card**
- ❖ **Card removal during read operation will never harm the content**
- ❖ **Password Protection of cards (optional)**
- ❖ **Support Adaptive Wear Leveling**
- ❖ **Sudden Power Loss management**
- ❖ **Temperature Range**
  - Operation: -40°C ~ 85°C
  - Storage: -40°C ~ 85°C
- ❖ **RoHS Compliant**
- ❖ **SMART Function**
- ❖ **Bus Speed Mode**
  - **Non-UHS mode**
    - Default speed mode: 3.3V signaling, frequency up to 25MHz, up to 12.5MB/sec
    - High speed mode: 3.3V signaling, frequency up to 50MHz, up to 25MB/sec

## 2. PRODUCT SPECIFICATIONS



### 2.1. Performance

Table 2-1 Performance of microSD (FxPrem I)

| Capacity | Sequential  |              |
|----------|-------------|--------------|
|          | Read (MB/s) | Write (MB/s) |
| 128MB    | 20          | 13           |
| 256MB    | 20          | 13           |
| 512MB    | 20          | 13           |

**NOTES:**

1. The performance is obtained from TestMetrix Test (@500MB).
2. Samples are made of SLC NAND Flash.
3. Performance may vary from flash configuration and platform.

### 2.2. Power

Table 2-2 Power Consumption of microSD (FxPrem I)

| Capacity | Read (mA) | Write (mA) | Standby (uA) |
|----------|-----------|------------|--------------|
| 128MB    | 40        | 36         | 150          |
| 256MB    | 40        | 36         | 150          |
| 512MB    | 40        | 36         | 150          |

### 2.3. MTBF

MTBF, an acronym for Mean Time Between Failures, is a measure of a device's reliability. Its value represents the average time between a repair and the next failure. The higher the MTBF value, the higher the reliability of the device. The predicted result of FLEXXON's FxPrem I microSD is more than 3,000,000 hours.

### 2.4. Data Retention

- 10 years if > 90% life remaining (@25C)
- 1 year if < 10% life remaining (@25C)

### 3. ENVIRONMENTAL SPECIFICATIONS



| Test Items            | Test Conditions                                                                                                           |
|-----------------------|---------------------------------------------------------------------------------------------------------------------------|
| Storage Temperature   | -40°C ~ 85°C                                                                                                              |
| Operating Temperature | -40°C ~ 85°C                                                                                                              |
| Storage Humidity      | 55°C, 95% RH                                                                                                              |
| Operating Humidity    | 55°C, 95% RH                                                                                                              |
| Shock                 | 1500G, Half Sin Pulse Duration 0.5ms                                                                                      |
| Vibration             | 80Hz ~ 2000Hz/20G, 20Hz ~ 80Hz/1.52mm, 3 axis/30min                                                                       |
| Drop                  | 150cm free fall, 6 face of each unit                                                                                      |
| Bending               | ≥ 10N, Hold 1 min/5 times                                                                                                 |
| Torque                | 0.1N-m or +/-2.5 deg, Hold 30 seconds/5 times                                                                             |
| Salt Spray            | Concentration: 3% NaCl, Temperature: 35°C, 24hours                                                                        |
| Waterproof            | Water temperature: 25°C<br>Water depth: The lowest point of unit is locating 1000mm below surface.<br>Storage for 30 mins |
| Switch Cycle          | 0.4~0.5 N, 1,000 times                                                                                                    |
| Durability            | 10,000 times                                                                                                              |
| ESD                   | Contact: +/- 4KV each item 25 times<br>Air: +/- 8KV 10 times                                                              |

## 4. ELECTRICAL SPECIFICATIONS



### 4.1. DC Characteristics

#### 4.1.1. Bus Operation Conditions for 3.3V Signaling

Table 4-1 Threshold Level for High Voltage Range

| Parameter           | Symbol   | Min.                 | Max                  | Unit | Condition                           |
|---------------------|----------|----------------------|----------------------|------|-------------------------------------|
| Supply Voltage      | $V_{DD}$ | 2.7                  | 3.6                  | V    |                                     |
| Output High Voltage | $V_{OH}$ | $0.75 \cdot V_{DD}$  |                      | V    | $I_{OH} = -2\text{mA}$ $V_{DD}$ Min |
| Output Low Voltage  | $V_{OL}$ |                      | $0.125 \cdot V_{DD}$ | V    | $I_{OL} = 2\text{mA}$ $V_{DD}$ Min  |
| Input High Voltage  | $V_{IH}$ | $0.625 \cdot V_{DD}$ | $V_{DD} + 0.3$       | V    |                                     |
| Input Low Voltage   | $V_{IL}$ | $V_{SS} - 0.3$       | $0.25 \cdot V_{DD}$  | V    |                                     |
| Power Up Time       |          |                      | 250                  | ms   | From 0V to $V_{DD}$ min             |

| Parameter           | Symbol     | Min.           | Max  | Unit | Condition              |
|---------------------|------------|----------------|------|------|------------------------|
| Supply Voltage      | $V_{DD}$   | 2.7            | 3.6  | V    |                        |
| Regulator Voltage   | $V_{DDIO}$ | 1.7            | 1.95 | V    | Generated by $V_{DD}$  |
| Output High Voltage | $V_{OH}$   | 1.4            | -    | V    | $I_{OH} = -2\text{mA}$ |
| Output Low Voltage  | $V_{OL}$   | -              | 0.45 | V    | $I_{OL} = 2\text{mA}$  |
| Input High Voltage  | $V_{IH}$   | 1.27           | 2.00 | V    |                        |
| Input Low Voltage   | $V_{IL}$   | $V_{SS} - 0.3$ | 0.58 | V    |                        |

| Parameter             | Symbol | Min | Max. | Unit          | Remarks                       |
|-----------------------|--------|-----|------|---------------|-------------------------------|
| Input Leakage Current |        | -2  | 2    | $\mu\text{A}$ | DAT3 pull-up is disconnected. |

Table 4-2 Peak Voltage and Leakage Current

| Parameter                 | Symbol | Min  | Max.           | Unit          | Remarks |
|---------------------------|--------|------|----------------|---------------|---------|
| Peak voltage on all lines |        | -0.3 | $V_{DD} + 0.3$ | V             |         |
| All Inputs                |        |      |                |               |         |
| Input Leakage Current     |        | -10  | 10             | $\mu\text{A}$ |         |
| All Outputs               |        |      |                |               |         |
| Output Leakage Current    |        | -10  | 10             | $\mu\text{A}$ |         |

## 4.1.2. Bus Signal Line Load


### Bus Operation Conditions – Signal Line's Load

Total Bus Capacitance =  $C_{HOST} + C_{BUS} + N C_{CARD}$

| Parameter                                  | symbol                 | Min | Max    | Unit       | Remark                                              |
|--------------------------------------------|------------------------|-----|--------|------------|-----------------------------------------------------|
| Pull-up resistance                         | $R_{CMD}$<br>$R_{DAT}$ | 10  | 100    | k $\Omega$ | to prevent bus floating                             |
| Total bus capacitance for each signal line | $C_L$                  |     | 40     | pF         | 1 card<br>$C_{HOST}+C_{BUS}$ shall not exceed 30 pF |
| Card Capacitance for each signal pin       | $C_{CARD}$             |     | $10^1$ | pF         |                                                     |
| Maximum signal line inductance             |                        |     | 16     | nH         |                                                     |
| Pull-up resistance inside card (pin1)      | $R_{DAT3}$             | 10  | 90     | k $\Omega$ | May be used for card detection                      |
| Capacity Connected to Power Line           | $C_C$                  |     | 5      | $\mu$ F    | To prevent inrush current                           |

### 4.1.3. Power Up Time of Host

Host needs to keep power line level less than 0.5V and more than 1ms before power ramp up.



#### Power On or Power Cycle

Followings are requirements for Power on and Power cycle to assure a reliable SD Card hard reset.

- (1) Voltage level shall be below 0.5V
- (2) Duration shall be at least 1ms.

#### Power Supply Ramp Up

The power ramp up time is defined from 0.5V threshold level up to the operating supply voltage which is stable between VDD (min.) and VDD (max.) and host can supply SDCLK.

Followings are recommendation of Power ramp up:

- (1) Voltage of power ramp up should be monotonic as much as possible.
- (2) The minimum ramp up time should be 0.1ms.
- (3) The maximum ramp up time should be 35ms for 2.7-3.6V power supply.
- (4) Host shall wait until VDD is stable.
- (5) After 1ms VDD stable time, host provides at least 74 clocks before issuing the first command.


#### Power Down and Power Cycle

- When the host shuts down the power, the card VDD shall be lowered to less than 0.5Volt for a minimum period of 1ms. During power down, DAT, CMD, and CLK should be disconnected or driven to logical 0 by the host to avoid a situation that the operating current is drawn through the signal lines.
- If the host needs to change the operating voltage, a power cycle is required. Power cycle means the power is turned off and supplied again. Power cycle is also needed for accessing cards that are already in *Inactive State*. To create a power cycle the host shall follow the power down description before power up the card (i.e. the card VDD shall be once lowered to less than 0.5Volt for a minimum period of 1ms).

#### 4.1.4. Power Up Time of Card


A device shall be ready to accept the first command within 1ms from detecting VDD min.

Device may use up to 74 clocks for preparation before receiving the first command.



## 4.2. AC Characteristic


### 4.2.1. microSD Interface timing (Default)



| Parameter                                                                                 | Symbol            | Min                   | Max | Unit | Remark                             |
|-------------------------------------------------------------------------------------------|-------------------|-----------------------|-----|------|------------------------------------|
| <b>Clock CLK (All values are referred to min(V<sub>IH</sub>) and max(V<sub>IL</sub>))</b> |                   |                       |     |      |                                    |
| Clock frequency Data Transfer Mode                                                        | f <sub>PP</sub>   | 0                     | 25  | MHz  | C <sub>card</sub> ≤ 10 pF (1 card) |
| Clock frequency Identification Mode                                                       | f <sub>OD</sub>   | 0 <sub>(1)</sub> /100 | 400 | KHz  | C <sub>card</sub> ≤ 10 pF (1 card) |
| Clock low time                                                                            | t <sub>WL</sub>   | 10                    |     | ns   | C <sub>card</sub> ≤ 10 pF (1 card) |
| Clock high time                                                                           | t <sub>WH</sub>   | 10                    |     | ns   | C <sub>card</sub> ≤ 10 pF (1 card) |
| Clock rise time                                                                           | t <sub>TLH</sub>  |                       | 10  | ns   | C <sub>card</sub> ≤ 10 pF (1 card) |
| Clock fall time                                                                           | t <sub>THL</sub>  |                       | 10  | ns   | C <sub>card</sub> ≤ 10 pF (1 card) |
| <b>Inputs CMD, DAT (referenced to CLK)</b>                                                |                   |                       |     |      |                                    |
| Input set-up time                                                                         | t <sub>ISU</sub>  | 5                     |     | ns   | C <sub>card</sub> ≤ 10 pF (1 card) |
| Input hold time                                                                           | t <sub>IH</sub>   | 5                     |     | ns   | C <sub>card</sub> ≤ 10 pF (1 card) |
| <b>Outputs CMD, DAT (referenced to CLK)</b>                                               |                   |                       |     |      |                                    |
| Output Delay time during Data Transfer Mode                                               | t <sub>ODLY</sub> | 0                     | 14  | ns   | C <sub>L</sub> ≤ 40 pF (1 card)    |
| Output Delay time during Identification Mode                                              | t <sub>ODLY</sub> | 0                     | 50  | ns   | C <sub>L</sub> ≤ 40 pF (1 card)    |

(1) 0Hz means to stop the clock. The given minimum frequency range is for cases where continues clock is required.

## 4.2.2. microSD Interface Timing (High-Speed Mode)




| Parameter                                                                                 | Symbol            | Min | Max | Unit | Remark                                |
|-------------------------------------------------------------------------------------------|-------------------|-----|-----|------|---------------------------------------|
| <b>Clock CLK (All values are referred to min(V<sub>IH</sub>) and max(V<sub>IL</sub>))</b> |                   |     |     |      |                                       |
| Clock frequency Data Transfer Mode                                                        | f <sub>PP</sub>   | 0   | 50  | MHz  | C <sub>card</sub> ≤ 10 pF<br>(1 card) |
| Clock low time                                                                            | t <sub>WL</sub>   | 7   |     | ns   | C <sub>card</sub> ≤ 10 pF<br>(1 card) |
| Clock high time                                                                           | t <sub>WH</sub>   | 7   |     | ns   | C <sub>card</sub> ≤ 10 pF<br>(1 card) |
| Clock rise time                                                                           | t <sub>TLH</sub>  |     | 3   | ns   | C <sub>card</sub> ≤ 10 pF<br>(1 card) |
| Clock fall time                                                                           | t <sub>THL</sub>  |     | 3   | ns   | C <sub>card</sub> ≤ 10 pF<br>(1 card) |
| <b>Inputs CMD, DAT (referenced to CLK)</b>                                                |                   |     |     |      |                                       |
| Input set-up time                                                                         | t <sub>ISU</sub>  | 6   |     | ns   | C <sub>card</sub> ≤ 10 pF<br>(1 card) |
| Input hold time                                                                           | t <sub>IH</sub>   | 2   |     | ns   | C <sub>card</sub> ≤ 10 pF<br>(1 card) |
| <b>Outputs CMD, DAT (referenced to CLK)</b>                                               |                   |     |     |      |                                       |
| Output Delay time during Data Transfer Mode                                               | t <sub>ODLY</sub> |     | 14  | ns   | C <sub>L</sub> ≤ 40 pF<br>(1 card)    |
| Output Hold time                                                                          | T <sub>OH</sub>   | 2.5 |     | ns   | C <sub>L</sub> ≤ 15 pF<br>(1 card)    |
| Total System capacitance of each line <sup>1</sup>                                        | C <sub>L</sub>    |     | 40  | pF   | C <sub>L</sub> ≤ 15 pF<br>(1 card)    |

(1) In order to satisfy severe timing, the host shall drive only one card.

### 4.2.3. microSD Interface timing (SDR12, SDR25, SDR50 and SDR104 Modes)

#### Input:




**Clock Signal Timing**

| Symbol           | Min  | Max             | Unit | Remark                                                                                                                                                                                                             |
|------------------|------|-----------------|------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| $t_{CLK}$        | 4.80 | -               | ns   | 208MHz (Max.), Between rising edge, $V_{CT}= 0.975V$                                                                                                                                                               |
| $t_{CR}, t_{CF}$ | -    | $0.2 * t_{CLK}$ | ns   | $t_{CR}, t_{CF} < 0.96ns$ (max.) at 208MHz, $C_{CARD}=10pF$<br>$t_{CR}, t_{CF} < 2.00ns$ (max.) at 100MHz, $C_{CARD}=10pF$<br>The absolute maximum value of $t_{CR}, t_{CF}$ is 10ns regardless of clock frequency |
| Clock Duty       | 30   | 70              | %    |                                                                                                                                                                                                                    |

**Clock Signal Timing**


#### **SDR50 and SDR104 Input Timing:**



**Card Input Timing**

| Symbol   | Min  | Max | Unit | SDR104 Mode                       |
|----------|------|-----|------|-----------------------------------|
| $t_{IS}$ | 1.40 | -   | ns   | $C_{CARD} = 10pF, V_{CT}= 0.975V$ |
| $t_{IH}$ | 0.80 | -   | ns   | $C_{CARD} = 5pF, V_{CT}= 0.975V$  |
| Symbol   | Min  | Max | Unit | SDR50 Mode                        |
| $t_{IS}$ | 3.00 | -   | ns   | $C_{CARD} = 10pF, V_{CT}= 0.975V$ |
| $t_{IH}$ | 0.80 | -   | ns   | $C_{CARD} = 5pF, V_{CT}= 0.975V$  |

### Output:




Output Timing of Fixed Data Window

| Symbol     | Min | Max | Unit | Remark                                                                           |
|------------|-----|-----|------|----------------------------------------------------------------------------------|
| $t_{ODLY}$ | -   | 7.5 | ns   | $t_{CLK} \geq 10.0ns$ , $C_L = 30pF$ , using driver Type B, for SDR50            |
| $t_{ODLY}$ | -   | 14  | ns   | $t_{CLK} \geq 20.0ns$ , $C_L = 40pF$ , using driver Type B, for SDR25 and SDR12, |
| $T_{OH}$   | 1.5 | -   | ns   | Hold time at the $t_{ODLY}$ (min.), $C_L = 15pF$                                 |


Output Timing of Fixed Data Window

### Output (SDR104 Mode):




| Symbol          | Min  | Max   | Unit | Remark                                                |
|-----------------|------|-------|------|-------------------------------------------------------|
| $t_{OP}$        | 0    | 2     | UI   | Card Output Phase                                     |
| $\Delta t_{OP}$ | -350 | +1550 | ps   | Delay variable due to temperature change after tuning |
| $t_{ODW}$       | 0.60 | -     | UI   | $t_{ODW} = 2.88ns$ at 208MHz                          |

#### 4.2.4. microSD Interface timing (DDR50 Modes)



**Clock Signal Timing**

| Symbol           | Min | Max             | Unit | Remark                                                     |
|------------------|-----|-----------------|------|------------------------------------------------------------|
| $t_{CLK}$        | 4.8 | -               | ns   | 50MHz (Max.), Between rising edge                          |
| $t_{CR}, t_{CF}$ | -   | $0.2 * t_{CLK}$ | ns   | $t_{CR}, t_{CF} < 4.00ns$ (max.) at 50MHz, $C_{CARD}=10pF$ |
| Clock Duty       | 45  | 55              | %    |                                                            |



**Timing Diagram DAT Inputs/Outputs Referenced to CLK in DDR50 Mode**

### Bus Timings – Parameters Values (DDR50 Mode)

| Parameter                                                       | Symbol       | Min | Max  | Unit | Remark                                    |
|-----------------------------------------------------------------|--------------|-----|------|------|-------------------------------------------|
| <b>Input CMD</b> (referenced to CLK rising edge)                |              |     |      |      |                                           |
| Input set-up time                                               | $t_{ISU}$    | 6   | -    | ns   | $C_{card} \leq 10 \text{ pF}$<br>(1 card) |
| Input hold time                                                 | $t_{IH}$     | 0.8 | -    | ns   | $C_{card} \leq 10 \text{ pF}$<br>(1 card) |
| <b>Output CMD</b> (referenced to CLK rising edge)               |              |     |      |      |                                           |
| Output Delay time during Data Transfer Mode                     | $t_{ODLY}$   |     | 13.7 | ns   | $C_L \leq 30 \text{ pF}$<br>(1 card)      |
| Output Hold time                                                | $T_{OH}$     | 1.5 | -    | ns   | $C_L \geq 15 \text{ pF}$<br>(1 card)      |
| <b>Inputs DAT</b> (referenced to CLK rising and falling edges)  |              |     |      |      |                                           |
| Input set-up time                                               | $t_{ISU2x}$  | 3   | -    | ns   | $C_{card} \leq 10 \text{ pF}$<br>(1 card) |
| Input hold time                                                 | $t_{IH2x}$   | 0.8 | -    | ns   | $C_{card} \leq 10 \text{ pF}$<br>(1 card) |
| <b>Outputs DAT</b> (referenced to CLK rising and falling edges) |              |     |      |      |                                           |
| Output Delay time during Data Transfer Mode                     | $t_{ODLY2x}$ | -   | 7.0  | ns   | $C_L \leq 25 \text{ pF}$<br>(1 card)      |
| Output Hold time                                                | $T_{OH2x}$   | 1.5 | -    | ns   | $C_L \geq 15 \text{ pF}$<br>(1 card)      |

## 5. PAD ASSIGNMENT




Table 5-1 microSD Memory Card Pad Assignment

| pin | SD Mode              |                     |                                 | SPI Mode        |                |                           |
|-----|----------------------|---------------------|---------------------------------|-----------------|----------------|---------------------------|
|     | Name                 | Type <sup>1</sup>   | Description                     | Name            | Type           | Description               |
| 1   | DAT2                 | I/O/PP              | Data Line[bit2]                 | RSV             |                |                           |
| 2   | CD/DAT3 <sup>2</sup> | I/O/PP <sup>3</sup> | Card Detect/<br>Data Line[bit3] | CS              | I <sup>3</sup> | Chip Select (neg<br>true) |
| 3   | CMD                  | PP                  | Command/Response                | DI              | I              | Data In                   |
| 4   | V <sub>DD</sub>      | S                   | Supply voltage                  | V <sub>DD</sub> | S              | Supply voltage            |
| 5   | CLK                  | I                   | Clock                           | SCLK            | I              | Clock                     |
| 6   | V <sub>SS</sub>      | S                   | Supply voltage<br>ground        | V <sub>SS</sub> | S              | Supply voltage<br>ground  |
| 7   | DAT0                 | I/O/PP              | Data Line[bit0]                 | DO              | O/PP           | Data Out                  |
| 8   | DAT1                 | I/O/PP              | Data Line[bit1]                 | RSV             |                |                           |

- (1) S: power supply, I: input; O: output using push-pull drivers; PP: I/O using push-pull drivers
- (2) The extended DAT lines (DAT1-DAT3) are input on power up. They start to operate as DAT lines after SET\_BUS\_WIDTH command. The Host shall keep its own DAT1-DAT3 lines in input mode, as well, while they are not used. It is defined so, in order to keep compatibility to MultiMedia Cards.
- (3) At power up this line has a 50KOhm pull up enabled in the card. This resistor serves two functions: Card detection and Mode Selection. For Mode Selection, the host can drive the line high or let it be pulled high to select SD mode. If the host wants to select SPI mode it should drive the line low. For Card detection, the host detects that the line is pulled high. This pull-up should be disconnected by the user during regular data transfer period, with SET\_CLR\_CARD\_DETECT (ACMD42) command.

## 6. REGISTERS





| Name | Width  | Description                                                                                                                              |
|------|--------|------------------------------------------------------------------------------------------------------------------------------------------|
| CID  | 128bit | Card identification number; card individual number for identification.                                                                   |
| RCA  | 16bit  | Relative card address; local system address of a card, dynamically suggested by the card and approved by the host during initialization. |
| DSR  | 16bit  | Driver Stage Register; to configure the card's output drivers.                                                                           |
| CSD  | 128bit | Card Specific Data; Information about the card operation conditions.                                                                     |
| SCR  | 64bit  | SD Configuration Register; Information about the SD Memory Card's Special Features capabilities                                          |
| OCR  | 32bit  | Operation conditions register.                                                                                                           |
| SSR  | 512bit | SD Status; Information about the card proprietary features.                                                                              |
| OCR  | 32bit  | Card Status; Information about the card status.                                                                                          |

## 7. PHYSICAL DIMENSION



Dimension: 15mm (L) x 11mm (W) x 1mm (H)



| Common Dimensions |       |       |       |       |
|-------------------|-------|-------|-------|-------|
| Symbol            | Min   | Nom   | Max   | Note  |
| A                 | 10.90 | 11.00 | 11.10 |       |
| A1                | 9.60  | 9.70  | 9.80  |       |
| A2                | -     | 3.85  | -     | Basic |
| A3                | 7.60  | 7.70  | 7.80  |       |
| A4                | -     | 1.10  | -     | Basic |
| A5                | 0.75  | 0.80  | 0.85  |       |
| A6                | -     | -     | 8.50  |       |
| A7                | 0.90  | -     | -     |       |
| A8                | 0.60  | 0.70  | 0.80  |       |
| A9                | 0.80  | -     | -     |       |
| A10               | 1.35  | 1.40  | 1.45  |       |
| A11               | 6.50  | 6.60  | 6.70  |       |
| A12               | 0.50  | 0.55  | 0.60  |       |
| A13               | 0.40  | 0.45  | 0.50  |       |
| B                 | 14.90 | 15.00 | 15.10 |       |
| B1                | 6.30  | 6.40  | 6.50  |       |
| B2                | 1.64  | 1.84  | 2.04  |       |
| B3                | 1.30  | 1.50  | 1.70  |       |
| B4                | 0.42  | 0.52  | 0.62  |       |
| B5                | 2.80  | 2.90  | 3.00  |       |
| B6                | 5.50  | -     | -     |       |
| B7                | 0.20  | 0.30  | 0.40  |       |
| B8                | 1.00  | 1.10  | 1.20  |       |
| B9                | -     | -     | 9.00  |       |
| B10               | 7.60  | 7.90  | 8.00  |       |
| B11               | 1.10  | 1.20  | 1.30  |       |
| B12               | 3.60  | 3.70  | 3.80  |       |
| B13               | 2.80  | 2.90  | 3.00  |       |
| B14               | 8.20  | -     | -     |       |
| B15               | -     | -     | 6.20  |       |
| C                 | 0.90  | 1.00  | 1.10  |       |
| C1                | 0.60  | 0.70  | 0.80  |       |
| C2                | 0.20  | 0.30  | 0.40  |       |
| C3                | -     | -     | 0.15  |       |
| D1                | 1.00  | -     | -     |       |
| D2                | 1.00  | -     | -     |       |
| D3                | 1.00  | -     | -     |       |
| R1                | 0.20  | 0.40  | 0.60  |       |
| R2                | 0.20  | 0.40  | 0.60  |       |
| R3                | 0.70  | 0.80  | 0.90  |       |
| R4                | 0.70  | 0.80  | 0.90  |       |
| R5                | 0.60  | 0.80  | 0.90  |       |
| R6                | 0.60  | 0.80  | 0.90  |       |
| R7                | 29.50 | 30.00 | 30.50 |       |
| R10               | -     | 0.20  | -     |       |
| R11               | -     | 0.20  | -     |       |
| R17               | 0.10  | 0.20  | 0.30  |       |
| R18               | 0.20  | 0.40  | 0.60  |       |
| R19               | 0.05  | -     | 0.20  |       |
| R20               | 0.02  | -     | 0.15  |       |

**Notes:**

1. Dimensioning and tolerancing per ASME Y14.5M-1994
2. Dimensions are in millimeters.
3. Coplanarity is additive to C1 Max. thickness

## 8. ORDERING INFORMATION



| Capacity | Part Number     |
|----------|-----------------|
| 128MB    | FDMM128MSE-N100 |
| 256MB    | FDMM256MSE-N100 |
| 512MB    | FDMM512MSE-N100 |

FLEXXON CONFIDENTIAL

## Revision History

| Revision | Release Date | Description   |
|----------|--------------|---------------|
| 1.0      | 2017/10      | First release |

FLEXXON CONFIDENTIAL