



# IM12-02BDS-ZW1

IM Standard

**INDUCTIVE PROXIMITY SENSORS**

**SICK**  
Sensor Intelligence.



### Ordering information

| Type           | Part no. |
|----------------|----------|
| IM12-02BDS-ZW1 | 6020310  |

Other models and accessories → [www.sick.com/IM\\_Standard](http://www.sick.com/IM_Standard)

Illustration may differ



### Detailed technical data

#### Features

|                                            |                           |
|--------------------------------------------|---------------------------|
| <b>Housing</b>                             | Cylindrical thread design |
| <b>Housing</b>                             | Standard design           |
| <b>Thread size</b>                         | M12 x 1                   |
| <b>Diameter</b>                            | Ø 12 mm                   |
| <b>Sensing range <math>S_n</math></b>      | 2 mm                      |
| <b>Safe sensing range <math>S_a</math></b> | 1.62 mm                   |
| <b>Installation type</b>                   | Flush                     |
| <b>Switching frequency</b>                 | 1,500 Hz                  |
| <b>Connection type</b>                     | Cable, 2-wire, 2 m        |
| <b>Output function</b>                     | NO                        |
| <b>Electrical wiring</b>                   | DC 2-wire                 |
| <b>Enclosure rating</b>                    | IP67 <sup>1)</sup>        |

<sup>1)</sup> According to EN 60529.

#### Mechanics/electronics

|                                                |                                   |
|------------------------------------------------|-----------------------------------|
| <b>Supply voltage</b>                          | 10 V DC ... 30 V DC               |
| <b>Ripple</b>                                  | ≤ 10 %                            |
| <b>Voltage drop</b>                            | ≤ 2.8 V <sup>1)</sup>             |
| <b>Time delay before availability</b>          | ≤ 50 ms                           |
| <b>Hysteresis</b>                              | 2 % ... 10 %                      |
| <b>Reproducibility</b>                         | ≤ 5 % <sup>2)</sup> <sup>3)</sup> |
| <b>Temperature drift (of <math>S_r</math>)</b> | ± 10 %                            |
| <b>EMC</b>                                     | According to EN 60947-5-2         |

<sup>1)</sup> At  $I_a$  max.

<sup>2)</sup> Supply voltage  $U_b$  and constant ambient temperature  $T_a$ .

<sup>3)</sup> Of  $S_r$ .

|                                            |                                  |
|--------------------------------------------|----------------------------------|
| <b>Continuous current <math>I_a</math></b> | $\leq 100 \text{ mA}$            |
| <b>Off-state current</b>                   | $\leq 0.8 \text{ mA}$            |
| <b>Minimum load current</b>                | $\geq 3 \text{ mA}$              |
| <b>Cable material</b>                      | PVC                              |
| <b>Conductor size</b>                      | 0.22 mm <sup>2</sup>             |
| <b>Short-circuit protection</b>            | ✓                                |
| <b>Reverse polarity protection</b>         | ✓                                |
| <b>Shock and vibration resistance</b>      | 30 g, 11 ms / 10 ... 55 Hz, 1 mm |
| <b>Ambient operating temperature</b>       | -25 °C ... +70 °C                |
| <b>Housing material</b>                    | Brass, Nickel-plated brass       |
| <b>Sensing face material</b>               | Plastic                          |
| <b>Housing length</b>                      | 60 mm                            |
| <b>Thread length</b>                       | 50 mm                            |
| <b>Tightening torque, max.</b>             | 10 Nm                            |

1) At  $I_a$  max.

2) Supply voltage  $U_b$  and constant ambient temperature  $T_a$ .

3) Of Sr.

#### Safety-related parameters

|                         |           |
|-------------------------|-----------|
| <b>MTTF<sub>D</sub></b> | 192 years |
| <b>DC<sub>avg</sub></b> | 0 %       |

#### Reduction factors

|                                   |                                                |
|-----------------------------------|------------------------------------------------|
| <b>Note</b>                       | The values are reference values which may vary |
| <b>Stainless steel (V2A, 304)</b> | Approx. 0.8                                    |
| <b>Aluminum (Al)</b>              | Approx. 0.35                                   |
| <b>Copper (Cu)</b>                | Approx. 0.3                                    |
| <b>Brass (Br)</b>                 | Approx. 0.5                                    |

#### Installation note

|               |                                       |
|---------------|---------------------------------------|
| <b>Remark</b> | Associated graphic see "Installation" |
| <b>A</b>      | 6 mm                                  |
| <b>B</b>      | 12 mm                                 |
| <b>C</b>      | 12 mm                                 |
| <b>D</b>      | 6 mm                                  |
| <b>E</b>      | 2.4 mm                                |
| <b>F</b>      | 16 mm                                 |


#### Classifications

|                     |          |
|---------------------|----------|
| <b>eCl@ss 5.0</b>   | 27270101 |
| <b>eCl@ss 5.1.4</b> | 27270101 |
| <b>eCl@ss 6.0</b>   | 27270101 |
| <b>eCl@ss 6.2</b>   | 27270101 |
| <b>eCl@ss 7.0</b>   | 27270101 |
| <b>eCl@ss 8.0</b>   | 27270101 |


|                       |          |
|-----------------------|----------|
| <b>eCl@ss 8.1</b>     | 27270101 |
| <b>eCl@ss 9.0</b>     | 27270101 |
| <b>eCl@ss 10.0</b>    | 27270101 |
| <b>eCl@ss 11.0</b>    | 27270101 |
| <b>eCl@ss 12.0</b>    | 27274001 |
| <b>ETIM 5.0</b>       | EC002714 |
| <b>ETIM 6.0</b>       | EC002714 |
| <b>ETIM 7.0</b>       | EC002714 |
| <b>ETIM 8.0</b>       | EC002714 |
| <b>UNSPSC 16.0901</b> | 39122230 |

Installation note

Flush installation




Connection type




Connection diagram

Cd-012



### Dimensional drawing (Dimensions in mm (inch))

IM12, DC, cable, flush



- ① Connection
- ② Display LED
- ③ Fastening nuts (2x); width across 17, metal

### Recommended accessories

Other models and accessories → [www.sick.com/IM\\_Standard](http://www.sick.com/IM_Standard)

|                                                                                     | Brief description                                                                                                            | Type        | Part no. |
|-------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------|-------------|----------|
| Mounting brackets and plates                                                        |                                                                                                                              |             |          |
|    | Mounting plate for M12 sensors, steel, zinc coated, without mounting hardware                                                | BEF-WG-M12  | 5321869  |
|  | Mounting bracket for M12 sensors, steel, zinc coated, without mounting hardware                                              | BEF-WN-M12  | 5308447  |
| Terminal and alignment brackets                                                     |                                                                                                                              |             |          |
|  | Clamping block for round sensors M12, without fixed stop, plastic (PA12), glass-fiber reinforced, mounting hardware included | BEF-KH-M12  | 2051479  |
|                                                                                     | Clamping block for round sensors M12, with fixed stop, plastic (PA12), glass-fiber reinforced, mounting hardware included    | BEF-KHF-M12 | 2051480  |

## SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

**For us, that is “Sensor Intelligence.”**

## WORLDWIDE PRESENCE:

Contacts and other locations –[www.sick.com](http://www.sick.com)