



# WL11-2K2432

## W11-2

SMALL PHOTOELECTRIC SENSORS

**SICK**  
Sensor Intelligence.



Ordering information

| Type        | Part no. |
|-------------|----------|
| WL11-2K2432 | 1054233  |

Other models and accessories → [www.sick.com/W11-2](http://www.sick.com/W11-2)

Illustration may differ



Detailed technical data

Features

|                                 |                                       |
|---------------------------------|---------------------------------------|
| Functional principle            | Photoelectric retro-reflective sensor |
| Functional principle detail     | Dual lens                             |
| Dimensions (W x H x D)          | 15.6 mm x 48.5 mm x 42 mm             |
| Housing design (light emission) | Rectangular                           |
| Sensing range max.              | 0.15 m ... 10 m <sup>1)</sup>         |
| Sensing range                   | 0.15 m ... 8 m <sup>1)</sup>          |
| Focus                           | Approx. 2.2°                          |
| Type of light                   | Visible red light                     |
| Light source                    | LED <sup>2)</sup>                     |
| Light spot size (distance)      | Ø 50 mm (3 m)                         |
| Angle of dispersion             | Approx. 2.2°                          |
| Wave length                     | 640 nm                                |
| Adjustment                      | Single teach-in button                |

<sup>1)</sup> Reflector PL80A.

<sup>2)</sup> Average service life: 100,000 h at T<sub>U</sub> = +25 °C.

## Mechanics/electronics

|                                            |                                                       |
|--------------------------------------------|-------------------------------------------------------|
| <b>Supply voltage <math>U_B</math></b>     | 10 V DC ... 30 V DC <sup>1)</sup>                     |
| <b>Ripple</b>                              | < 5 V <sub>pp</sub> <sup>2)</sup>                     |
| <b>Current consumption</b>                 | 30 mA <sup>3)</sup>                                   |
| <b>Switching output</b>                    | PNP                                                   |
| <b>Output function</b>                     | Complementary                                         |
| <b>Switching mode</b>                      | Light/dark switching                                  |
| <b>Signal voltage PNP HIGH/LOW</b>         | U <sub>v</sub> - 2.5 V / approx. 0 V                  |
| <b>Output current <math>I_{max}</math></b> | ≤ 100 mA                                              |
| <b>Response time</b>                       | ≤ 2.5 ms <sup>4)</sup>                                |
| <b>Switching frequency</b>                 | 200 Hz <sup>5)</sup>                                  |
| <b>Connection type</b>                     | Male connector M12, 4-pin                             |
| <b>Circuit protection</b>                  | A <sup>6)</sup><br>C <sup>7)</sup><br>D <sup>8)</sup> |
| <b>Protection class</b>                    | II <sup>9)</sup>                                      |
| <b>Weight</b>                              | 120 g                                                 |
| <b>Polarisation filter</b>                 | ✓                                                     |
| <b>Housing material</b>                    | Plastic, ABS                                          |
| <b>Optics material</b>                     | Plastic, PMMA                                         |
| <b>Enclosure rating</b>                    | IP66<br>IP67<br>IP69K                                 |
| <b>Ambient operating temperature</b>       | -30 °C ... +60 °C                                     |
| <b>Ambient temperature, storage</b>        | -40 °C ... +75 °C                                     |
| <b>UL File No.</b>                         | NRKH.E181493 & NRKH7.E181493                          |

<sup>1)</sup> Limit values when operated in short-circuit protected network: max. 8 A.

<sup>2)</sup> May not exceed or fall below U<sub>v</sub> tolerances.

<sup>3)</sup> Without load.

<sup>4)</sup> Signal transit time with resistive load.

<sup>5)</sup> With light/dark ratio 1:1.

<sup>6)</sup> A = V<sub>S</sub> connections reverse-polarity protected.

<sup>7)</sup> C = interference suppression.

<sup>8)</sup> D = outputs overcurrent and short-circuit protected.

<sup>9)</sup> Reference voltage DC 50 V.

## Safety-related parameters


|                                     |             |
|-------------------------------------|-------------|
| <b>MTTF<sub>D</sub></b>             | 1,625 years |
| <b>DC<sub>avg</sub></b>             | 0 %         |
| <b>T<sub>M</sub> (mission time)</b> | 20 years    |

## Classifications

|                     |          |
|---------------------|----------|
| <b>eCl@ss 5.0</b>   | 27270902 |
| <b>eCl@ss 5.1.4</b> | 27270902 |
| <b>eCl@ss 6.0</b>   | 27270902 |

|                       |          |
|-----------------------|----------|
| <b>eCl@ss 6.2</b>     | 27270902 |
| <b>eCl@ss 7.0</b>     | 27270902 |
| <b>eCl@ss 8.0</b>     | 27270902 |
| <b>eCl@ss 8.1</b>     | 27270902 |
| <b>eCl@ss 9.0</b>     | 27270902 |
| <b>eCl@ss 10.0</b>    | 27270902 |
| <b>eCl@ss 11.0</b>    | 27270902 |
| <b>eCl@ss 12.0</b>    | 27270902 |
| <b>ETIM 5.0</b>       | EC002717 |
| <b>ETIM 6.0</b>       | EC002717 |
| <b>ETIM 7.0</b>       | EC002717 |
| <b>ETIM 8.0</b>       | EC002717 |
| <b>UNSPSC 16.0901</b> | 39121528 |


### Dimensional drawing (Dimensions in mm (inch))



- ① Optical axis, sender
- ② Optical axis, receiver
- ③ LED indicator yellow: Status of received light beam
- ④ LED indicator green: Supply voltage active
- ⑤ Mounting hole ø 4.2 mm
- ⑥ Male connector M12, 4-pin
- ⑦ Mounting hole ø 4.2 mm


## Adjustments

Teach-in




- ② LED indicator yellow: Status of received light beam
- ③ Green LED indicator: power on, teach-in mode I Blue LED indicator: teach-in mode II
- ⑥ Single teach-in button, Function 1: teach-in sensitivity on reflector, Function 2: change operation/teach-in mode

## Connection type




## Connection diagram

Cd-101




Characteristic curve



- ① Reflector PL80A
- ② Reflector C110A
- ③ Reflector PL50A
- ④ Reflector PL40A
- ⑤ Reflector PL30A
- ⑥ Reflector PL20A
- ⑦ Reflective tape Diamond Grade

Sensing range diagram



■ Sensing range      ■ Sensing range typ. max.

- ① Reflector PL80A
- ② Reflector C110A
- ③ Reflector PL50A
- ④ Reflector PL40A
- ⑤ Reflector PL30A
- ⑥ Reflector PL20A
- ⑦ Reflective tape Diamond Grade

## Recommended accessories

Other models and accessories → [www.sick.com/W11-2](http://www.sick.com/W11-2)

|                                                                                   | Brief description                                                                                                                     | Type               | Part no. |
|-----------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------|--------------------|----------|
| Mounting brackets and plates                                                      |                                                                                                                                       |                    |          |
|  | Mounting bracket, large, stainless steel, mounting hardware included                                                                  | BEF-WG-W12         | 2013942  |
|  | Universal mounting bracket for reflectors, steel, zinc coated                                                                         | BEF-WN-REFX        | 2064574  |
| Plug connectors and cables                                                        |                                                                                                                                       |                    |          |
|  | Head A: female connector, M12, 4-pin, straight, A-coded<br>Head B: Flying leads<br>Cable: Sensor/actuator cable, PVC, unshielded, 5 m | YF2A14-050VB3XLEAX | 2096235  |
|  | Head A: male connector, M12, 4-pin, straight<br>Cable: unshielded                                                                     | STE-1204-G         | 6009932  |
| Reflectors                                                                        |                                                                                                                                       |                    |          |
|  | Rectangular, screw connection, 40 mm x 60 mm, PMMA/ABS, Screw-on, 2 hole mounting                                                     | PL40A              | 1012720  |

## SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is “Sensor Intelligence.”

## WORLDWIDE PRESENCE:

Contacts and other locations –[www.sick.com](http://www.sick.com)