





FEATURES

- P.C. board mountable
- Low cost
- Rugged design
- Solderable leads
- Versatile
- Available on tape and reel
- .1 inch to .4 inch diameter
- Res values from 100 Ω to 100K Ω
- Tinned copper leads

DISC Thermistors are ideally suited for low cost applications with a maximum temperature of 150° C. They lend themselves to be P.C. board mounted. Other lead styles available upon request.

DISC THERMISTORS * 10% Tolerance @ 25° C								
Resis. at 25° C (Ohms)	R-T Curve	Part Number	Fig.	D.C. (min.)	T.C. (max.)	Lead Dia.	Lead Spacing	D
500	10	140-501FAG-RB1 ①	1	3	10	.016	.1	.1
500	10	142-501FAG-RB1	2	3	10	.016	.1	.15
1,000	10	140-102FAG-RB1 ①	1	4	10	.016	.1	.1
1,000	10	142-102FAG-RB1	2	4	10	.016	.1	.15
3,000	16	140-302LAG-RB1 ①	1	3	10	.016	.1	.1
3,000	16	142-302LAG-RB1	2	3	10	.016	.1	.15
5,000	16	140-502LAG-RB1 ①	1	4	10	.016	.1	.1
5,000	16	142-502LAG-RB1	2	4	10	.016	.1	.15
10,000	16	140-103LAG-RB1 ①	1	4	10	.016	.1	.1
10,000	16	142-103LAG-RB1 ①	2	4	10	.016	.1	.15
50,000	1	140-503QAG-RB1	1	3	10	.016	.1	.1
50,000	1	142-503QAG-RB1	2	3	10	.016	.1	.15
100,000	1	140-104QAG-RB1 ①	1	3	10	.016	.1	.1
100,000	1	142-104QAG-RB1	2	3	10	.016	.1	.15
100	10	143-101FAG-RC1 ①	1	4	16	.020	.2	.2
100	10	145-101FAG-RC1 ①	2	4	16	.020	.2	.25
200	10	143-201FAG-RC1 ①	1	5	18	.020	.2	.2
200	10	145-201FAG-RC1	2	5	18	.020	.2	.25
300	10	143-301FAG-RC1 ①	1	6	20	.020	.2	.2
300	10	145-301FAG-RC1	2	6	20	.020	.2	.25
500	10	143-501FAG-RC1 ①	1	6	25	.020	.2	.2
500	10	145-501FAG-RC1	2	6	25	.020	.2	.25
1,000	16	143-102LAG-RC1 ①	1	6	20	.020	.2	.2
1,000	16	145-102LAG-RC1 ①	2	6	20	.020	.2	.25
3,000	16	143-302LAG-RC1 ①	1	6	22	.020	.2	.2
3,000	16	145-302LAG-RC1	2	6	22	.020	.2	.25
5,000	16	143-502LAG-RC1 ①	1	7	35	.020	.2	.2
5,000	16	145-502LAG-RC1	2	7	35	.020	.2	.25
10,000	1	143-103QAG-RC1 ①	1	4	20	.020	.2	.2
10,000	1	145-103QAG-RC1	2	4	20	.020	.2	.25
30,000	1	143-303QAG-RC1 ①	1	6	25	.020	.2	.2
30,000	1	145-303QAG-RC1	2	7	28	.020	.2	.25
50,000	1	143-503QAG-RC1 ①	1	7	30	.020	.2	.2
50,000	1	145-503QAG-RC1	2	8	32	.020	.2	.25

* Also offered in 1,2,5 and 20% tolerances.

① = Distributor item