


PNOZ X2.8P 24VACDC 3n/o 1n/c

777301



Safety relay (standalone), inputs: 1/2-channel wiring with/without detection of shorts across contacts, outputs: 3 N/O, 1 N/C, automatic/manual start, UB 24 V AC/DC, width: 22.5 mm, plug-in screw terminals, monitoring of E-STOP, safety gates.

Technical details

General data

Approval: CCC, CE, UKCA, cULus Listed, KOSHA, EAC (Eurasian), TÜV

Technical data

Environment

RoHS directive: 2011/65/EU, 2015/863/EU

RoHS conformity: 0

RoHS exceptions: 0

RoHS except.s acc. to direct.: 7A, 6C, 7C I

REACH compliance: 1

REACH included substances: Blei, Bleioxid

%-part of the pollutant: > 0,1

CAS No.: 7439-92-1, 1317-36-8

SCIP entry available: yes

WEEE classification (08/2018): U_KATEGORIE_5

Commercial data

ECLASS version: ECLASS-13

ECLASS Reference Feature: 27371819

ETIM Version: ETIM-9.0

ETIM Reference Group: EG000019

ETIM Reference Feature: EC001449

UNSPSC 25:	39122331
GTIN:	4046548009897
Volume:	0.301
Harmonized System Code:	85364900
Type of tariff number:	TARIC
Use of customs tariff number:	export, Import
Quantity per packaging unit:	1

Optional accessories

374280

PNOZ X Set plug in screw terminals P1+P2

