


DURACELL®

Zinc/Monovalent Silver Oxide Watch Battery
0% Mercury

D303/D357

Zn/Ag₂O




Diameter: 11.60 mm
Height: 5.40 mm

Specifications

Classification:	Silver
Chemical System:	Zinc/Monovalent Silver Oxide, high drain (Zn/Ag ₂ O)
Designation:	ANSI-1131SO, IEC-SR44
Nominal Voltage:	1.55V
Self Discharge:	Less than 10% per year at 20°C
Operating Temp:	0°C - 60°C
Typical Weight:	~2.09 g
Capacity:	*170 mAh, Discharge over 6.8 kΩ at 20°C to 0.9V

Discharge Curve



Constant Load: 6.8 kΩ
Starting Drain: 229 μA
Temperature: 20°C

DURACELL®

BATTERIES

Berkshire Corporate Park
Bethel, CT 06801 U.S.A.
Telephone: Toll free 1.800.544.5454
Internet: www.duracell.com

*Delivered capacity is dependent on the applied load, intermittent usage, operating temperature and cut off voltage. Please refer to the charts and discharge data for examples of energy/service life that the battery will provide for various conditions.

Information and contents in this data sheet are for reference purposes only. They do not constitute any warranty and representation is subject to change without notice. For most current information and further details, please contact Duracell.