


Home > Product Overview > External Antennas > GNSS > TS.07.0113W



 Need help or have a question?
Click here to chat.





7.0113 GPS/GLONASS/GALILEO/BeiDou Antenna Hinged SMA(M)

Passive GPS/GLONASS/GALILEO/BeiDou Monopole Terminal Antenna

Gain BeiDou 4.05dBi / GPS-GALILEO 4.04dBi / GLONASS 3.98dBi (30*30cm metal Ground Plane edge)

Efficiency BeiDou 73.2% / GPS-GALILEO 72.35% / GLONASS 70.81%(30*30cm metal Ground Plane edge)

Rotatable hinge design for optimal reception

SMA(M) Hinged Connector

Dims: H: 72mm, Ø: 10mm

[Buy Now](#)

[Get Quote](#)

[Request Sample](#)

[Datasheet](#)

Description

Technical Specification

Technical Specification

Name	Value
Antenna Type	<u>EXTERNAL ANTENNAS</u> , <u>GNSS</u>
Impedance	50
Minimum Operating Temperature	-40°C
Maximum Operating Temperature	85°C
Mounting Style	Terminal
Termination Style	Connector
Antenna Connector Type	SMA

Name	Value
Connector Body Style	Hinged
Polarity	Linear
Frequency Range	1559 - 1610MHz
Connector Polarity	Normal
Cable Length (mm)	n/a
Packaging	PE Bag, Carton
VSWR	0
RoHS	Yes
Gain (Max)	4
GNSS Type	Passive GNSS
GNSS Bands	L1
Length (mm)	10
Width (mm)	10
Height (mm)	72
Weight (g)	6

Related Products

SMA Straight PCB Mount, Jack, Gold, 50Ω, Surface Mount 1MM Leg Length