

SPECIFICATIONS

1.General Specifications

Model	POLE22-0100AT	POLE22-0300AT	POLE22-0500AT	POLE22-0800AT	POLE22-1000AT
Applicable Models	List in the website http://www.patlite.com/				
Applicable Optional Parts					
Mounting Location	Indoor Only				
Mass (Tolerance $\pm 10\%$)	0.05kg	0.15kg	0.26kg	0.42kg	0.52kg
	(No Accessories)				
Outer Dimensions	Refer to the 3.Outer Dimensions				
Remarks	There are no contents of controlled substances exceeding the threshold for the RoHS				

2.Model Number Configuration

Model	Pole length
POLE	POLE22
-	↓
AT	

Pole length
0100 100mm
0300 300mm
0500 500mm
0800 800mm
1000 1000mm

3.Outer Dimensions

POLE22-□AT

(Unit:mm)

POLE22-0100AT : 100
POLE22-0300AT : 300
POLE22-0500AT : 500
POLE22-0800AT : 800
POLE22-1000AT : 1000

Effective Length of Screw(32)

Color : Silver

No.	Name	Material
1	Pole	AL
2	Rubber Bushing	EPR

Accessory
Hexagon Nut(M22) 2pcs.
Plain Washer(ϕ 22 Inside Diameter) 2pcs.
Binding Head Tapping Screw(M3 $\times$ 12) 2pcs.

POLE22-0300AT-W18C

PATLITE Corporation